

# Printed-circuit board connector - PC 16/ 4-STF-SH-10,16 BKBD SWHL - 1703253

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



PCB connector, nominal current: 76 A, number of positions: 4, pitch: 10.16 mm, connection method: Screw connection with tension sleeve, color: black, contact surface: Silver

The figure shows a 4-pos. version of the product

## Your advantages

- ✓ Well-known connection principle allows worldwide use
- ✓ Low temperature rise, thanks to maximum contact force
- ✓ Allows connection of two conductors
- ✓ Integrated double steel spring provides additional safety in the event of temperature and power fluctuations
- ✓ Shield for adherence to the EMC requirements and an optional strain relief
- ✓ Screwable flange for superior mechanical stability
- ✓ Integrated protective guide prevents incorrect insertion of the conductor underneath the tension sleeve



## Key Commercial Data

|                        |                                                                                      |
|------------------------|--------------------------------------------------------------------------------------|
| Packing unit           | 50 pc                                                                                |
| Minimum order quantity | 100 pc                                                                               |
| GTIN                   |  |
| GTIN                   | 4046356651356                                                                        |

## Technical data

### Dimensions

|              |          |
|--------------|----------|
| Length [ l ] | 89.8 mm  |
| Width [ w ]  | 58.4 mm  |
| Height [ h ] | 29.1 mm  |
| Pitch        | 10.16 mm |
| Dimension a  | 30.48 mm |

# Printed-circuit board connector - PC 16/ 4-STF-SH-10,16 BKBD SWHL - 1703253

## Technical data

### General

|                                  |                                      |
|----------------------------------|--------------------------------------|
| Range of articles                | PC 16/...STF-SH                      |
| Number of positions              | 4                                    |
| Connection method                | Screw connection with tension sleeve |
| Rated voltage (III/3)            | 1000 V                               |
| Connection in acc. with standard | EN-VDE                               |
| Nominal current $I_N$            | 76 A                                 |
| Nominal cross section            | 16 mm <sup>2</sup>                   |

### Connection data

|                                                                                         |                      |
|-----------------------------------------------------------------------------------------|----------------------|
| Conductor cross section solid min.                                                      | 0.75 mm <sup>2</sup> |
| Conductor cross section solid max.                                                      | 16 mm <sup>2</sup>   |
| Conductor cross section flexible min.                                                   | 0.75 mm <sup>2</sup> |
| Conductor cross section flexible max.                                                   | 16 mm <sup>2</sup>   |
| Conductor cross section flexible, with ferrule without plastic sleeve min.              | 0.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule without plastic sleeve max.              | 16 mm <sup>2</sup>   |
| Conductor cross section flexible, with ferrule with plastic sleeve min.                 | 0.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule with plastic sleeve max.                 | 10 mm <sup>2</sup>   |
| Conductor cross section AWG min.                                                        | 18                   |
| Conductor cross section AWG max.                                                        | 6                    |
| 2 conductors with same cross section, solid min.                                        | 0.75 mm <sup>2</sup> |
| 2 conductors with same cross section, solid max.                                        | 6 mm <sup>2</sup>    |
| 2 conductors with same cross section, stranded min.                                     | 0.75 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded max.                                     | 6 mm <sup>2</sup>    |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.   | 0.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.   | 4 mm <sup>2</sup>    |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 6 mm <sup>2</sup>    |

### Standards and Regulations

|                                  |        |
|----------------------------------|--------|
| Connection in acc. with standard | EN-VDE |
|                                  | CUL    |

### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1                                                                                      |
| China RoHS | Environmentally Friendly Use Period = 50                                                            |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

# Printed-circuit board connector - PC 16/ 4-STF-SH-10,16 BKBD SWHL - 1703253

## Approvals

### Approvals

#### Approvals

IECEE CB Scheme / SEV / EAC / cULus Recognized

#### Ex Approvals

### Approval details

|                    |                                                                                   |                                                           |         |
|--------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------|---------|
| IECEE CB Scheme    |  | <a href="http://www.iecee.org/">http://www.iecee.org/</a> | CH-8077 |
| Nominal voltage UN | 1000 V                                                                            |                                                           |         |
| Nominal current IN | 76 A                                                                              |                                                           |         |

|                    |                                                                                     |                                                                                                                                                     |         |
|--------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| SEV                |  | <a href="https://www.electrosuisse.ch/de/meta/shop/produktezertifikate.html">https://www.electrosuisse.ch/de/meta/shop/produktezertifikate.html</a> | IK-3431 |
| Nominal voltage UN | 1000 V                                                                              |                                                                                                                                                     |         |
| Nominal current IN | 76 A                                                                                |                                                                                                                                                     |         |
| mm²/AWG/kcmil      | 16                                                                                  |                                                                                                                                                     |         |

|     |                                                                                     |         |  |
|-----|-------------------------------------------------------------------------------------|---------|--|
| EAC |  | B.01742 |  |
|-----|-------------------------------------------------------------------------------------|---------|--|

|                    |                                                                                     |                                                                                                                                                       |                 |
|--------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| cULus Recognized   |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E60425-20040202 |
|                    | B                                                                                   | C                                                                                                                                                     |                 |
| Nominal voltage UN | 600 V                                                                               | 600 V                                                                                                                                                 |                 |
| Nominal current IN | 55 A                                                                                | 55 A                                                                                                                                                  |                 |
| mm²/AWG/kcmil      | 20-6                                                                                | 20-6                                                                                                                                                  |                 |

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9