



Features

- Small diameter
- Wide resistance range
- Good resolution
- Linear tapers
- Cermet element

3862 - 1/2 " Diameter Single-Turn Panel Control

Initial Electrical Characteristics¹

Standard Resistance Range.....	1K ohms to 1 megohm
Total Resistance Tolerance.....	(A Taper) $\pm 10\%$ (H Taper) $\pm 5\%$
Independent Linearity.....	$\pm 5\%$
Absolute Minimum Resistance.....	2 ohms maximum
Effective Electrical Angle.....	$260^\circ \pm 10^\circ$
Contact Resistance Variation.....	$\pm 3\%$ or 6 ohms (whichever is greater)
Dielectric Withstanding Voltage (MIL-STD-202, Method 301)	
Sea Level.....	750 VAC minimum
70,000 Feet.....	350 VAC minimum
Insulation Resistance (500 VDC).....	1,000 megohms minimum
Power Rating (Voltage Limited by Power Dissipation or 350 VAC, Whichever is Less)	
+70 °C.....	1 watt
+125 °C.....	0 watt
Theoretical Resolution.....	Essentially infinite

Environmental Characteristics¹

Operating Temperature Range.....	-40 °C to +125 °C
Storage Temperature Range.....	-65 °C to +125 °C
Temperature Coefficient Over Storage Temperature Range.....	± 150 ppm/°C
Vibration.....	20 G
Total Resistance Shift.....	$\pm 2\%$ maximum
Voltage Ratio Shift.....	$\pm 6\%$ maximum
Shock.....	50 G
Total Resistance Shift.....	$\pm 2\%$ maximum
Voltage Ratio Shift.....	$\pm 6\%$ maximum
Load Life.....	1,000 hours
Total Resistance Shift.....	$\pm 3\%$ maximum
Rotational Life, No Load	
(C & N Bushings).....	50,000 cycles
(E & T Bushings).....	1,000 cycles
Total Resistance Shift.....	$\pm 5\%$ maximum
Contact Resistance Variation.....	$\pm 3\%$ or 6 ohms (whichever is greater)
Moisture Resistance (MIL-STD-202, Method 106, Condition B)	
Total Resistance Shift.....	$\pm 2\%$ maximum
Insulation Resistance (500 VDC).....	100 megohms minimum
Salt Spray.....	MIL-STD-202, Method 101, Condition A
IP Rating.....	IP 40

Mechanical Characteristics¹

Stop Strength.....	33 N-cm (3 lb.-in.) maximum
Mechanical Angle.....	$295^\circ \pm 3^\circ$
Torque	
Starting and Running.....	3.53 N-cm (5 oz.-in.) maximum
Mounting (Torque on Bushing).....	1.7-2.0 N-m (15-18 lb.-in.) maximum
Shaft Locking Torque with Locking Bushings.....	14.12 N-cm (20 oz.-in.)
Weight (Single Section).....	25 grams maximum
Terminals.....	Printed circuit pins or J-Hooks
Soldering Condition.....	Recommended hand soldering using Sn85/Ag5 no clean solder, 0.025 " wire diameter Maximum temperature 399 °C (750 °F) for 3 seconds. No wash process to be used with no clean flux. Part can be wave soldered at 260 °C (500 °F) for 5 seconds, no wash process with no clean flux.
Marking.....	Manufacturer's trademark, wiring diagram, date code, resistance, manufacturer's part number
Ganging.....	1 cup maximum
Hardware.....	One lockwasher and one mounting nut is shipped with each potentiometer, except where noted in the part number.

¹ AT ROOM AMBIENT: +25 °C NOMINAL AND 50 % RELATIVE HUMIDITY NOMINAL, EXCEPT AS NOTED.

*RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.


Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.

Users should verify actual device performance in their specific applications.

BOURNS®

PANEL LAYOUT



3862E/T

Technical drawing of a bushing with the following dimensions and tolerances:

- Overall length: $15.88 \pm .015$ (STD.)
- Top flange outer diameter: $11.51 \pm .41$ (.453 $\pm$.016)
- Top flange thickness: $12.07 \pm .76$ (.475 $\pm$.030)
- Top flange inner diameter: $12.7 \pm .41$ (.500 $\pm$.016)
- Top flange hole diameter: 6.25 (1/4)
- Thread: $\text{32 UNEF} \times 2\text{A}$
- Position of slots: VARIABLE
- Length L: 9.53 (.375) FOR "T" BUSHING, 12.7 (.500) FOR "E" BUSHING
- Bottom flange outer diameter: $3.18 \pm .03$ (.125 $\pm$.001) DIA.
- Bottom flange thickness: $.79$ (.031)
- Bottom flange hole diameter: $.79 \pm .25$ (.031 $\pm$.010)
- Bottom flange hole angle: $45^\circ \pm 5^\circ \times$


Technical drawing of a shaft-hub assembly. The drawing shows a shaft with a 32 UNEF-2A thread and a hub with a corresponding internal thread. Dimensions and tolerances are provided for various parts of the assembly.

Dimensions and Tolerances:

- 11.51 ± .41 (453 ± .016)
- 17 ± .76 (± .030)
- DIA. 12.7 ± .41 (500 ± .016)
- 6.25 (1/4)
- 32 UNEF-2A
- OPTIONAL FLAT
- FROM BUSHING FOR SHAFTS UNDER
- L = 6.35 (250) FOR "C" BUSHING, 9.65 (380) FOR "N" BUSHING
- 6.35 (250)
- LONG OR
- 3.3 (13)
- 6.88 (5/8)
- 7.9 ± .25 (0.031 ± .010)
- 45° ± 5° X .41 (0.016)
- 7.9 (0.031)
- 3.18 ± .03 (0.125 ± .001) DIA.
- 2.38 (0.094)
- 2 PLCS.
- .89 ± .25 (0.035 ± .010)
- (3/8, 7/8) STD.

$45 \pm 15^\circ$
 $\frac{2.31}{(.091)} 2 \text{ PLCS.}$
 $\frac{.25}{(.010)} 2 \text{ PLCS.}$
 $\frac{6.22}{(.245)} 2 \text{ PLCS.}$
 $32\text{-}1/2^\circ \pm 10^\circ$
 FLAT ORIENTATION
 @ CCW END
 SLOTS ARE
 NOT ORIENTED
 C OF LUG

Figure 1 shows the dimensions of the 100-pin DIP package. The top view includes dimensions for pin pitch (2.54 mm / .10 in), pin width (1.27 mm / .05 in), and pin spacing (2.286 mm / .09 in). The side view shows the package height (8.89 mm / .35 in) and the maximum pin length (6.35 mm / .250 in).




Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time. Users should verify actual device performance in their specific applications.

How to Order 3862 Series Panel Controls

BOURNS®



Boldface features are Bourns standard options. All others are available with higher minimum order quantities.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9