

## Isobar 6-Outlet Surge Protector, 6-ft. Cord, 2850 Joules, Tel/Coax/Modem Protection

MODEL NUMBER: ISOBAR6DBS



### Description

Tripp Lite's ISOBAR6DBS Isobar Home/Business Theater Surge Suppressor provides premium protection--2850 joules--stopping damaging surges and filtering disruptive line noise so components perform at their peak! You can see and hear the difference: sharper, crisper video; deeper, fuller audio and longer component life spans. Perfect for small-to-medium home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more. Exclusive Isolated Filter Banks eliminate noise interference between components. 6 outlets (with transformer spacing and plug-in safety covers), 2-line 2.2 GHz gold coaxial protection and 1-line tel/modem protection safeguard an entire home/business theater system. \$250,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only). Includes all-metal housing, three diagnostic LEDs, 6-ft. cord with a right-angle plug, 6-ft. coaxial cable and 6-ft. phone cord.

### Features

- 2850 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)
- \$250,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only) covers connected components against surge damage...for life!
- Isolated Filter Banks eliminate interference between connected components
- All-metal housing safely withstands the strongest surges
- 6 surge-protected NEMA 5-15R AC outlets safeguard an entire home/business theater system
- Widely spaced outlets accommodate up to 3 transformers
- Four plug-in safety covers protect against accidental contact
- 2 sets of 2.2GHz gold coaxial protection to safeguard components on cable, satellite or antenna line (includes 6-ft gold coax cable)
- 1-line tel/modem surge protection (with included 6-ft. phone cord) safeguards personal video recorders (PVRs) on a single dial-up line.
- 6-ft. cord with right-angle NEMA 5-15P plug provides convenient location anywhere within a home/business theater system
- 3 diagnostic LEDs alert user to protection, line power and fault status
- Keyhole slots provide convenient wall or cabinet mounting
- Illuminated master switch provides one-touch power control over all components. Circuit breaker protects against dangerous system overload

### Highlights

- 6 outlets / 6-ft. cord
- 2850 joule rating
- Isolated Filter Banks / all-metal housing
- 2-line 2.2 GHz gold coaxial protection
- 1-line tel/modem surge protection
- \$250,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

### Applications

- Perfect for small-to-medium home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more

### Package Includes

- ISOBAR6DBS Home/Business Theater Surge Suppressor
- 6 ft. gold coaxial cable
- 6 ft. phone cord
- Instruction manual with warranty information



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

- All-metal housing (black) stands up to the most demanding environments
- UL and cUL listed

## Specifications

| OUTPUT                             |                                                                                     |
|------------------------------------|-------------------------------------------------------------------------------------|
| Frequency Compatibility            | 50 / 60 Hz                                                                          |
| Output Receptacles                 | (6) 5-15R                                                                           |
| Output (Watts)                     | 1440                                                                                |
| Circuit Breaker (amps)             | 12                                                                                  |
| Transformer Accommodation          | Accommodates 3 transformers                                                         |
| USB Charging                       | No                                                                                  |
| INPUT                              |                                                                                     |
| Nominal Input Voltage(s) Supported | 120V AC                                                                             |
| Recommended Electrical Service     | 120V (110-125V)                                                                     |
| Input Connection Type              | NEMA 5-15P                                                                          |
| Input Plug Features                | Space-saving right angle input plug                                                 |
| Input Cord Length (ft.)            | 6                                                                                   |
| Input Cord Length (m)              | 1.8                                                                                 |
| Input Cord Gauge Type              | 14 gauge, SJT                                                                       |
| Voltage Compatibility (VAC)        | 120                                                                                 |
| Maximum Surge Amps                 | 135000                                                                              |
| USER INTERFACE, ALERTS & CONTROLS  |                                                                                     |
| Switches                           | Combination AC circuit breaker and two position red illuminated on/off power switch |
| Diagnostic LEDs                    | PROTECTION PRESENT (green), LINE FAULT (red) and LINE OK (green)                    |
| SURGE / NOISE SUPPRESSION          |                                                                                     |
| AC Suppression Joule Rating        | 2850                                                                                |
| AC Suppression Response Time       | NM = 0 ns. CM = <1 ns                                                               |
| Protection Modes                   | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression  |
| Clamping Voltage (RMS)             | 140V                                                                                |
| UL1449 Let Through Rating          | 330V - UL verified                                                                  |
| EMI / RFI Filtering                | Up to 40 dB40-80 dB                                                                 |
| DATALINE SURGE SUPPRESSION         |                                                                                     |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

|                                                      |                                                                                            |
|------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Telephone/DSL Protection                             | Yes                                                                                        |
| Telephone/DSL Protection Details                     | 1 line                                                                                     |
| Cable (Coax) Protection                              | Yes                                                                                        |
| Cable (Coax) Protection Details                      | 2 line                                                                                     |
| Network (Ethernet) Protection                        | No                                                                                         |
| <b>PHYSICAL</b>                                      |                                                                                            |
| Shipping Dimensions (hwd / in.)                      | 3 x 11.5 x 7                                                                               |
| Shipping Dimensions (hwd / cm)                       | 7.62 x 29.2 x 17.8                                                                         |
| Shipping Weight (lbs.)                               | 3.6                                                                                        |
| Shipping Weight (kg)                                 | 1.6                                                                                        |
| Unit Dimensions (hwd / in.)                          | 2.5 x 9 x 3.5                                                                              |
| Unit Dimensions (hwd / cm)                           | 6.35 x 22.9 x 8.9                                                                          |
| Unit Weight (lbs.)                                   | 2.8                                                                                        |
| Unit Weight (kg)                                     | 1.27                                                                                       |
| Material of Construction                             | Metal                                                                                      |
| Integrated Keyhole Mounting Tabs                     | Keyhole mounting slots allow desk or wall mounting                                         |
| Housing Color                                        | Black                                                                                      |
| Receptacle Color                                     | Black                                                                                      |
| Color (AC Line Cord)                                 | Black                                                                                      |
| Outlets Measurement (Center to Center)               | Distance between horizontal outlets = 39.45mm; Distance between vertical outlets = 39.30mm |
| Keyhole Slot Mounting Measurement (Center to Center) | Distance between horizontal tabs = 210.79mm; Distance between vertical tabs = 58.17mm      |
| Metal Case                                           | Yes                                                                                        |
| <b>SPECIAL FEATURES</b>                              |                                                                                            |
| Right-Angle Plug                                     | Yes                                                                                        |
| <b>CERTIFICATIONS</b>                                |                                                                                            |
| UL1449 3rd Edition (AC Suppression)                  | UL1449                                                                                     |
| UL1363 (Power Tap)                                   | UL1363UL1363                                                                               |
| UL497A (Communications)                              | UL497A                                                                                     |
| FCC Part 68 (Communications)                         | FCC PFCC Part 68art 68                                                                     |
| cUL / CSA (Canada)                                   | cULcUL                                                                                     |
| Approvals                                            | Exceeds IEEE 587 category A&B specifications                                               |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

| WARRANTY                                                   |                                                       |
|------------------------------------------------------------|-------------------------------------------------------|
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty                             |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$250,000 <a href="#">Ultimate Lifetime Insurance</a> |

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9