



8		7	
THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION	
© COPYRIGHT 2011		2011	
BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.			
ATLANTIC VERSION TERMINATOR INTERFACE ADAPTER	PART NUMBER	REVISION	DESCRIPTION
	2150016-1	J	FINE CRIMP HEIGHT ADJUST
	2150016-2	J	FINE CRIMP HEIGHT ADJUST
	2150016-5	J	FINE CRIMP HEIGHT ADJUST
	2150016-6	J	NON-CRIMP HEIGHT ADJUST
	2150016-7	J	FINE CRIMP HEIGHT ADJUST
	7-2150016-7	H	CRIMP TOOLING KIT

APPLICATOR DATA		
CRIMP	SIZE	TYPE
WIRE	2.79 mm [.110]	F
INSUL	4.57 mm [.180]	F
APPLICATOR INSTRUCTIONS		
408-10390		

TERMINAL DATA: TE TERMINAL		TE CRIMP SPECIFICATION	
TERMINAL NAME: RECEPTACLE, FASTON .250 SERIES			
WIRE STRIP LENGTH		INSULATION DIAMETER RANGE	
6.00-6.80 mm [.236-.268 IN]		Ø3.05-4.31 mm [.120-.170 IN]	
TERMINAL APPLICATION SPECIFICATION		114-2036	
TERMINALS APPLIED			
TE TERMINAL		TE TERMINAL	
63306-1		60713-1	
63306-2		60713-2	
42400-1		350981-2	
42400-2		42219-1	
42400-3		42219-2	
1742198-1		154692-1	

WIRE SIZE	CRIMP HEIGHT mm [INCH]	CRIMP HEIGHT REFERENCE SETTING
14 AWG	1.85+/-0.05 [0.073+/-0.002]	7.5
(1)18 & (1)16	1.85+/-0.05 [0.073+/-0.002]	7.5
(2)18	1.73+/-0.05 [0.068+/-0.002]	9.0
16 OR (1)20 & (1)18	1.63+/-0.05 [0.064+/-0.002]	10.0
18 AWG	1.47+/-0.05 [0.058+/-0.002]	11.7



- 1 RECOMMENDED SPARE PARTS
- 2 GREASE BEARING SURFACES LIGHTLY
3. LUBRICATE DAILY PER THE APPLICATOR INSTRUCTION SHEET SUPPLIED WITH THE APPLICATOR.
- 4 APPLICATOR SPECIFIC DATA TO BE ENTERED INTO BLANK MEMORY CHIP AT ASSEMBLY. SEE BELOW FOR PART NUMBER:
MECHANICAL FEED WITH "SMART APPLICATOR" CONVERSION: 8-2150016-4
PNEUMATIC FEED WITH "SMART APPLICATOR" CONVERSION: 8-2150016-4
SERVO FEED WITH "FINE CRIMP HEIGHT ADJUST": 8-2150016-5
SERVO FEED WITH "NON-CRIMP HEIGHT ADJUST": 8-2150016-6
5. ADJUSTMENT OF THE STRIPPER MAY BE REQUIRED WHEN MOVING THE APPLICATOR BETWEEN BENCH AND LEADMAKER APPLICATIONS.
- 6 APPLY PART NUMBER 1-23419-5 LOCTITE TO THREADS OF ITEMS 50, 62. APPLY PART NUMBER 2-23419-6 LOCTITE TO THREADS OF ITEMS 242. FOR -6 ONLY APPLY PART NUMBER 1-23419-5 LOCTITE TO THREADS OF ITEM 37.
- 7 GREASE THREADS, GROOVE AND O-RING ON ITEMS 35 & 252.
- 8 MAGNET, ITEM 166 MUST BE ORIENTED CORRECTLY IN ORDER TO PROPERLY ACTUATE THE COUNTER.
- 9 CRIMP HEIGHT REFERENCE SETTING WAS THE SETTING USED WHEN THE APPLICATOR WAS QUALIFIED AT THE FACTORY. ADJUSTMENT MAY BE NECESSARY WHEN RUNNING APPLICATOR IN THE FIELD.
- 10 SPARE FEED CAM STORAGE LOCATION REFER TO INSTRUCTION SHEET FOR ADDITIONAL INFORMATION.
- 11 THE RECOMMENDED SET-UP FOR END FEED APPLICATORS IS POST-FEED WITH ITEM 2119653-1. THE APPLICATOR CAN BE CONFIGURED FOR PRE-FEED WITH ITEM 2119652-1 BUT MAY ENCOUNTER PROBLEMS WITH SOME APPLICATIONS. FEED ISSUES OR TERMINAL JAMMING MAY OCCUR IN THE PRE-FEED CONFIGURATION.
- 12 WHEN ASSEMBLING -6 NON-CRIMP HEIGHT ADJUST APPLICATOR USE SHIM PACK 2119957-2 TO ALIGN APPLICATOR'S MAXIMUM WIRE CRIMP HEIGHT AT NORMAL TERMINATOR SHUT HEIGHT


*WARNING
ON INSTALLATION, SET WIRE DISC, ITEM 40 TO LARGEST WIRE SIZE SETTING. USE OF SETTINGS BELOW MINIMUM REQUIRED CRIMP HEIGHT SETTING WILL CAUSE DAMAGE TO CRIMP TOOLING.

-	1	1	1	1	1	2079383-5	SCR, BHSC, RoHS (M4 X 20)	261
-	-	1	-	-	-	2119957-2	APPLICATOR SHIM PACK	260
-	1	-	1	1	1	8-21084-0	O-RING, .676 ID, .070 DIA. MAT.	252
-	-	-	-	1	-	2119640-1	PUSH ROD, AIR FEED	250
-	-	-	-	1	-	2079988-1	BUSHING, LCH5-12, MISUMI	249
-	-	-	-	1	-	2119641-1	FEED CAM, AIR FEED	248
-	1	-	1	1	1	2119798-1	DETENT PIN	247
-	1	-	1	1	1	1-22279-3	SPRING, COMPRESSION	246
-	-	1	-	-	-	2119759-1	RAM, AMP STYLE, END FEED, NON-ADJUST	245
-77	-7	-6	-5	-2	-1	PART NO	DESCRIPTION	ITEM NO


ATLANTIC VERSION
Shown on sheets 1 of 4 & 2 of 4
(Pacific version shown on sheets 3 of 4 & 4 of 4)

SET UP GAUGE 2119599-2	LOC A	DIST 66	REVISIONS			
			P	LTR	DESCRIPTION	DATE
				H	ECR-13-012589	07AUG2013
				J	ECR-14-003386	06MAR2014
				J1	ECR-15-002618	17FEB2015


-	1	1	1	1	1	2119082-9	CAM, SNAIL, INSULATION ADJUSTMENT	244
-	1	1	1	1	1	2079764-1	WASHER, WAVE SPRING, CREST-TO-CREST	243
-	1	1	1	1	1	2119083-1	RETAINER, INSULATION DIAL	242
-	-	2	2	-	-	2168400-7	SHCS, LOW HEAD, RoHS, M5 X 10	240
-	-	-	-	-	1	2119580-1	MECHANICAL FEED ASSEMBLY	239
-	-	-	-	1	-	2063440-1	AIR FEED MODULE	238
-	-	1	1	-	-	2119740-2	TAG, IDENTIFICATION	213
-	-	REF	REF	-	-	1901697-1	FEED FINGER ASSEMBLY, EF	183
-	1	1	1	1	1	6-993111-6	PIN, SLOTTED SPRING 3.0 X 14.0	177
-	1	1	1	1	1	8-22280-7	SPRING, COMPRESSION	176
-	1	1	1	1	1	1752353-2	GUIDE PIN, HOLDDOWN	175
-	1	1	1	1	1	1901680-2	GUIDE PIN, HOLDDOWN	174
-	-	-	-	2	-	21045-3	RING, RETAIN, EXTERN, 3/16 CRESCENT	172
-	1	1	1	1	1	994969-1	MAGNET, RARE EARTH HIGH ENERGY	166
-	REF	REF	REF	REF	REF	994970-2	COUNTER, MAGNETIC	164
-	-	-	-	1	-	240638-1	SPRING, FEED FINGER	163
-	-	-	-	1	-	3-23627-7	PIN, RETAIN, GRVD, 3/16 X .854	137
-	-	REF	REF	-	-	SEE NOTE 4	MEMORY CHIP, PROGRAMMED	135
-	-	1	1	-	-	1633743-1	SERVO FEED LATCH ASM	133
-	1	1	1	1	1	455888-4	SPACER, CRIMPER	82
-	1	1	1	1	1	2119956-2	DOCUMENTATION PACKAGE	71
-	2	2	2	2	2	2-18032-2	SCR, SET, FLT POINT M3 X 10.0	70
-	1	-	-	1	1	2119740-1	TAG, IDENTIFICATION	67
-	2	2	2	2	2	2168078-1	SCREW, DRIVE, RH, RoHS, 2 x .188	66
-	1	1	1	1	1	1901681-5	HOLDDOWN, TERMINAL	65
-	2	2	2	2	2	2168400-5	SHCS, LOW HEAD, RoHS, M4 X 20	64
-	1	-	-	1	1	2119793-1	LIMITER, ADJUSTMENT BOLT	63
-	3	-	3	3	3	992763-5	SCR, SET, SOC, CONE POINT, M3 x 4.0	62
-	1	1	1	1	1	2079383-4	SCR, BHSC, RoHS (M4 X 8)	60
-	-	-	-	-	1	5-18022-5	SCR, HEX HD CAP, M4 X 6.0	59
-	-	-	-	-	1	2063961-1	FEED FINGER	58
-	3	3	3	3	3	2168400-4	SHCS, LOW HEAD, RoHS, M4 X 8	57
-	2	2	2	2	2	2168083-3	SCR, SKT HD CAP, RoHS, M4 X 12.0	56
-	2	2	2	2	2	5018030-2	NUT, HEX, REG, RoHS, M4	55
-	2	2	2	2	2	5018030-1	NUT, HEX, REG, RoHS, M3	54
-	2	2	2	2	2	986965-8	NUT, LOCK, HEX, TORQUE (M4)	53
-	1	1	1	1	1	1-5018030-0	NUT, HEX, REG, RoHS, M3.5	52
-	-	-	-	1	-	2119792-2	PAWL, EF, AIR	51
-	1	1	1	1	1	1-1752354-4	STANDOFF, HOLD-DOWN	50
-	-	-	-	1	2	18023-9	SCR, SKT HD CAP M4 X 6.0	49
-	-	-	-	-	1	2119652-1	FEED CAM, PRE FEED	48
-	-	-	-	-	1	2119653-1	FEED CAM, POST FEED	47
-	1	1	1	1	1	2119655-5	APPLICATOR BASIC ASSEMBLY, EF	46
-	1	-	1	1	1	2119369-1	RAM, AMP STYLE, END FEED	44
-	1	1	1	1	1	2079383-7	SCR, BHSC, RoHS (M8 X 25)	41
-	1	-	1	1	1	2119645-1	DISC, NUMBERED FA WIRE ADJUSTMENT	40
-	1	-	1	1	1	2119957-1	APPLICATOR SHIM PACK	39
-	1	1	1	1	1	2119644-2	RAM WASHER, PRECISION	38
-	1	1	1	1	1	2119085-1	FA HEAD, ATLANTIC STYLE	37
-	1	-	1	1	1	2119092-1	BOLT, ADJUSTMENT	35
-	7	7	7	7	7	1-18028-2	WASHER, FLAT, REG M4	33
-	1	1	1	1	1	2168400-5	SHCS, LOW HEAD, RoHS, M4 X 20	31
-	2	2	2	2	2	1-2168083-0	SCR, SKT HD CAP, RoHS, M4 X 10	29
-	1	1	1	1	1	240639-1	STRIPPER (MACHINING)	27
-	2	2	2	2	2	1320906-1	STUD, THREADED	25
-	1	1	1	1	1	1752371-1	PLATE, STRIP GUIDE	24
-	1	1	1	1	1	240825-1	PLATE, STRIP HOLD DOWN	23
-	2	2	2	2	2	2-22281-3	SPRING, COMPRESSION	22
-	1	1	1	1	1	1752373-4	DRAG	20
-	2	2	2	2	2	1901259-6	GUIDE, LOWER STRIP	18
-	4	4	4	4	4	1-2079383-1	SCR, BHSC, RoHS (M6 X 12)	17
-	1	1	1	1	1	240641-1	SPACER	16
-	1	1	1	1	1	1752360-1	SPACER, HOLD-DOWN	13
-	1	1	1	1	1	240644-1	PLATE, REAR SHEAR	11
-	-	-	-	-	-	-	-	10
-	1	1	1	1	1	690495-4	PLATE, FRONT SHEAR	9
-	1	1	1	1	1	3-1803000-1	ANVIL, COMBINATION, END FEED	8
-	1	1	1	1	1	1-2217206-4	BLADE, SLUG	7
-	1	1	1	1	1	1-240641-6	SPACER	5
-	1	1	1	1	1	238009-1	BLOCK, FL CRIMPER SPACER	4
-	1	1	1	1	1	2119582-3	CRIMPER, INSULATION F PREMIUM	3
-	1	1	1	1	1	1-455888-0	SPACER, CRIMPER	2
-	1	1	1	1	1	1-1633730-9	CRIMPER, WIRE	1
-77	-7	-6	-5	-2	-1	PART NO	DESCRIPTION	ITEM NO

THIS IS SUBJECT TO CHANGE WITHOUT NOTICE. THE USER SHALL BE RESPONSIBLE FOR VERIFYING THE LATEST REVISIONS OF THIS DRAWING. ANY CHANGES TO THIS DRAWING SHALL BE CONTACTED FOR THE LATEST REVISION.				OWN B. WEAVER	29NOV2011	TE Connectivity Harrisburg, PA 17105-3608	
DIMENSIONS:				CHK G. HOFENER	29NOV2011	NAME	
mm				APVD T. ELBIN	29NOV2011	PRODUCT SPEC	
				TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC	
MATERIAL				FINISH		WEIGHT	
-				-		-	
Customer Accessible Production Drawing				SCALE		1:1	
-				SHEET		1 OF 4	
-				REV		J1	


LOC		DIST		REVISONS			
A	66	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-		SEE SHEET 1	-	-	-




HOLDDOWN SET-UP




FEED TYPE
MECHANICAL




PNEUMATIC



SERVO
LATCH PLATE



CAM POSITIONS



ATLANTIC VERSION
Shown on sheets 1 of 4 & 2 of 4
(Pacific version shown on sheets 3 of 4 & 4 of 4)

1ST PUBLISHED BY: COMPANY NAME FOR THE ELECTRONIC CORPORATION IT IS SUBJECT TO CHANGE WITHOUT NOTICE AND THE ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST NOTATION.				DWN B. WEAVER 29NOV2011		TE Connectivity Harrisburg, PA 17105-3608	
CHK G. HOFFNER 29NOV2011				NAME		Ocean End Feed Applicator	
APVD T. ELBIN 29NOV2011				PRODUCT SPEC		SIZE	
				APPLICATION SPEC		CAGE CODE	
				WEIGHT		DRAWING NO	
				MATERIAL		00779	
				Customer Accessible Production Drawing		©=2150016	
				SCALE		SHEET 2 OF 4	
				REV		J1	

8

7

6

5

4

3

2

1

THIS DRAWING IS UNPUBLISHED.


RELEASED FOR PUBLICATION

2011

© COPYRIGHT 2011

BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

PACIFIC VERSION
TERMINATOR
INTERFACE ADAPTER



PART
NUMBER

2-2150016-1

REVISION

J

DESCRIPTION

FINE CRIMP HEIGHT ADJUST

FEED TYPE

MECHANICAL

2-2150016-2

J

FINE CRIMP HEIGHT ADJUST

PNEUMATIC

2-2150016-5

J

FINE CRIMP HEIGHT ADJUST

SERVO LATCH PLATE

2-2150016-7

J

FINE CRIMP HEIGHT ADJUST

NONE

7-2150016-7

H

CRIMP TOOLING KIT

-

APPLICATOR DATA

CRIMP

SIZE

TYPE

WIRE

2.79 mm [.110]

F

INSUL

4.57 mm [.180]

F

APPLICATOR INSTRUCTIONS

408-10390



TERMINAL DATA: TE TERMINAL

TE CRIMP SPECIFICATION

TERMINAL NAME: RECEPTACLE, FASTON .250 SERIES

WIRE STRIP LENGTH

6.00-6.80 mm [.236-.268 IN]

INSULATION DIAMETER RANGE

Ø3.05-4.31 mm [.120-.170 IN]

TERMINAL APPLICATION SPECIFICATION

114-2036

-

-

-

-

-

-

TERMINALS APPLIED

TE TERMINAL

TE TERMINAL

TE TERMINAL

TE TERMINAL

63306-1

60713-1

42660-1

1217393-1

63306-2

60713-2

42660-2

63985-1

42400-1

350981-2

60650-1

63674-1

42400-2

42219-1

60650-2

1742948-1

42400-3

42219-2

60650-3

1742198-1

154692-1

1217272-1

WIRE SIZE



CRIMP HEIGHT mm [INCH]



CRIMP HEIGHT REFERENCE SETTING



14 AWG

1.85+/-0.05 [.073+/- .002]

7.5

(1)18 & (1)16

1.85+/-0.05 [.073+/- .002]

7.5

(2)18

1.73+/-0.05 [.068+/- .002]

9.0

16 OR (1)20 & (1)18

1.63+/-0.05 [.064+/- .002]

10.0

18 AWG

1.47+/-0.05 [.058+/- .002]

11.7



RECOMMENDED SPARE PARTS

GREASE BEARING SURFACES LIGHTLY

LUBRICATE DAILY PER THE APPLICATOR INSTRUCTION SHEET SUPPLIED WITH THE APPLICATOR.

APPLICATOR SPECIFIC DATA TO BE ENTERED INTO BLANK MEMORY CHIP AT ASSEMBLY. SEE BELOW FOR PART NUMBER:
MECHANICAL FEED WITH "SMART APPLICATOR" CONVERSION: 8-2150016-4
PNEUMATIC FEED WITH "SMART APPLICATOR" CONVERSION: 8-2150016-4
SERVO FEED WITH "FINE CRIMP HEIGHT ADJUST": 8-2150016-5

ADJUSTMENT OF THE STRIPPER MAY BE REQUIRED WHEN MOVING THE APPLICATOR BETWEEN BENCH AND LEADMAKER APPLICATIONS.

APPLY PART NUMBER 1-23419-5 LOCTITE TO THREADS OF ITEMS 50, 62.
APPLY PART NUMBER 2-23419-6 LOCTITE TO THREADS OF ITEMS 242.

GREASE THREADS, GROOVE AND O-RING ON ITEMS 139 & 153.

MAGNET, ITEM 166 MUST BE ORIENTED CORRECTLY IN ORDER TO PROPERLY ACTUATE THE COUNTER.

CRIMP HEIGHT REFERENCE SETTING WAS THE SETTING USED WHEN THE APPLICATOR WAS QUALIFIED AT THE FACTORY. ADJUSTMENT MAY BE NECESSARY WHEN RUNNING APPLICATOR IN THE FIELD.

SPARE FEED CAM STORAGE LOCATION REFER TO INSTRUCTION SHEET FOR ADDITIONAL INFORMATION.

THE RECOMMENDED SET-UP FOR END FEED APPLICATORS IS POST-FEED WITH ITEM 2119653-1. THE APPLICATOR CAN BE CONFIGURED FOR PRE-FEED WITH ITEM 2119652-1 BUT MAY ENCOUNTER PROBLEMS WITH SOME APPLICATIONS. FEED ISSUES OR TERMINAL JAMMING MAY OCCUR IN THE PRE-FEED CONFIGURATION.

APPLICATOR STYLE CONVERSION CHART

CONVERT TO

PART NUMBERS REQUIRED

PNEUMATIC FEED

2119950-1

2119792-2

-

2119641-2

-

2063440-1

SERVO LATCH PLATE

2119951-1

1901697-1

8-2150016-5

-

-

2168400-7 (QUANTITY 2)

SMART APPLICATOR

2161326-1

-

8-2150016-4

-

-

-

MECHANICAL FEED

2119949-1

2063961-1

5-18022-5

2119653-2

-

-

SERVO LATCH PLATE

2119951-1

1901697-1

8-2150016-5

-

-

2168400-7 (QUANTITY 2)

SMART APPLICATOR

2161326-1

-

8-2150016-4

-

-

-

MECHANICAL FEED

2119949-1

2063961-1

5-18022-5

2119653-2

-

-

PNEUMATIC FEED

2119950-1

2119792-2

-

2119641-2

-

2063440-1

-

-

-

-

-

-

-

-

-

-

-

-

-

-

6

1

1

1

1

2119083-1

RETAINER, INSULATION DIAL

242

-

2

-

-

2168400-7

SHCS, LOW HEAD, RoHS, M5 X 10

240

-

-

-

1

2119580-1

MECHANICAL FEED ASSEMBLY

239

-

-

-

1

2063440-1

AIR FEED MODULE

238

-

1

-

-

2119740-2

TAG, IDENTIFICATION

213

-

4

4

4

2079383-9

SCR, BHSC, RoHS (M6 X 20)

186

-

REF

-

-

1901697-1

FEED FINGER ASSEMBLY, EF

183

-

1

1

1

1

6-993111-6

PIN, SLOTTED SPRING 3.0 X 14.0

177

-

1

1

1

1

8-22280-7

SPRING, COMPRESSION

176

-

1

1

1

1

1752353-2

GUIDE PIN,HOLDDOWN

175

-

1

1

1

1

1901680-2

GUIDE PIN,HOLDDOWN

174

-

-

-

2

-

21045-3

RING, RETAIN, EXTERN, 3/16 CRESCENT

172

-

1

1

1

1

994969-1

MAGNET, RARE EARTH HIGH ENERGY

166

-

REF

REF

REF

REF

994970-2

COUNTER, MAGNETIC

164

-

-

-

1

-

240638-1

SPRING, FEED FINGER

163

-

1

1

1

1

8-21084-1

O-RING, .801 ID, .070 DIA. MAT.

153

-

-

-

1

-

2119641-2

FEED CAM, AIR FEED

152

-

1

1

1

1

2119798-2

DETENT PIN

145

-

1

1

1

1

2079383-8

SCR, BHSC, RoHS (M4 X 16)

144

-

-

-

-

1

2119653-2

FEED CAM, POST FEED

142

-

1

1

1

1

2119655-6

APPLICATOR BASIC ASSEMBLY, EF

141

-

1

1

1

1

2119651-1

RAM, ASIAN STYLE, END FEED

140

-

1

1

1

1

2119092-2

BOLT, ADJUSTMENT

139

-

-

-

1

-

3-23627-7

PIN, RETAIN, GRVD, 3/16 X .854

137

-

-

REF

-

-

SEE NOTE 4

MEMORY CHIP, PROGRAMMED

135

-

-

1

-

-

1633743-1

SERVO FEED LATCH ASM

133

-

1

1

1

1

455888-4

SPACER, CRIMPER

82

-

1

1

1

1

2119956-2

DOCUMENTATION PACKAGE

71

-

2

2

2

2

2-18032-2

SCR, SET, FLT POINT M3 X 10.0

70

-

1

-

1

1

2119740-1

TAG, IDENTIFICATION

67

-

2

2

2

2

2168078-1

SCREW, DRIVE, RH, RoHS, 2 x .188

66

-

1

1

1

1

1901681-5

HOLDDOWN, TERMINAL

65

-

2

2

2

2

2168400-5

SHCS, LOW HEAD, RoHS, M4 X 20

64

-

1

1

1

1

2119793-1

LIMITER, ADJUSTMENT BOLT

63

6

3

3

3

3

992763-5

SCR, SET, SOC, CONE POINT, M3 x 4.0

62

-

-

-

-

1

5-18022-5

SCR, HEX HD CAP, M4 X 6.0

59

-

-

-

-

1

2063961-1

FEED FINGER

58

-

3

3

3

3

2168400-4

SHCS, LOW HEAD, RoHS, M4 X 8

57

-

2

2

2

2

2168083-3

SCR, SKT HD CAP, RoHS, M4 X 12.0

56

-

2

2

2

2

5018030-2

NUT, HEX, REG, RoHS, M4

55

-

2

2

2

2

5018030-1

NUT, HEX, REG, RoHS, M3

54

-

2

2

2

2

986965-8

NUT, LOCK, HEX, TORQUE (M4)

53

-

1

1

1

1

1-5018030-0

NUT, HEX, REG, RoHS, M3.5

52

-

-

-

1

-

2119792-2

PAWL, EF, AIR

51

6

1

1

1

1

1-1752354-4

STANDOFF,HOLD-DOWN

50

-

-

-

1

2

18023-9

SCR, SKT HD CAP M4 X 6.0

49

-

-

-

-

1

2119652-1

FEED CAM, PRE FEED

48

-

1

1

1

1

2079383-7

SCR, BHSC, RoHS (M8 X 25)

41

-

1

1

1

1

2119645-1

DISC, NUMBERED FA WIRE ADJUSTMENT

40

-

1

1

1

1

2119957-1

APPLICATOR SHIM PACK

39

-

1

1

1

1

2119644-2

RAM WASHER, PRECISION

38

-

7

7

7

7

1-18028-2

WASHER, FLAT, REG M4

33

-

1

1

1

1

2168400-5

SHCS, LOW HEAD, RoHS, M4 X 20

31

-

2

2

2

2

1-2168083-0

SCR, SKT HD CAP, RoHS, M4 X 10

29

-

1

1

1

1

240639-1

STRIPPER (MACHINING)

27

-

2

2

2

2

1320906-1

STUD, THREADED

25

-

1

1

1

1

1752371-1

PLATE, STRIP GUIDE

24

-

1

1

1

1

240825-1

PLATE, STRIP HOLD DOWN

23

-

2

2

2

2

2-22281-3

SPRING, COMPRESSION

22

-

1

1

1

1

1752373-4

DRAG

20

-

2

2

2

2

1901259-6

GUIDE, LOWER STRIP

18

-

1

1

1

1

240641-1

SPACER

16

-

1

1

1

1

1752360-1

SPACER,HOLD-DOWN

13

1

-

1

1

1

1

240644-1

PLATE, REAR SHEAR

11

-

-

-

-

-

-

-

10

1

-

1

1

1

1

690495-4

PLATE, FRONT SHEAR

9

1

1

1

1

1

1

3-1803000-1

ANVIL, COMBINATION, END FEED

8

1

-

1

1

1

1

1-2217206-4

BLADE, SLUG

7

-

1

1

1

1

1

1-240641-6

SPACER

5

-

1

1

1

1

1

238009-1

BLOCK, FL CRIMPER SPACER

4

1

1

1

1

1

1

2119582-3

CRIMPER, INSULATION F PREMIUM

3

-

1

1

1

1

1

1-455888-0

SPACER, CRIMPER

2

1

1

1

1

1

1

1-1633730-9

CRIMPER, WIRE

1

77-27-25-22-21

PART NO

DESCRIPTION

ITEM NO

1

1

1

1

1

2079383-5

SCR, BHSC, RoHS (M4 X 20)

261

1

1

1

1

1

2119782-1

FINE ADJUST HEAD ASM, PACIFIC STYLE

251

-

-

-

1

-

2119640-1

PUSH ROD, AIR FEED

250

-

-

-

1

-

2079988-1

BUSHING, LCH5-12, MISUMI

249

-

1

1

1

1

1-22279-3

SPRING, COMPRESSION

246

-

1

1

1

1

2119082-9

CAM, SNAIL, INSULATION ADJUSTMENT

244

-

1

1

1

1

2079764-1

WASHER, WAVE SPRING, CREST-TO-CREST

243

PACIFIC VERSION

Shown on sheets 3 of 4 & 4 of 4

(Atlantic version shown on sheets 1 of 4 & 2 of 4)

SET UP GAUGE

2119599-2

LOC

A

DIST

66

P

LTR

DESCRIPTION

DATE

OWN

APVD

-

-

SEE SHEET 1

-

-

-

6

1

1

1

1

2119083-1

RETAINER, INSULATION DIAL

242

-

2

-

-

2168400-7

SHCS, LOW HEAD, RoHS, M5 X 10

240

-

-

-

1

2119580-1

MECHANICAL FEED ASSEMBLY

239

-

-

-

1

2063440-1

AIR FEED MODULE

238

-

1

-

-

2119740-2

TAG, IDENTIFICATION

213

-

4

4

4

2079383-9

SCR, BHSC, RoHS (M6 X 20)

186

-

REF

-

-

1901697-1

FEED FINGER ASSEMBLY, EF

183

-

1

1

1

1

6-993111-6

PIN, SLOTTED SPRING 3.0 X 14.0

177

-

1

1

1

1

8-22280-7

SPRING, COMPRESSION

176

-

1

1

1

1

1752353-2

GUIDE PIN,HOLDDOWN

175

-

1

1

1

1

1901680-2

GUIDE PIN,HOLDDOWN

174

-

-

-

2

-

21045-3

RING, RETAIN, EXTERN, 3/16 CRESCENT

172

-

1

1

1

1

994969-1

MAGNET, RARE EARTH HIGH ENERGY

166

-

REF

REF

REF

REF

994970-2

COUNTER, MAGNETIC

164

-

-

-

1

-

240638-1

SPRING, FEED FINGER

163

-

1

1

1

1

8-21084-1

O-RING, .801 ID, .070 DIA. MAT.

153

-

-

-

1

-

2119641-2

FEED CAM, AIR FEED

152

-

1

1

1

1

2119798-2

DETENT PIN

145

-

1

1

1

1

2079383-8

SCR, BHSC, RoHS (M4 X 16)

144

-

-

-

-

1

2119653-2

FEED CAM, POST FEED

142

-

1

1

1

1

2119655-6

APPLICATOR BASIC ASSEMBLY, EF

141

-

1

1

1

1

2119651-1

RAM, ASIAN STYLE, END FEED

140

-

1

1

1

1

2119092-2

BOLT, ADJUSTMENT

139

-

-

-

1

-

3-23627-7

PIN, RETAIN, GRVD, 3/16 X .854

137

-

-

REF

-

-

SEE NOTE 4

MEMORY CHIP, PROGRAMMED

135

-

-

1

-

-

1633743-1

SERVO FEED LATCH ASM

133

-

1

1

1

1

455888-4

SPACER, CRIMPER

82

-

1

1

1

1

2119956-2

DOCUMENTATION PACKAGE

71

-

2

2

2

2

2-18032-2

SCR, SET, FLT POINT M3 X 10.0

70

-

1

-

1

1

2119740-1

TAG, IDENTIFICATION

67

-

2

2

2

2

2168078-1

SCREW, DRIVE, RH, RoHS, 2 x .188

66

-

1

1

1

1

1901681-5

HOLDDOWN, TERMINAL

65

-

2

2

2

2

2168400-5

SHCS, LOW HEAD, RoHS, M4 X 20

64

-

1

1

1

1

2119793-1

LIMITER, ADJUSTMENT BOLT

63

6

3

3

3

3

992763-5

SCR, SET, SOC, CONE POINT, M3 x 4.0

62

-

-

-

-

1

5-18022-5

SCR, HEX HD CAP, M4 X 6.0

59

-

-

-

-

1

2063961-1

FEED FINGER

58

-

3

3

3

3

2168400-4

SHCS, LOW HEAD, RoHS, M4 X 8

57

-

2

2

2

2

2168083-3

SCR, SKT HD CAP, RoHS, M4 X 12.0

56

-

2

2

2

2

5018030-2

NUT, HEX, REG, RoHS, M4

55

-

2

2

2

2

5018030-1

NUT, HEX, REG, RoHS, M3

54

-

2

2

2

2

986965-8

NUT, LOCK, HEX, TORQUE (M4)

53

-

1

1

1

1

1-5018030-0

NUT, HEX, REG, RoHS, M3.5

52

-

-

-

1

-

2119792-2

PAWL, EF, AIR

51

6

1

1

1

1

1-1752354-4

STANDOFF,HOLD-DOWN

50

-

-

-

1

2

18023-9

SCR, SKT HD CAP M4 X 6.0

49

-

-

-

-

1

2119652-1

FEED CAM, PRE FEED

48

-

1

1

1

1

2079383-7

SCR, BHSC, RoHS (M8 X 25)

41

-

1

1

1

1

2119645-1

DISC, NUMBERED FA WIRE ADJUSTMENT

40

-

1

1

1

1

2119957-1

APPLICATOR SHIM PACK

39

-

1

1

1

1

2119644-2

RAM WASHER, PRECISION

38

-

7

7

7

7

1-18028-2

WASHER, FLAT, REG M4

33

-

1

1

1

1

2168400-5

SHCS, LOW HEAD, RoHS, M4 X 20

31

-

2

2

2

2

1-2168083-0

SCR, SKT HD CAP, RoHS, M4 X 10

29

-

1

1

1

1

240639-1

STRIPPER (MACHINING)

27

-

2

2

2

2

1320906-1

STUD, THREADED

25

-


1

1


1

<


LOC		DIST		REVISIONS			
A	66	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-		SEE SHEET 1	-	-	-




HOLDDOWN SET-UP




FEED TYPE
MECHANICAL




PNEUMATIC



SERVO
LATCH PLATE



CAM POSITIONS



PACIFIC VERSION
Shown on sheets 3 of 4 & 4 of 4
(Atlantic version shown on sheets 1 of 4 & 2 of 4)

1ST PUBLISHED BY: COMPANY NAME FOR THE ELECTRONIC CORPORATION IT IS SUBJECT TO CHANGE WITHOUT NOTICE AND THE ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST NOTATION		DWN B. WEAVER 29NOV2011	STE Connectivity Harrisburg, PA 17105-3608	
DIMENSIONS: mm		CHK G. HOFFNER 29NOV2011	NAME Ocean End Feed Applicator	
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±0.5 1 PLC ±0.13 2 PLC ±0.13 3 PLC ±0.13 4 PLC ±0.0001 ANGLES ±0.0001		APVD T. ELBIN 29NOV2011	PRODUCT SPEC	
MATERIAL			APPLICATION SPEC	
			WEIGHT	
			Customer Accessible Production Drawing	
			SCALE 1:1	
			SHEET 4 OF 4	
			REV J1	

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9