



Micro Commercial Components



Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

AK1-076C THRU AK15-076C

Features


- Axial Lead Terminals
- High Current Transient Suppressor
- Excellent Clamping Capability
- Glass Passivated Junction
- Bi-directional
- Low Slope Resistance
- Repetition Rate(duty cycle):0.01%
- Halogen Free
- High Temperature Soldering:260°C/10 Seconds at Terminals
- Lead Free Finish/Rohs Compliant (Note1) ("P"Suffix designates Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

Maximum Ratings And Thermal Characteristics

Parameter	Symbol	Value		Unit
Current Rating, Rated IPP Measured With 8/20us Pulse	I _{pp}	AK1	1	KAmps
		AK3	3	
		AK6	6	
		AK10	10	
		AK15	15	
Operating Junction and Storage Temperature Range	T _J T _{STG}	-55 to +150		°C

Notes: 1. High Temperature Solder Exemption Applied, see EU Directive Annex Notes 7

AK Series TVS Diodes 58-430 Volts



DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	---	.630	---	16.00	
B	---	.709	---	18.00	
C	.047	.052	1.20	1.32	
D	.197	---	5.00	---	
E	.922	.979	23.43	24.87	
F	---	.157	---	4.00	

Electrical Characteristics($T_A=25^{\circ}\text{C}$ unless otherwise noted)

Part Number	Reverse Stand-Off Voltage		Breakdown Voltage	Test Current	Surge Current Rating	Maximum Clamping Voltage	Reverse Leakage
	VAC(V)	VDC(V)	VBR(V) MIN.@IT	IT(mA)	8/20us (KA)	VC(V) @IPP	IR(uA) @VDC
AK1-076C	54	76	83	10	1	135	20
AK3-058C	40	58	64	10	3	110	20
AK3-066C	45	66	70	10	3	125	20
AK3-076C	54	76	85	10	3	140	20
AK3-380C	275	380	401	10	3	520	20
AK3-430C	310	430	440	10	3	625	20
AK6-058C	40	58	64	10	6	110	20
AK6-066C	45	66	70	10	6	125	20
AK6-076C	54	76	83	10	6	135	20
AK6-170C	130	170	180	10	6	260	20
AK6-190C	145	190	200	10	6	290	20
AK6-240C	180	240	250	10	6	340	20
AK6-380C	275	380	401	10	6	520	20
AK6-430C	310	430	440	10	6	625	20
AK10-058C	40	58	64	10	10	110	20
AK10-066C	45	66	70	10	10	125	20
AK10-076C	54	76	83	10	10	135	20
AK10-170C	130	170	180	10	10	260	20
AK10-190C	145	190	200	10	10	290	20
AK10-200C	150	200	222	10	10	330	20
AK10-240C	180	240	250	10	10	340	20
AK10-380C	275	380	401	10	10	520	20
AK10-430C	310	430	440	10	10	625	20
AK15-058C	40	58	64	10	15	110	20
AK15-076C	54	76	85	10	15	145	20

Ratings and Characteristics Curves ($T_A=25^{\circ}\text{C}$ unless otherwise noted)




Fig. 1 - Pulse Derating Curve

Ordering Information

Device	Packing
(Part Number)-BP	Bulk:150pcs/Box

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9