

FO cable - PSM-LWL-HCS-200/230-METER - 2799885

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



HCS cable, duplex 200/230 µm, by the meter, without connector, for indoor installation

Why buy this product

- ✓ 2.9 mm individual wires made from highly flexible FRNC material
- ✓ Rugged installation cable for indoor use
- ✓ Highly tear-resistant aramid strain relief elements
- ✓ Rugged polyurethane (PUR) outer sheath
- ✓ Halogen-free, ozone, and UV resistant

Key commercial data

Packing unit	1
Minimum order quantity	1
Catalog page	Page 528 (IF-2011)
GTIN	 4 017918 074159
Custom tariff number	85447000
Country of origin	GERMANY

Technical data

Mechanical characteristics

Fiber	HCS, 200/230 µm
Cable diameter	8 mm
Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (operation)	-20 °C ... 70 °C (with quick mounting connector)
Ambient temperature (storage/transport)	-40 °C ... 70 °C

Material data

Outer sheath, material	PUR
External sheath, color	orange

Line characteristics

Cable type	HCS
Cable abbreviation	I-VH11Y 2K200/230 HCS
Length of cable	Free input (1.0 ... 2000 m)

FO cable - PSM-LWL-HCS-200/230-METER - 2799885

Technical data

Line characteristics

External cable diameter	8 mm
Wire colors	Red/Green
External sheath, color	orange
Outer sheath, material	PUR
Cable weight	54 kg/km
Impact strength	2 Nm / 10 x
cable layer type	Indoors
Halogen-free	According to IEC 60754-2
Resistance to oil	IRM 902 No.2, 100 °C, DIN VDE 0473-811-2-1

Temperature data

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (operation)	-20 °C ... 70 °C (with quick mounting connector)
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Altitude	5000 m

Classifications

ETIM

ETIM 2.0	EC000752
ETIM 3.0	EC000752
ETIM 4.0	EC000752
ETIM 5.0	EC000830

UNSPSC

UNSPSC 11	26121607
UNSPSC 12.01	26121607
UNSPSC 13.2	26121607
UNSPSC 6.01	26121607
UNSPSC 7.0901	26121607

eCl@ss

eCl@ss 4.0	27061001
eCl@ss 4.1	27061001
eCl@ss 5.0	27061803
eCl@ss 5.1	27061803
eCl@ss 6.0	27061803
eCl@ss 7.0	27061803

Accessories

Accessories

Cable/conductor

FO cable - PSM-LWL-HCS-200/230-METER - 2799885

Accessories

FO patch cable - FOC-HCS-RUGGED-1014/IP20/... - 2901555



rugged HCS installation cable (IP20 heads only) for inner areas with highly tear-proof aramid strain-relief elements. Individual elements made from highly flexible FRNC material. The cable is halogen-free, ozone and UV resistant and has a rugged polyurethane (PUR) outer sheath.

FO patch cable - FOC-HCS-RUGGED-1014/... - 1402191



rugged HCS installation cable for inner areas with highly tear-proof aramid strain-relief elements. Individual elements made from highly flexible FRNC material. The cable is halogen-free, ozone and UV resistant and has a rugged polyurethane (PUR) outer sheath.

Plug/Adapter

FO plug connectors - PSM-SET-FSMA/4-HCS - 2799487



F-SMA plug set for HCS fiber, for self assembly consisting of 4 quick mounting connectors with bend protection sleeve

FO plug connectors - PSM-SET-B-FOC/4-HCS - 2708481



B-FOC (ST) connector set for HCS fiber, for self assembly consisting of 4 quick mounting connectors with bend protection sleeve

FO plug connectors - PSM-SET-SCRJ-DUP/2-HCS - 2313070



SCRJ connector set for HCS fiber, for self assembly, consisting of 2 duplex quick mounting connectors with bending protection

Tools

FO cable - PSM-LWL-HCS-200/230-METER - 2799885

Accessories

Assembly tool - PSM-HCS-KONFTOOL - 2799526



HCS assembly kit for F-SMA quick mounting connectors, including stripping blade, stripping pliers, aramide yarn scissors, fiber stripper, microscope, fiber cleaving tool for standard HCS fibers, and documentation

Assembly tool - PSM-HCS-KONFTOOL/B-FOC - 2708465



HCS assembly kit for B-FOC (ST) quick mounting connectors, including stripping blade, stripping pliers, aramide yarn scissors, fiber stripper, microscope, fiber cleaving tool for standard HCS and HCS GI fibers, and documentation

Assembly tool - PSM-HCS-KONFTOOL/SC-RJ - 2708876



HCS assembly kit for SCRJ quick mounting connectors, including stripping blade, stripping pliers, aramide yarn scissors, fiber stripper, microscope, fiber cleaving tool for standard HCS and HCS GI fibers, and documentation

Assembly tool - PSM-HCS-CLEAVETOOL - 2744995



Fiber cleaving tool for HCS fibers, pin assignment: F-SMA for the assembly of F-SMA quick mounting connectors, supplements PSM-HCS-KONFTOOL...

Assembly tool - PSM-HCS-CLEAVETOOL/B-FOC - 2708478



Fiber cleaving tool for HCS fibers, pin assignment: B-FOC (ST) for the assembly of B-FOC quick mounting connectors, supplements PSM-HCS-KONFTOOL...

Assembly tool - PSM-HCS-CLEAVETOOL/SCRJ - 2313122



Fiber cleaving tool for HCS fibers, pin assignment: SCRJ or SC duplex for the assembly of SC quick mounting connectors, supplements PSM-HCS-KONFTOOL...

FO cable - PSM-LWL-HCS-200/230-METER - 2799885

Accessories

© Phoenix Contact 2012 - all rights reserved
<http://www.phoenixcontact.com>

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9