

MS Series Subminiature Snap-acting Switches

Features/Benefits

- Detect interlock and movement
- Different lever options
- Various operating forces
- Extended mechanical life
- UL approval on some designs
- Customization available
- RoHS compatible and compliant

Typical Applications

- Office equipment
- Consumer electronics
- Appliances
- Audio & visual equipment
- Medical
- Industrial meters



Specifications


CONTACT ARRANGEMENT: SPDT
 CONTACT RATING: 5 A @ 125 VAC / 3 A @ 250 VAC
 OPERATING LIFE: 1,000,000 cycles without load
 6,000 cycles with load UL
 INITIAL CONTACT RESISTANCE: 100 mΩ max.
 INSULATION RESISTANCE: 100 MΩ min. @ 500 VDC
 DIELECTRIC STRENGTH: 1000 VAC (50-60 Hz)
 OPERATING TEMPERATURE: -40°C to + 85°C
 OPERATING FORCE: 130 ± 30 gf
 PRE-TRAVEL (PT): 0.6 mm max.
 OVERTRAVEL: 0.5 mm max.
 OPERATING POSITION (OP): 8.40 ± 0.40 mm

Materials


COVER: PBT (UL94V-0)
 HOUSING: PBT (UL94V-0)
 KNOB: PBT (UL94V-0)
 TERMINALS: Silver plated

NOTE: Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.

PART NUMBER
MS-105A01




Circuit Diagram



SCHEMATIC

Mounting Holes



PIERCING PLAN

Snap-acting



J



Snap-acting

Snap-acting

Snap-acting

Snap-acting

Snap-acting

Snap-acting



Snap-acting

Snap-acting

Snap-acting

Snap-acting


Snap-acting



MS Series Subminiature Snap-acting Switches

PART NUMBER

MS-118305



Specifications

CONTACT ARRANGEMENT: SPDT
CONTACT RATING: 0.1 A @ 30 VDC
OPERATING LIFE: 500,000 cycles without load
50,000 cycles with load
INITIAL CONTACT RESISTANCE: 50 m Ω max.
INSULATION RESISTANCE: 100 M Ω min. @ 500 VDC
DIELECTRIC STRENGTH: 1000 VAC (50-60 Hz)
OPERATING TEMPERATURE: -20°C to + 70°C
OPERATING FORCE: 70 $\pm$ 40 gf
PRE-TRAVEL (PT): 0.50 mm max.
OVERTRAVEL: 0.5 mm min.
OPERATING POSITION (OP): 5.50 $\pm$ 0.30 mm


Materials

COVER: PBT (UL94V-0)
HOUSING: PBT (UL94V-0)
KNOB: PBT (UL94V-0)
TERMINALS: Silver plated

NOTE: Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.

PART NUMBER

MS-118305-A



Specifications

CONTACT ARRANGEMENT: SPDT
CONTACT RATING: 0.1 A @ 30 VDC
OPERATING LIFE: 500,000 cycles without load
50,000 cycles with load
INITIAL CONTACT RESISTANCE: 50 m Ω max.
INSULATION RESISTANCE: 100 M Ω min. @ 500 VDC
DIELECTRIC STRENGTH: 1000 VAC (50-60 Hz)
OPERATING TEMPERATURE: -20°C to + 70°C
OPERATING FORCE: 25 $\pm$ 15 gf
OVERTRAVEL: 0.5 mm min.
OPERATING POSITION (OP): 6.0 $\pm$ 0.80 mm
FREE POSITION (FP): 8.5mm max.

Materials

COVER: PBT (UL94V-0)
HOUSING: PBT (UL94V-0)
KNOB: PBT (UL94V-0)
TERMINALS: Silver plated

NOTE: Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.

Snap-acting

NOTE: Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.

Technical drawings of the 1P-2T relay, showing dimensions and electrical connections.

Dimensions:

- Top view: 12.8 (width)
- Front view: 13.90 (diagonal length), 2X2.2 (flange thickness), 6.5 (height), 5 (height), 3.5 (height), 2.7 (height), 3-1 (height), 6.5 (width), 4.8 (width), 4.8 (width), 3-2 (height), 0.P. (height), 1.6 (width), 2 (width)
- Side view: 5.8 (width), 3.7 (width), 0.6 (width)


Electrical Connections:

- 1P-2T:** 1P (Common), 2T (NO, NC)
- Terminal Block:** COMMON, NO, NC

Schematic: Shows the internal wiring of the relay, with 1P connected to the COMMON terminal, and 2T connected to the NO and NC terminals.

Pierce Plan: Shows the physical layout of the relay components, including the terminal block and the relay body.

NOTE: Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.



Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9