

# MS Series Subminiature Snap-acting Switches

## Features/Benefits

- Detect interlock and movement
- Different lever options
- Various operating forces
- Extended mechanical life
- UL approval on some designs
- Customization available
- RoHS compatible and compliant

## Typical Applications

- Office equipment
- Consumer electronics
- Appliances
- Audio & visual equipment
- Medical
- Industrial meters



## Specifications


CONTACT ARRANGEMENT: SPDT  
 CONTACT RATING: 5 A @ 125 VAC / 3 A @ 250 VAC  
 OPERATING LIFE: 1,000,000 cycles without load  
 6,000 cycles with load UL  
 INITIAL CONTACT RESISTANCE: 100 mΩ max.  
 INSULATION RESISTANCE: 100 MΩ min. @ 500 VDC  
 DIELECTRIC STRENGTH: 1000 VAC (50-60 Hz)  
 OPERATING TEMPERATURE: -40°C to + 85°C  
 OPERATING FORCE: 130 ± 30 gf  
 PRE-TRAVEL (PT): 0.6 mm max.  
 OVERTRAVEL: 0.5 mm max.  
 OPERATING POSITION (OP): 8.40 ± 0.40 mm

## Materials

COVER: PBT (UL94V-0)  
 HOUSING: PBT (UL94V-0)  
 KNOB: PBT (UL94V-0)  
 TERMINALS: Silver plated


NOTE: Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.

| PART NUMBER      |
|------------------|
| <b>MS-105A01</b> |




Standard Size

Circuit Diagram



SCHEMATIC

Mounting Holes



PIERCING PLAN

## Snap-acting


**J**

## Snap-acting

## Snap-acting

## Snap-acting

## Snap-acting

## Snap-acting

## Snap-acting



## Snap-acting

## Snap-acting

## Snap-acting

## Snap-acting

## Snap-acting




## Snap-acting

## Snap-acting

# MS Series Subminiature Snap-acting Switches

## PART NUMBER

**MS-118305**



## Specifications

CONTACT ARRANGEMENT: SPDT  
CONTACT RATING: 0.1 A @ 30 VDC  
OPERATING LIFE: 500,000 cycles without load  
50,000 cycles with load  
INITIAL CONTACT RESISTANCE: 50 m $\Omega$  max.  
INSULATION RESISTANCE: 100 M  $\Omega$  min. @ 500 VDC  
DIELECTRIC STRENGTH: 1000 VAC (50-60 Hz)  
OPERATING TEMPERATURE: -20°C to + 70°C  
OPERATING FORCE: 70  $\pm$  40 gf  
PRE-TRAVEL (PT): 0.50 mm max.  
OVERTRAVEL: 0.5 mm min.  
OPERATING POSITION (OP): 5.50  $\pm$  0.30 mm


## Materials

COVER: PBT (UL94V-0)  
HOUSING: PBT (UL94V-0)  
KNOB: PBT (UL94V-0)  
TERMINALS: Silver plated

NOTE: Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.

## PART NUMBER

**MS-118305-A**



## Specifications

CONTACT ARRANGEMENT: SPDT  
CONTACT RATING: 0.1 A @ 30 VDC  
OPERATING LIFE: 500,000 cycles without load  
50,000 cycles with load  
INITIAL CONTACT RESISTANCE: 50 m $\Omega$  max.  
INSULATION RESISTANCE: 100 M  $\Omega$  min. @ 500 VDC  
DIELECTRIC STRENGTH: 1000 VAC (50-60 Hz)  
OPERATING TEMPERATURE: -20°C to + 70°C  
OPERATING FORCE: 25  $\pm$  15 gf  
OVERTRAVEL: 0.5 mm min.  
OPERATING POSITION (OP): 6.0  $\pm$  0.80 mm  
FREE POSITION (FP): 8.5mm max.

## Materials

COVER: PBT (UL94V-0)  
HOUSING: PBT (UL94V-0)  
KNOB: PBT (UL94V-0)  
TERMINALS: Silver plated

NOTE: Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.

## Snap-acting

The technical drawings include:

- Top View:** Shows a rectangular component with a width of 12.8. It features a central rectangular cutout and a smaller rectangular feature on the left side.
- Side View:** Shows the component's profile with a total height of 6.5. It includes a mounting tab on the left with a width of 3.5 and a central section with a width of 5. The bottom section has a width of 2.7. The total width is 6.5. The bottom section is divided into two 4.8 segments with a 3-1 ratio. The bottom section has a width of 3-2. The bottom section has a width of 1.8. The bottom section has a width of 0.6. The bottom section has a width of 0.6.
- Front View:** Shows the component's front face with a width of 5.8 and a height of 2.8. It features a central rectangular cutout and a smaller rectangular feature on the left side.
- Schematic Diagram:** Shows the internal wiring of the relay. It includes a common terminal (COM) and two normally open (N.O.) and normally closed (N.C.) terminals. The schematic is labeled "1P-2T".

NOTE: Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.

Technical drawings of the 1P-2T relay, showing dimensions and electrical connections.

**Dimensions:**

- Top view: 12.8
- Front view: 13.90, 2X2.2, 6.5, 5, 3.5, 2.7, 3-1, 4.8, 4.8, 6.5, 3-2, 0.P., P.P., 5.8, 3.7, 0.6

**Labels:**

- Smaller Size
- 1P-2T
- 1, 2
- COM, NO, NC
- COMMON, NO, NC
- TERMINAL, TERMINAL


**Schematic:**

Diagram showing the internal wiring connections between terminals 1, 2, COM, NO, and NC.

**Piercing Plan:**

Diagram showing the physical layout of the terminals (COMMON, NO, NC) and their corresponding labels (TERMINAL, TERMINAL).

NOTE: Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.



## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9