

# G-Series

## HYDRAULIC-MAGNETIC CIRCUIT BREAKER

The G-Series din-rail hydraulic-magnetic circuit breaker insures maximum protection by integrating wiping contacts for longevity; a common trip linkage between poles; a unique terminal bus connection system; and optional integrated auxiliary switch. It is also suitable for reverse feed and provides finger safe terminals. This DIN rail mount circuit breaker accommodates either a 35mm x 7.5mm, or a 35mm x 15mm symmetrical din rails.

G-Series DIN Rail Circuit Breaker:

UL 489 Listed: 1 to 3 poles; 1-50 Amps; 125 VDC, 240 VAC;

UL 1077 Recognized: 1 to 4 poles; 0.1-63 Amps; 80 VDC, 240 VAC/480VAC; cUL, TUV, CSA & CCC.



### Resources:

[Configure a Complete Part](#)

[\*\*Download CAD & Sales Drawing >\*\*](#)

### Product Highlights:

- DIN Rail Mounting
- UL 489 Listed
- UL 1077 Recognized, cUL, TUV, CSA & CCC
- Wiping Contacts
- Common Trip Linkage Between Poles
- Optional Integrated Auxiliary Switch

### Typical Applications:

- Renewable Energy
- Telecom
- Control Panels
- Industrial Automation Controls



**Carling Technologies®**  
Innovative Designs. Powerful Solutions.

**Carling Technologies, Inc.**  
60 Johnson Avenue, Plainville, CT 06062  
Email: [sales@carlingtech.com](mailto:sales@carlingtech.com)  
Application Support: [team2@carlingtech.com](mailto:team2@carlingtech.com)  
Phone: 860.793.9281 Fax: 860.793.9231


[www.carlingtech.com](http://www.carlingtech.com)

# G-Series

## DESIGN FEATURES

### TERMINAL BARRIERS

Meet UL 489 Spacing Requirements



### OPTIONAL AUXILIARY SWITCH

Provides Breaker Status Indication



### DIN RAIL MOUNTING

Snap on Back Panel Rail Mounting for either 35 x 7.5 mm or 35 x 15 mm

### DIN RAIL LOCK

Secures Circuit Breaker to the DIN Rail

## Auxiliary Switch with Internal Connector





### Advantages:

- Pre-wiring is possible
- Easy interchangeable
- Time saving solution
- Various connection methods
- Many different plugs

### Example Plugs:

Spring clamp terminals



Screw terminals



Screw terminals 45° angle



Dimensions in mm

Wire size solid wire 0.2 - 1.5 mm<sup>2</sup>  
 Wire size stranded wire 0.2 - 2.5 mm<sup>2</sup>  
 Wire size stranded wire with ferrule 0.25 - 1.5 mm<sup>2</sup>  
 Wire stripping length 10 mm

The auxiliary contact with internal connector can be used with Phoenix Combicon plugs. Phoenix item number internal connector: 1753453. The circuit breaker is standard delivered without plugs.

\*Manufacturer reserves the right to change product specification without prior notice.

## Electrical Tables

**Table A:** Lists UL Recognized, CSA Accepted and TUV Certified capabilities as a Component Supplementary Protector.

| G-SERIES TABLE A: COMPONENT SUPPLEMENTARY PROTECTORS |            |           |       |               |                |                               |            |                   |              |
|------------------------------------------------------|------------|-----------|-------|---------------|----------------|-------------------------------|------------|-------------------|--------------|
| Circuit Configuration                                | Voltage    |           |       |               | Current Rating | Short Circuit Capacity (Amps) |            |                   |              |
|                                                      | Max Rating | Frequency | Phase | Minimum Poles | Full Load Amps | Without Backup Fuse           |            | Application Codes |              |
|                                                      |            |           |       |               |                | UL/CSA                        | TUV        | UL                | CSA          |
| Series                                               | 80         | DC        | ---   | 1             | .1 - 63        | 3000                          | 1500       | TC1, OL1, U1      | TC1, OL1, U1 |
|                                                      | 240        | 50 / 60   | 1     | 1             | .1 - 63        | 3000                          | 1500       | TC1, OL1, U1      | TC1, OL1, U1 |
|                                                      | 240        | 50 / 60   | 1     | 2             | .1 - 63        | 3000                          | 1500       | TC1, OL1, U1      | TC1, OL1, U1 |
|                                                      | 480        | 50 / 60   | 3     | 3             | .1 - 63        | 1500                          | 415V, 1000 | TC1, OL1, U1      | TC1, OL1, U1 |


**Table B:** Lists UL Listed (489) configuration and performance capabilities.

| G-SERIES TABLE B: UL 489 LISTED BRANCH CIRCUIT BREAKERS |            |           |       |                    |                                  |                                     |
|---------------------------------------------------------|------------|-----------|-------|--------------------|----------------------------------|-------------------------------------|
| Circuit Configuration                                   | Voltage    |           |       |                    | Current Rating<br>Full Load Amps | Interrupting Capacity<br>(Amps RMS) |
|                                                         | Max Rating | Frequency | Phase | Poles              |                                  |                                     |
| Series                                                  | 80         | DC        | ---   | 1                  | 1 - 50                           | 5000                                |
|                                                         | 125        | DC        | ---   | 2                  | 1 - 50                           | 5000                                |
|                                                         | 120        | 50 / 60   | 1     | 1                  | 1 - 50                           | 5000                                |
|                                                         | 120 / 240  | 50 / 60   | 1     | 1 - 3 <sup>1</sup> | 1 - 50                           | 5000                                |
|                                                         | 240        | 50 / 60   | 1     | 1                  | 1 - 25                           | 5000                                |

<sup>1</sup> One pole out of the three poles must be a neutral break.

### Electrical

|                                              |                                                                                                                                                                                                                                                                                                                                                                                                |
|----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Maximum Voltage                              | AC: 240VAC (single pole),<br>480VAC (3 poles, additional pole shall be dedicated for neutral break)<br>DC: 80VDC (single pole & multipole) 0.1 – 63A. Other ratings available, see Ordering Scheme.                                                                                                                                                                                            |
| Current Rating                               | (optional) Integrated, load side. SPST, 3A – 125VAC, 2A – 30VDC. Auxiliary switch senses the on & off position of circuit breaker handle, as well as contact arm position. Switch connections are screw terminals.                                                                                                                                                                             |
| Auxiliary Switch Rating                      | Minimum of 100 Megohms at 500 VDC<br>UL, CSA: 1960 V 50/60 Hz for one minute between all electrically isolated terminals. G-Series circuit breakers comply with the 8mm spacing and 3750V 50/60 Hz dielectric requirements from hazardous voltage to operator accessible surfaces, between adjacent poles and from main circuits to auxiliary circuits per Publications EN 60950 and VDE 0805. |
| Insulation Resistance<br>Dielectric Strength | Values from Line to Load Terminal - based on series trip circuit breaker.                                                                                                                                                                                                                                                                                                                      |
| Resistance, Impedance                        |                                                                                                                                                                                                                                                                                                                                                                                                |



| CURRENT<br>(AMPS) | TOLERANCE<br>(%) |
|-------------------|------------------|
| 0.10 - 5.0        | 15               |
| 5.1 - 20.0        | 25               |
| 20.1 - 63.0       | 35               |

### Mechanical

|                 |                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Endurance       | 10,000 ON-OFF operations @ 6 per minute; with rated current & voltage.                                                                                                                                                                                                                                                                                           |
| Trip Free       | All G-Series circuit breakers will trip on overload, even when actuator is forcibly held in the ON position.                                                                                                                                                                                                                                                     |
| Trip Indication | The operating actuator moves positively to the OFF position when an overload causes the breaker to trip. With mid-trip, the handle moves to the mid position on electrical trip of the circuit breaker. With mid trip handle with alarm switch, handle moves to the mid position and the alarm switch actuates when the circuit breaker is electrically tripped. |

### Physical

|                 |                                      |
|-----------------|--------------------------------------|
| Number of Poles | 1 pole ≤ 63A, 2 poles ≤ 63A per pole |
| Weight          | Approx. 172 grams/pole ( 4.13 oz).   |
| Standard Colors | Housing: Black                       |

### Environmental

|                                                                                                   |                                                                                                                                                                                                                                                                                                                                                  |
|---------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Designed in accordance with requirements of specification MIL-PRF-55629 & MIL-STD-202 as follows: |                                                                                                                                                                                                                                                                                                                                                  |
| Shock                                                                                             | Withstands 100 Gs, 6ms sawtooth while carrying rated current per Method 213, Test Condition "I". Instantaneous and ultrashort curves tested @ 90% of rated current. Withstands 0.060" excursion from 10-55 Hz & 10 Gs 55-500 Hz, @ rated current per Method 204C, Test Cond. A. Instantaneous & ultrashort curves tested @ 90% of rated current. |
| Vibration                                                                                         |                                                                                                                                                                                                                                                                                                                                                  |
| Moisture Resistance                                                                               | Method 106D, i.e., ten 24-hour cycles @ +25°C to +65°C, 80-98% RH.                                                                                                                                                                                                                                                                               |
| Salt Spray                                                                                        | Method 101, Condition A (90-95% RH @ 5% NaCl Solution, 96 hrs).                                                                                                                                                                                                                                                                                  |
| Thermal Shock                                                                                     | Method 107D, Condition A (five cycles @ -55°C to +25°C to +85°C to +25°C).                                                                                                                                                                                                                                                                       |
| Operating Temperature                                                                             | -40°C to +85°C                                                                                                                                                                                                                                                                                                                                   |

|             |               |            |          |              |                          |          |                           |          |                     |          |               |                                    |          |              |                          |
|-------------|---------------|------------|----------|--------------|--------------------------|----------|---------------------------|----------|---------------------|----------|---------------|------------------------------------|----------|--------------|--------------------------|
| <b>G</b>    | <b>A</b>      | <b>1</b>   | <b>-</b> | <b>B</b>     | <b>0</b>                 | <b>-</b> | <b>24</b>                 | <b>-</b> | <b>620</b>          | <b>-</b> | <b>1</b>      | <b>1</b>                           | <b>-</b> | <b>D</b>     | <b>C</b>                 |
| 1<br>Series | 2<br>Actuator | 3<br>Poles |          | 4<br>Circuit | 5<br>Aux/Alarm<br>Switch |          | 6<br>Frequency<br>& Delay |          | 7<br>Current Rating |          | 8<br>Terminal | 9<br>Actuator<br>Color &<br>Legend |          | 10<br>Rating | 11<br>Agency<br>Approval |

#### 1 SERIES

**G**

#### 2 ACTUATOR

- A** Handle, one per pole  
**S** Mid-Trip Handle, one per pole

#### 3 POLES

- 1** One                      **3** Three  
**2** Two                    **4** Four

#### 4 CIRCUIT

- A**<sup>1</sup> Switch Only (no coil)  
**B** Series Trip (current)

#### 5 AUXILIARY / ALARM SWITCH <sup>3</sup>

- 0** without Aux Switch  
**1** S.P.D.T., Screw Terminal  
**3** S.P.D.T. Screw Terminal (Gold Contacts)  
**5** Plug-in Terminal  
**6** Plug-in Terminal (Gold Contacts)

#### 6 FREQUENCY & DELAY

- |                                  |                                                   |
|----------------------------------|---------------------------------------------------|
| <b>03</b> Switch Only            | <b>26</b> 50/60 Hz Long                           |
| <b>10</b> DC, Instantaneous      | <b>42</b> 50/60 Hz High-inrush Short <sup>2</sup> |
| <b>11</b> DC, Ultra Short        | <b>44</b> 50/60 Hz High-inrush Medium             |
| <b>12</b> DC, Short              | <b>46</b> 50/60 Hz High-inrush Long               |
| <b>14</b> DC, Medium             | <b>52</b> DC High-inrush Short                    |
| <b>16</b> DC, Long               | <b>54</b> DC High-inrush Medium                   |
| <b>20</b> 50/60 Hz Instantaneous | <b>56</b> DC High-inrush Long                     |
| <b>21</b> 50/60 Ultra Short      |                                                   |
| <b>22</b> 50/60 Hz Short         |                                                   |
| <b>24</b> 50/60 Hz Medium        |                                                   |

#### 7 CURRENT RATING (AMPERES)

| CODE       | AMPERES |            |       |                   |
|------------|---------|------------|-------|-------------------|
| <b>210</b> | 0.100   | <b>410</b> | 1.000 | <b>470</b> 7.000  |
| <b>220</b> | 0.200   | <b>512</b> | 1.250 | <b>475</b> 7.500  |
| <b>225</b> | 0.250   | <b>415</b> | 1.500 | <b>480</b> 8.000  |
| <b>230</b> | 0.300   | <b>517</b> | 1.750 | <b>485</b> 8.500  |
| <b>235</b> | 0.350   | <b>420</b> | 2.000 | <b>490</b> 9.000  |
| <b>240</b> | 0.400   | <b>522</b> | 2.250 | <b>495</b> 9.500  |
| <b>245</b> | 0.450   | <b>425</b> | 2.500 | <b>610</b> 10.000 |
| <b>250</b> | 0.500   | <b>527</b> | 2.750 | <b>710</b> 10.500 |
| <b>255</b> | 0.550   | <b>430</b> | 3.000 | <b>611</b> 11.000 |
| <b>260</b> | 0.600   | <b>435</b> | 3.500 | <b>711</b> 11.500 |
| <b>265</b> | 0.650   | <b>440</b> | 4.000 | <b>612</b> 12.000 |
| <b>270</b> | 0.700   | <b>445</b> | 4.500 | <b>712</b> 12.500 |
| <b>275</b> | 0.750   | <b>450</b> | 5.000 | <b>613</b> 13.000 |
| <b>280</b> | 0.800   | <b>455</b> | 5.500 | <b>614</b> 14.000 |
| <b>285</b> | 0.850   | <b>460</b> | 6.000 | <b>615</b> 15.000 |
| <b>290</b> | 0.900   | <b>465</b> | 6.500 | <b>616</b> 16.000 |

#### 8 TERMINAL

- 1** Screw Terminal

#### 9 ACTUATOR COLOR & LEGEND

| Actuator Color | I-O      | ON-OFF   | Dual     | Legend Color |
|----------------|----------|----------|----------|--------------|
| White          | <b>A</b> | <b>B</b> | <b>1</b> | Black        |
| Black          | <b>C</b> | <b>D</b> | <b>2</b> | White        |
| Red            | <b>F</b> | <b>G</b> | <b>3</b> | White        |
| Green          | <b>H</b> | <b>J</b> | <b>4</b> | White        |
| Blue           | <b>K</b> | <b>L</b> | <b>5</b> | White        |
| Yellow         | <b>M</b> | <b>N</b> | <b>6</b> | Black        |
| Gray           | <b>P</b> | <b>Q</b> | <b>7</b> | Black        |
| Orange         | <b>R</b> | <b>S</b> | <b>8</b> | Black        |

#### 10 APPLICATION RATING

- B** 125 VDC <sup>5</sup>  
**D** 240 VAC  
**H** 480 VAC <sup>4</sup>  
**M** 80 VDC

#### 11 AGENCY APPROVAL

- A** Without Approvals  
**C** UL Recognized, CSA Accepted  
**E** UL Recognized, CSA Accepted, TUV Certified, CCC Certified

#### Notes:

- <sup>1</sup> Switch only circuit only available when tied to a protected pole (Circuit code B)  
- for .2 to 30 amps select current code 630  
- for 31 to 50 amps select current code 650  
- for 51 to 63 amps select current code 663  
- Use delay 03 for all switch only poles  
<sup>2</sup> Hi Inrush Delays limited to 50A max  
<sup>3</sup> On multi-pole breakers one auxiliary switch is supplied, mounted in the extreme left pole when viewed from front of panel  
<sup>4</sup> 480 VAC rating requires 3 or 4 pole break 3Φ and 2 pole break 1Φ  
<sup>5</sup> This construction is polarity sensitive when constructed as a single pole unit, 125 VDC is only available without agency approvals

|             |               |            |          |              |                          |          |                           |          |                     |          |               |                                    |          |              |                          |
|-------------|---------------|------------|----------|--------------|--------------------------|----------|---------------------------|----------|---------------------|----------|---------------|------------------------------------|----------|--------------|--------------------------|
| <b>G</b>    | <b>A</b>      | <b>1</b>   | <b>-</b> | <b>B</b>     | <b>0</b>                 | <b>-</b> | <b>24</b>                 | <b>-</b> | <b>620</b>          | <b>-</b> | <b>1</b>      | <b>1</b>                           | <b>-</b> | <b>D</b>     | <b>G</b>                 |
| 1<br>Series | 2<br>Actuator | 3<br>Poles |          | 4<br>Circuit | 5<br>Aux/Alarm<br>Switch |          | 6<br>Frequency<br>& Delay |          | 7<br>Current Rating |          | 8<br>Terminal | 9<br>Actuator<br>Color &<br>Legend |          | 10<br>Rating | 11<br>Agency<br>Approval |

#### 1 SERIES

**G**

#### 2 ACTUATOR

- A** Handle, one per pole  
**S**<sup>1</sup> Mid-Trip Handle, one per pole

#### 3 POLES

- 1** One  
**2** Two  
**3** Three

#### 4 CIRCUIT

- B** Series Trip (current)

#### 5 AUXILIARY / ALARM SWITCH<sup>3</sup>

- 0** without Aux Switch  
**1** S.P.D.T., Screw Terminal  
**3** S.P.D.T. Screw Terminal (Gold Contacts)  
**5** Plug-in Terminal  
**6** Plug-in Terminal (Gold Contacts)

#### 6 FREQUENCY & DELAY

- |                             |                                                    |
|-----------------------------|----------------------------------------------------|
| <b>11</b> DC, Ultra Short   | <b>42</b> 50/60 Hz High-inrush Short <sup>4</sup>  |
| <b>12</b> DC, Short         | <b>44</b> 50/60 Hz High-inrush Medium <sup>4</sup> |
| <b>14</b> DC, Medium        | <b>46</b> 50/60 Hz High-inrush Long <sup>4</sup>   |
| <b>16</b> DC, Long          | <b>52</b> DC High-inrush Short <sup>4</sup>        |
| <b>21</b> 50/60 Ultra Short | <b>54</b> DC High-inrush Medium <sup>4</sup>       |
| <b>22</b> 50/60 Hz Short    | <b>56</b> DC High-inrush Long <sup>4</sup>         |
| <b>24</b> 50/60 Hz Medium   |                                                    |
| <b>26</b> 50/60 Hz Long     |                                                    |

#### 7 CURRENT RATING (AMPERES)

| CODE       | AMPERES |            |       |                   |
|------------|---------|------------|-------|-------------------|
| <b>410</b> | 1.000   | <b>445</b> | 4.500 | <b>610</b> 10.000 |
| <b>512</b> | 1.250   | <b>450</b> | 5.000 | <b>710</b> 10.500 |
| <b>415</b> | 1.500   | <b>455</b> | 5.500 | <b>611</b> 11.000 |
| <b>517</b> | 1.750   | <b>460</b> | 6.000 | <b>711</b> 11.500 |
| <b>420</b> | 2.000   | <b>465</b> | 6.500 | <b>612</b> 12.000 |
| <b>522</b> | 2.250   | <b>470</b> | 7.000 | <b>712</b> 12.500 |
| <b>425</b> | 2.500   | <b>475</b> | 7.500 | <b>613</b> 13.000 |
| <b>527</b> | 2.750   | <b>480</b> | 8.000 | <b>614</b> 14.000 |
| <b>430</b> | 3.000   | <b>485</b> | 8.500 | <b>615</b> 15.000 |
| <b>435</b> | 3.500   | <b>490</b> | 9.000 | <b>616</b> 16.000 |
| <b>440</b> | 4.000   | <b>495</b> | 9.500 | <b>617</b> 17.000 |
|            |         |            |       | <b>618</b> 18.000 |
|            |         |            |       | <b>620</b> 20.000 |
|            |         |            |       | <b>622</b> 22.000 |
|            |         |            |       | <b>624</b> 24.000 |
|            |         |            |       | <b>625</b> 25.000 |
|            |         |            |       | <b>630</b> 30.000 |
|            |         |            |       | <b>635</b> 35.000 |
|            |         |            |       | <b>640</b> 40.000 |
|            |         |            |       | <b>650</b> 50.000 |

#### 8 TERMINAL

- 1** Screw Terminal

#### 9 ACTUATOR COLOR & LEGEND

| Actuator Color | ON-OFF   | Dual     | Legend Color |
|----------------|----------|----------|--------------|
| White          | <b>B</b> | <b>1</b> | Black        |
| Black          | <b>D</b> | <b>2</b> | White        |
| Red            | <b>G</b> | <b>3</b> | White        |
| Green          | <b>J</b> | <b>4</b> | White        |
| Blue           | <b>L</b> | <b>5</b> | White        |
| Yellow         | <b>N</b> | <b>6</b> | Black        |
| Gray           | <b>Q</b> | <b>7</b> | Black        |
| Orange         | <b>S</b> | <b>8</b> | Black        |

#### 10 APPLICATION RATING

- B** 125 VDC<sup>5</sup>  
**C** 120/240 VAC<sup>6</sup>  
**D** 240 VAC<sup>7</sup>  
**K** 120 VAC<sup>8</sup>  
**M** 80 VDC<sup>9</sup>

#### 11 AGENCY APPROVAL


- A** Without Approvals  
**G** UL489 Listed

#### Notes:


- 1 Mid-trip Handle(s) available at 1 pole unit and 2 pole unit only.  
2 Third pole of a 3 pole unit is switch only pole.  
3 On multi-pole breakers one auxiliary switch is supplied, mounted in the extreme left pole when viewed from front of panel.  
4 Hi Inrush Delays limited to 50A maximum.  
5 125VDC for 2 pole unit only.  
6 120/240VAC for 2 pole and 3 pole unit only. Limited to 50A maximum, and third pole of a 3-pole unit is switch only pole.  
7 240VAC for 1 pole unit only, limited to 25A maximum.  
8 120VAC for 1 pole unit only, limited to 50A maximum.  
9 80VDC for 1 pole unit only

## Dimensional Specifications: in. [mm]


### 1 POLE WITHOUT AUXILIARY SWITCH




### 1 POLE WITH AUXILIARY SWITCH (PLUG-IN TERMINAL BLOCK)



### 1 POLE WITH AUXILIARY SWITCH (SCREW TERMINAL BLOCK)




### MULTIPLE POLES WITH AUXILIARY SWITCH (PLUG-IN TERMINAL BLOCK)




- Notes:
- 1 All dimensions are in inches [millimeters].
  - 2 Tolerance  $\pm 0.020$  [.51] unless otherwise specified.



### UL RECOGNIZED



### UL489



## Authorized Sales Representatives and Distributors

Click on a region of the map below to find your local representatives and distributors or visit [www.carlingtech.com/findarep](http://www.carlingtech.com/findarep).



## About Carling

Founded in 1920, Carling Technologies is a leading manufacturer of electrical and electronic switches and assemblies, circuit breakers, electronic controls, power distribution units, and multiplexed power distribution systems. With four ISO9001 and IATF16949 registered manufacturing facilities and technical sales offices worldwide, Carling Technologies Sales, Service and Engineering teams do much more than manufacture electrical components, they engineer powerful solutions! To learn more about Carling please visit [www.carlingtech.com/company-profile](http://www.carlingtech.com/company-profile).

To view all of Carling's environmental, quality, health & safety certifications please visit [www.carlingtech.com/environmental-certifications](http://www.carlingtech.com/environmental-certifications)

## **Worldwide Headquarters**

Carling Technologies, Inc.  
60 Johnson Avenue, Plainville, CT 06062  
**Phone:** 860.793.9281 **Fax:** 860.793.9231  
**Email:** sales@carlingtech.com

**Northern Region Sales Office:** nrsm@carlingtech.com  
**Southeast Region Sales Office:** sersm@carlingtech.com  
**Midwest Region Sales Office:** mrsm@carlingtech.com  
**West Region Sales Office:** wrsm@carlingtech.com  
**Latin America Sales Office:** larsm@carlingtech.com

## **Asia-Pacific Headquarters**

Carling Technologies, Asia-Pacific Ltd.,  
Suite 1607, 16/F Tower 2, The Gateway,  
Harbour City, 25 Canton Road,  
Tsimshatsui, Kowloon, Hong Kong  
**Phone:** Int + 852-2737-2277 **Fax:** Int + 852-2736-9332  
**Email:** sales@carlingtech.com.hk

**Shenzhen, China:** shenzhen@carlingtech.com  
**Shanghai, China:** shanghai@carlingtech.com  
**Pune, India:** india@carlingtech.com  
**Kaohsiung, Taiwan:** taiwan@carlingtech.com  
**Yokohama, Japan:** japan@carlingtech.com

## **Europe | Middle East | Africa Headquarters**

Carling Technologies LTD  
4 Airport Business Park, Exeter Airport,  
Clyst Honiton, Exeter, Devon, EX5 2UL, UK  
**Phone:** Int + 44 1392.364422 **Fax:** Int + 44 1392.364477  
**Email:** ltd.sales@carlingtech.com

**Germany:** gmbh@carlingtech.com  
**France:** sas@carlingtech.com



**Carling Technologies®**

Innovative Designs. Powerful Solutions.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9