

## Small Signal Product


### NPN Transistor

#### FEATURES

- Low reverse current, high reliability
- Surface device type mounting
- Moisture sensitivity level 1
- Matte Tin(Sn) lead finish with Nickel(Ni) underplate
- Pb free version and RoHS compliant
- Packing code with suffix "G" means green compound (halogen-free)

#### MECHANICAL DATA

- Case: SOT-323 small outline plastic package
- Terminal: Matte tin plated, lead free., solderable per MIL-STD-202, Method 208 guaranteed
- High temperature soldering guaranteed : 260°C/10s
- Weight: 5 ± 0.5 mg


**SOT-323**


| MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T <sub>A</sub> =25°C unless otherwise noted) |                                   |              |      |
|----------------------------------------------------------------------------------------------|-----------------------------------|--------------|------|
| PARAMETER                                                                                    | SYMBOL                            | VALUE        | UNIT |
| Power Dissipation                                                                            | P <sub>D</sub>                    | 200          | mW   |
| Collector-Base Voltage                                                                       | V <sub>CBO</sub>                  | 80           | V    |
|                                                                                              |                                   | 50           |      |
|                                                                                              |                                   | 30           |      |
|                                                                                              |                                   | 30           |      |
|                                                                                              |                                   | 50           |      |
| Collector-Emitter Voltage                                                                    | V <sub>CEO</sub>                  | 65           | V    |
|                                                                                              |                                   | 45           |      |
|                                                                                              |                                   | 30           |      |
|                                                                                              |                                   | 30           |      |
|                                                                                              |                                   | 45           |      |
| Emitter-Base Voltage                                                                         | V <sub>EBO</sub>                  | 6            | V    |
|                                                                                              |                                   | 6            |      |
|                                                                                              |                                   | 5            |      |
|                                                                                              |                                   | 5            |      |
|                                                                                              |                                   | 5            |      |
| Collector Current                                                                            | I <sub>C</sub>                    | 0.1          | A    |
| Peak Collector Current                                                                       | I <sub>CM</sub>                   | 0.2          | A    |
| Junction and Storage Temperature Range                                                       | T <sub>J</sub> , T <sub>STG</sub> | -55 to + 150 | °C   |

## Small Signal Product

| PARAMETER                                               |                                                | SYMBOL        | MIN  | MAX  | UNIT |
|---------------------------------------------------------|------------------------------------------------|---------------|------|------|------|
| Collector-Base Breakdown Voltage<br>at $I_C = 10 \mu A$ | BC846AW/BW/CW                                  | $V_{CBO}$     | 80   | -    | V    |
|                                                         | BC847AW/BW/CW                                  |               | 50   | -    |      |
|                                                         | BC848AW/BW/CW                                  |               | 30   | -    |      |
|                                                         | BC849AW/BW/CW                                  |               | 30   | -    |      |
|                                                         | BC850AW/BW/CW                                  |               | 50   | -    |      |
| Collector-Emitter Breakdown Voltage<br>at $I_C = 10 mA$ | BC846AW/BW/CW                                  | $V_{(BR)CEO}$ | 65   | -    | V    |
|                                                         | BC847AW/BW/CW                                  |               | 45   | -    |      |
|                                                         | BC848AW/BW/CW                                  |               | 30   | -    |      |
|                                                         | BC849AW/BW/CW                                  |               | 30   | -    |      |
|                                                         | BC850AW/BW/CW                                  |               | 45   | -    |      |
| Emitter-Base Breakdown Voltage<br>at $I_E = 1 \mu A$    | BC846AW/BW/CW                                  | $V_{EBO}$     | 6    | -    | V    |
|                                                         | BC847AW/BW/CW                                  |               | 6    | -    |      |
|                                                         | BC848AW/BW/CW                                  |               | 5    | -    |      |
|                                                         | BC849AW/BW/CW                                  |               | 5    | -    |      |
|                                                         | BC850AW/BW/CW                                  |               | 5    | -    |      |
| Collector Cut-off Current at $V_{CB} = 30 V$            |                                                | $I_{CBO}$     | -    | 15   | nA   |
| Emitter Cut-off Current at $V_{EB} = 5 V$               |                                                | $I_{EBO}$     | -    | 100  | nA   |
| DC Current Gain<br>at $V_{CE} = 5 V$ , $I_C = 2 mA$     | BC846AW - BC850AW                              | $h_{FE}$      | 110  | 220  | -    |
|                                                         | BC846BW - BC850BW                              |               | 200  | 450  | -    |
|                                                         | BC846CW - BC850CW                              |               | 420  | 800  | -    |
| Collector-Emitter Saturation Voltage                    | $I_C = 10 mA$ , $I_B = 0.5 mA$                 | $V_{CE(sat)}$ | -    | 0.25 | V    |
|                                                         | $I_C = 100 mA$ , $I_B = 5 mA$                  |               | -    | 0.60 |      |
| Transition Frequency                                    | $V_{CE} = 5 V$ , $I_C = 10 mA$ , $f = 100 MHz$ | $f_T$         | 100  | -    | MHz  |
| Base Emitter Voltage                                    | $V_{CE} = 5 V$ , $I_C = 2 mA$                  | $V_{BE}$      | 0.58 | 0.70 | V    |
|                                                         | $V_{CE} = 5 V$ , $I_C = 10 mA$                 |               | -    | 0.77 |      |
| Collector Output Capacitance                            | $V_{CB} = 10 V$ , $I_E = 0$ , $f = 1 MHz$      | $C_{ob}$      | -    | 4.50 | pF   |

## Small Signal Product

### RATINGS AND CHARACTERISTICS CURVES

( $T_A=25^\circ\text{C}$  unless otherwise noted)

Fig.1 Normalized DC Current Gain




Fig.2 "Saturation" and "On" Voltages




Fig.3 Collector Saturation Region




Fig.4 Base-Emitter Current (mA)




Fig.5 Capacitances





Fig.6 Current-Gain-Bandwidth Product



Small Signal Product

Fig.7 DC Collector Current (mA)




Fig. 8 "On" Voltage




Fig.9 Collector Saturation Region




Fig.4 Bae-Emitter Temperature Coefficient




Fig.11 Capacitance






Fig.12 Current-Gain-Bandwidth Product




Small Signal Product

ORDER INFORMATION (EXAMPLE)

BC846AW RFG




PACKAGE OUTLINE DIMENSIONS  
**SOT-323**



| DIM. | Unit (mm) |      | Unit (inch) |       |
|------|-----------|------|-------------|-------|
|      | Min       | Max  | Min         | Max   |
| A    | 1.80      | 2.20 | 0.071       | 0.087 |
| B    | 1.15      | 1.35 | 0.045       | 0.053 |
| C    | 0.15      | 0.40 | 0.006       | 0.016 |
| D    | 1.20      | 1.40 | 0.047       | 0.055 |
| E    | 2.00      | 2.45 | 0.079       | 0.096 |
| F    | 0.80      | 1.10 | 0.031       | 0.043 |

SUGGEST PAD LAYOUT



| DIM. | Unit (mm) | Unit (inch) |
|------|-----------|-------------|
|      | Typ.      | Typ.        |
| Z    | 2.80      | 0.110       |
| X    | 0.70      | 0.028       |
| Y    | 0.90      | 0.035       |
| C    | 1.90      | 0.075       |
| E    | 1.00      | 0.039       |

MARKING

| Part No. | Marking |
|----------|---------|
| BC846AW  | 1A      |
| BC847AW  | 1E      |
| BC848AW  | 1E      |
| BC849AW  | 1E      |
| BC850AW  | 1E      |

| Part No. | Marking |
|----------|---------|
| BC846BW  | 1B      |
| BC847BW  | 1F      |
| BC848BW  | 1F      |
| BC849BW  | 1F      |
| BC850BW  | 1F      |

| Part No. | Marking |
|----------|---------|
| BC846CW  | 1C      |
| BC847CW  | 1G      |
| BC848CW  | 1G      |
| BC849CW  | 1G      |
| BC850CW  | 1G      |

Small Signal Product

### Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9