

# Type 947D Polypropylene, High Energy Density, DC Link Capacitors

## High Current, High Capacitance for Inverter Applications




Type 947D series uses the most advanced metallized film technology for long life and high reliability in DC Link applications. This series combines high capacitance and very high ripple current capability needed for today’s inverter designs for wind, solar, fuel cells, UPS systems and more.

### Specifications

|                                                |                                       |
|------------------------------------------------|---------------------------------------|
| Capacitance Range                              | 130 to 1500 µF                        |
| Capacitance Tolerance                          | ±10% standard                         |
| Rated Voltage                                  | 900 to 1300 Vdc                       |
| Operating Temperature Range                    | -45 °C to 85 °C (ambient)             |
| Maximum rms Current                            | see data tables                       |
| Maximum rms Voltage                            | 230 Vac                               |
| Test Voltage between Terminals @ 25 °C         | 150% rated DC voltage for 10 s        |
| Test Voltage between Terminals and Case @ 25°C | 4 kVac @ 50/60 Hz for 10 s            |
| Life Test                                      | 7000 h @ 85 °C, rated voltage         |
| Life Expectancy                                | 350,000 h @ 60 °C Core, rated voltage |
| RoHS Compliant                                 |                                       |

### Dimensions

| Construction Details   |                       |
|------------------------|-----------------------|
| Case Material          | Aluminum Can          |
| Resin Material         | Dry Resin UL94V-0     |
| Terminal Material      | Tin Plated Brass      |
| Insulator Cap Material | Polypropylene UL94V-0 |



All dimensions have a ±1 mm tolerance  
Consult factory for mounting options

# Type 947D Polypropylene, High Energy Density, DC Link Capacitors

## High Current, High Capacitance for Inverter Applications

### Part Numbering System

| 947D | 391                           | K         | 112                                                                                   | C                                                  | E                                                                                                          | R                                                                                                                                            | S                              | N                              |
|------|-------------------------------|-----------|---------------------------------------------------------------------------------------|----------------------------------------------------|------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|--------------------------------|
| Type | Capacitance                   | Tolerance | Voltage                                                                               | Diameter ±1mm                                      | Height ±1mm                                                                                                | Terminal                                                                                                                                     | Mounting                       | Sleeve                         |
| 947D | 391 = 390 µF<br>152 = 1500 µF | K = ±10%  | 901 = 900 Vdc<br>102 = 1000 Vdc<br>112 = 1100 Vdc<br>122 = 1200 Vdc<br>132 = 1300 Vdc | A = 85 mm<br>B = 90 mm<br>C = 100 mm<br>D = 116 mm | C = 75 mm<br>D = 87 mm<br>E = 100 mm<br>F = 112 mm<br>G = 126 mm<br>H = 136 mm<br>J = 150 mm<br>L = 162 mm | G = M6 Insert (32 mm)<br>N = M8 Stud (32 mm)<br>J = M8 Stud (45 mm)<br>M = M6 Insert (45 mm)<br>P = M8 Stud (50 mm)<br>R = M6 Insert (50 mm) | F = Flat Base<br>S = Stud Base | N = No Sleeve<br>S = Black PVC |

### Ratings

|                  | Rated | Can                | Can      | Lead   | Current |                    | Thermal               |      |      |                 |                 |      |
|------------------|-------|--------------------|----------|--------|---------|--------------------|-----------------------|------|------|-----------------|-----------------|------|
|                  | Cap   | Voltage            | Diameter | Height | Spacing | Case               | T <sub>A</sub> =55 °C | Typ  | Typ  | Resistance      |                 | Max  |
| PartNumber       | C     | V <sub>R</sub>     | D        | H      | S       | Area               | I <sub>rms</sub>      | ESR  | ESL  | Θ <sub>cc</sub> | Θ <sub>ca</sub> | Mass |
|                  | (µF)  | (V <sub>DC</sub> ) | (mm)     | (mm)   | (mm)    | (mm <sup>2</sup> ) | (A)                   | (mΩ) | (nH) | (°C/W)          | (°C/W)          | (kg) |
| 947D311K901ACGSN | 310   | 900                | 85       | 75     | 32      | 31400              | 67                    | 1.4  | 30   | 1.4             | 3.8             | 0.5  |
| 947D351K901BCMSN | 350   | 900                | 90       | 75     | 45      | 33900              | 73                    | 1.2  | 30   | 1.3             | 3.5             | 0.6  |
| 947D371K901ADGSN | 370   | 900                | 85       | 87     | 32      | 34600              | 66                    | 1.5  | 34   | 1.3             | 3.5             | 0.6  |
| 947D421K901BDMSN | 420   | 900                | 90       | 87     | 45      | 37300              | 75                    | 1.2  | 33   | 1.3             | 3.2             | 0.6  |
| 947D441K901AEGSN | 440   | 900                | 85       | 100    | 32      | 38100              | 65                    | 1.7  | 38   | 1.2             | 3.2             | 0.6  |
| 947D441K901CCRSN | 440   | 900                | 100      | 75     | 50      | 39300              | 85                    | 1.0  | 30   | 1.1             | 3.1             | 0.7  |
| 947D501K901BEMSN | 500   | 900                | 90       | 100    | 45      | 41000              | 74                    | 1.3  | 37   | 1.3             | 2.9             | 0.7  |
| 947D511K901AFGSN | 510   | 900                | 85       | 112    | 32      | 41300              | 64                    | 1.9  | 42   | 1.2             | 2.9             | 0.7  |
| 947D541K901CDRSN | 540   | 900                | 100      | 87     | 50      | 43000              | 83                    | 1.2  | 34   | 1.1             | 2.8             | 0.8  |
| 947D571K901AGGSN | 570   | 900                | 85       | 126    | 32      | 45000              | 63                    | 2.1  | 46   | 1.1             | 2.7             | 0.8  |
| 947D581K901BFMSN | 580   | 900                | 90       | 112    | 45      | 44400              | 72                    | 1.5  | 41   | 1.3             | 2.7             | 0.8  |
| 947D601K901DCRSN | 600   | 900                | 116      | 75     | 50      | 48500              | 102                   | 0.9  | 35   | 0.8             | 2.5             | 0.9  |
| 947D631K901CERSN | 630   | 900                | 100      | 100    | 50      | 47100              | 82                    | 1.3  | 38   | 1.0             | 2.5             | 0.9  |
| 947D641K901AHGSN | 640   | 900                | 85       | 136    | 32      | 47700              | 62                    | 2.3  | 50   | 1.1             | 2.5             | 0.8  |
| 947D651K901BGMSN | 650   | 900                | 90       | 126    | 45      | 48300              | 71                    | 1.6  | 45   | 1.2             | 2.5             | 0.9  |
| 947D711K901AJGSN | 710   | 900                | 85       | 150    | 32      | 51400              | 62                    | 2.5  | 54   | 1.1             | 2.3             | 0.9  |
| 947D731K901BHMSN | 730   | 900                | 90       | 136    | 45      | 51200              | 69                    | 1.8  | 49   | 1.2             | 2.3             | 0.9  |
| 947D731K901CFRSN | 730   | 900                | 100      | 112    | 50      | 50900              | 81                    | 1.4  | 42   | 1.0             | 2.4             | 1.0  |
| 947D731K901DDRSN | 730   | 900                | 116      | 87     | 50      | 52800              | 101                   | 1.0  | 40   | 0.8             | 2.3             | 1.1  |
| 947D781K901ALGSN | 780   | 900                | 85       | 162    | 32      | 54600              | 61                    | 2.7  | 59   | 1.0             | 2.2             | 1.0  |
| 947D811K901BJMSN | 810   | 900                | 90       | 150    | 45      | 55100              | 68                    | 1.9  | 53   | 1.2             | 2.2             | 1.0  |
| 947D821K901CGRSN | 820   | 900                | 100      | 126    | 50      | 55300              | 80                    | 1.6  | 46   | 1.0             | 2.2             | 1.1  |
| 947D861K901DERSN | 860   | 900                | 116      | 100    | 50      | 57600              | 100                   | 1.1  | 45   | 0.8             | 2.1             | 1.2  |
| 947D881K901BLMSN | 880   | 900                | 90       | 162    | 45      | 58500              | 67                    | 2.1  | 58   | 1.2             | 2.1             | 1.1  |
| 947D921K901CHRSN | 920   | 900                | 100      | 136    | 50      | 58400              | 79                    | 1.7  | 50   | 1.0             | 2.1             | 1.2  |
| 947D991K901DFRSN | 990   | 900                | 116      | 112    | 50      | 62000              | 99                    | 1.2  | 50   | 0.8             | 1.9             | 1.3  |
| 947D102K901CJRSN | 1000  | 900                | 100      | 150    | 50      | 62800              | 78                    | 1.9  | 54   | 0.9             | 1.9             | 1.3  |
| 947D112K901CLRSN | 1100  | 900                | 100      | 162    | 50      | 66600              | 77                    | 2.0  | 59   | 0.9             | 1.8             | 1.4  |
| 947D112K901DGRSN | 1100  | 900                | 116      | 126    | 50      | 67100              | 98                    | 1.3  | 55   | 0.8             | 1.8             | 1.5  |
| 947D122K901DHRSN | 1200  | 900                | 116      | 136    | 50      | 70700              | 96                    | 1.4  | 60   | 0.8             | 1.7             | 1.6  |
| 947D132K901DJRSN | 1300  | 900                | 116      | 150    | 50      | 75800              | 95                    | 1.5  | 65   | 0.8             | 1.6             | 1.7  |
| 947D152K901DLRSN | 1500  | 900                | 116      | 162    | 50      | 80200              | 94                    | 1.6  | 70   | 0.7             | 1.5             | 1.8  |
| 947D241K102ACGSN | 240   | 1000               | 85       | 75     | 32      | 31400              | 63                    | 1.5  | 30   | 1.4             | 3.8             | 0.5  |

# Type 947D Polypropylene, High Energy Density, DC Link Capacitors

## High Current, High Capacitance for Inverter Applications

|                  | Rated | Can                | Can  | Lead   | Current |                    | Thermal               |      |      |                 |                 |      |
|------------------|-------|--------------------|------|--------|---------|--------------------|-----------------------|------|------|-----------------|-----------------|------|
|                  | Cap   | Voltage            | Dia  | Height | Spacing | Case               | T <sub>A</sub> =55 °C | Typ  | Typ  | Resistance      |                 | Max  |
| PartNumber       | C     | V <sub>R</sub>     | D    | H      | S       | Area               | I <sub>rms</sub>      | ESR  | ESL  | Θ <sub>cc</sub> | Θ <sub>ca</sub> | Mass |
|                  | (μF)  | (V <sub>DC</sub> ) | (mm) | (mm)   | (mm)    | (mm <sup>2</sup> ) | (A)                   | (mΩ) | (nH) | (°C/W)          | (°C/W)          | (kg) |
| 947D271K102BCMSN | 270   | 1000               | 90   | 75     | 45      | 33900              | 69                    | 1.3  | 30   | 1.3             | 3.5             | 0.6  |
| 947D291K102ADGSN | 290   | 1000               | 85   | 87     | 32      | 34600              | 62                    | 1.7  | 34   | 1.4             | 3.5             | 0.6  |
| 947D331K102BDMSN | 330   | 1000               | 90   | 87     | 45      | 37300              | 71                    | 1.3  | 33   | 1.3             | 3.2             | 0.6  |
| 947D341K102AEGSN | 340   | 1000               | 85   | 100    | 32      | 38100              | 61                    | 1.9  | 38   | 1.3             | 3.2             | 0.6  |
| 947D341K102CCRSN | 340   | 1000               | 100  | 75     | 50      | 39300              | 81                    | 1.1  | 30   | 1.2             | 3.1             | 0.7  |
| 947D391K102BEMSN | 390   | 1000               | 90   | 100    | 45      | 41000              | 70                    | 1.5  | 37   | 1.2             | 2.9             | 0.7  |
| 947D401K102AFGSN | 400   | 1000               | 85   | 112    | 32      | 41300              | 60                    | 2.1  | 42   | 1.2             | 2.9             | 0.7  |
| 947D421K102CDRSN | 420   | 1000               | 100  | 87     | 50      | 43000              | 79                    | 1.3  | 34   | 1.1             | 2.8             | 0.8  |
| 947D451K102AGGSN | 450   | 1000               | 85   | 126    | 32      | 45000              | 60                    | 2.3  | 46   | 1.2             | 2.7             | 0.8  |
| 947D451K102BFMSN | 450   | 1000               | 90   | 112    | 45      | 44400              | 68                    | 1.7  | 41   | 1.2             | 2.7             | 0.8  |
| 947D471K102DCRSN | 470   | 1000               | 116  | 75     | 50      | 48500              | 98                    | 0.9  | 35   | 0.9             | 2.5             | 0.9  |
| 947D491K102CERSN | 490   | 1000               | 100  | 100    | 50      | 47100              | 78                    | 1.4  | 38   | 1.1             | 2.5             | 0.9  |
| 947D501K102AHGSN | 500   | 1000               | 85   | 136    | 32      | 47700              | 58                    | 2.5  | 50   | 1.1             | 2.5             | 0.8  |
| 947D511K102BGMSN | 510   | 1000               | 90   | 126    | 45      | 48300              | 67                    | 1.8  | 45   | 1.2             | 2.5             | 0.9  |
| 947D551K102AJGSN | 550   | 1000               | 85   | 150    | 32      | 51400              | 58                    | 2.7  | 54   | 1.1             | 2.3             | 0.9  |
| 947D571K102BHMSN | 570   | 1000               | 90   | 136    | 45      | 51200              | 66                    | 2.0  | 49   | 1.2             | 2.3             | 0.9  |
| 947D571K102CFRSN | 570   | 1000               | 100  | 112    | 50      | 50900              | 77                    | 1.6  | 42   | 1.0             | 2.4             | 1.0  |
| 947D571K102DDRSN | 570   | 1000               | 116  | 87     | 50      | 52800              | 96                    | 1.0  | 40   | 0.8             | 2.3             | 1.1  |
| 947D601K102ALGSN | 600   | 1000               | 85   | 162    | 32      | 54600              | 57                    | 3.0  | 59   | 1.1             | 2.2             | 1.0  |
| 947D631K102BJMSN | 630   | 1000               | 90   | 150    | 45      | 55100              | 65                    | 2.2  | 53   | 1.1             | 2.2             | 1.0  |
| 947D641K102CGRSN | 640   | 1000               | 100  | 126    | 50      | 55300              | 76                    | 1.7  | 46   | 1.0             | 2.2             | 1.1  |
| 947D671K102DERSN | 670   | 1000               | 116  | 100    | 50      | 57600              | 95                    | 1.2  | 45   | 0.8             | 2.1             | 1.2  |
| 947D691K102BLMSN | 690   | 1000               | 90   | 162    | 45      | 58500              | 64                    | 2.3  | 58   | 1.1             | 2.1             | 1.1  |
| 947D721K102CHRSN | 720   | 1000               | 100  | 136    | 50      | 58400              | 74                    | 1.9  | 50   | 1.0             | 2.1             | 1.2  |
| 947D771K102DFRSN | 770   | 1000               | 116  | 112    | 50      | 62000              | 94                    | 1.3  | 50   | 0.8             | 1.9             | 1.3  |
| 947D791K102CJRSN | 790   | 1000               | 100  | 150    | 50      | 62800              | 74                    | 2.1  | 54   | 1.0             | 1.9             | 1.3  |
| 947D871K102CLRSN | 870   | 1000               | 100  | 162    | 50      | 66600              | 73                    | 2.2  | 59   | 0.9             | 1.8             | 1.4  |
| 947D871K102DGRSN | 870   | 1000               | 116  | 126    | 50      | 67100              | 93                    | 1.4  | 55   | 0.8             | 1.8             | 1.5  |
| 947D971K102DHRSN | 970   | 1000               | 116  | 136    | 50      | 70700              | 91                    | 1.5  | 60   | 0.8             | 1.7             | 1.6  |
| 947D102K102DJRSN | 1000  | 1000               | 116  | 150    | 50      | 75800              | 90                    | 1.7  | 65   | 0.8             | 1.6             | 1.7  |
| 947D112K102DLRSN | 1100  | 1000               | 116  | 162    | 50      | 80200              | 89                    | 1.8  | 70   | 0.8             | 1.5             | 1.8  |
| 947D191K112ACGSN | 190   | 1100               | 85   | 75     | 32      | 31400              | 60                    | 1.6  | 30   | 1.5             | 3.8             | 0.5  |
| 947D221K112BCMSN | 220   | 1100               | 90   | 75     | 45      | 33900              | 65                    | 1.5  | 30   | 1.4             | 3.5             | 0.6  |
| 947D231K112ADGSN | 230   | 1100               | 85   | 87     | 32      | 34600              | 59                    | 1.9  | 34   | 1.4             | 3.5             | 0.6  |
| 947D261K112BDMSN | 260   | 1100               | 90   | 87     | 45      | 37300              | 68                    | 1.5  | 33   | 1.2             | 3.2             | 0.6  |
| 947D271K112AEGSN | 270   | 1100               | 85   | 100    | 32      | 38100              | 58                    | 2.1  | 38   | 1.3             | 3.2             | 0.6  |
| 947D271K112CCRSN | 270   | 1100               | 100  | 75     | 50      | 39300              | 77                    | 1.2  | 30   | 1.2             | 3.1             | 0.7  |
| 947D311K112BEMSN | 310   | 1100               | 90   | 100    | 45      | 41000              | 67                    | 1.7  | 37   | 1.2             | 2.9             | 0.7  |
| 947D321K112AFGSN | 320   | 1100               | 85   | 112    | 32      | 41300              | 57                    | 2.3  | 42   | 1.3             | 2.9             | 0.7  |
| 947D331K112CDRSN | 330   | 1100               | 100  | 87     | 50      | 43000              | 75                    | 1.4  | 34   | 1.1             | 2.8             | 0.8  |
| 947D361K112AGGSN | 360   | 1100               | 85   | 126    | 32      | 45000              | 56                    | 2.5  | 46   | 1.2             | 2.7             | 0.8  |
| 947D361K112BFMSN | 360   | 1100               | 90   | 112    | 45      | 44400              | 65                    | 1.8  | 41   | 1.2             | 2.7             | 0.8  |

# Type 947D Polypropylene, High Energy Density, DC Link Capacitors

## High Current, High Capacitance for Inverter Applications

|                  | Rated | Can                | Can  | Lead   | Current |                    |                       | Thermal |      |                 |                 |      |
|------------------|-------|--------------------|------|--------|---------|--------------------|-----------------------|---------|------|-----------------|-----------------|------|
|                  | Cap   | Voltage            | Dia  | Height | Spacing | Case               | T <sub>A</sub> =55 °C | Typ     | Typ  | Resistance      | Max             |      |
| PartNumber       | C     | V <sub>R</sub>     | D    | H      | S       | Area               | I <sub>rms</sub>      | ESR     | ESL  | Θ <sub>cc</sub> | Θ <sub>ca</sub> | Mass |
|                  | (μF)  | (V <sub>DC</sub> ) | (mm) | (mm)   | (mm)    | (mm <sup>2</sup> ) | (A)                   | (mΩ)    | (nH) | (°C/W)          | (°C/W)          | (kg) |
| 947D371K112DCRSN | 370   | 1100               | 116  | 75     | 50      | 48500              | 94                    | 1.0     | 35   | 0.9             | 2.5             | 0.9  |
| 947D391K112CERSN | 390   | 1100               | 100  | 100    | 50      | 47100              | 74                    | 1.6     | 38   | 1.1             | 2.5             | 0.9  |
| 947D411K112BGMSN | 410   | 1100               | 90   | 126    | 45      | 48300              | 64                    | 2.0     | 45   | 1.1             | 2.5             | 0.9  |
| 947D421K112AHGSN | 420   | 1100               | 85   | 136    | 32      | 47700              | 55                    | 2.8     | 50   | 1.2             | 2.5             | 0.8  |
| 947D441K112AJGSN | 440   | 1100               | 85   | 150    | 32      | 51400              | 55                    | 3.0     | 54   | 1.1             | 2.3             | 0.9  |
| 947D451K112CFRSN | 450   | 1100               | 100  | 112    | 50      | 50900              | 73                    | 1.7     | 42   | 1.1             | 2.4             | 1.0  |
| 947D451K112DDRSN | 450   | 1100               | 116  | 87     | 50      | 52800              | 92                    | 1.1     | 40   | 0.9             | 2.3             | 1.1  |
| 947D461K112BHMSN | 460   | 1100               | 90   | 136    | 45      | 51200              | 63                    | 2.2     | 49   | 1.1             | 2.3             | 0.9  |
| 947D481K112ALGSN | 480   | 1100               | 85   | 162    | 32      | 54600              | 54                    | 3.2     | 59   | 1.1             | 2.2             | 1.0  |
| 947D501K112BJMSN | 500   | 1100               | 90   | 150    | 45      | 55100              | 62                    | 2.4     | 53   | 1.1             | 2.2             | 1.0  |
| 947D521K112CGRSN | 520   | 1100               | 100  | 126    | 50      | 55300              | 72                    | 1.9     | 46   | 1.0             | 2.2             | 1.1  |
| 947D541K112DERSN | 540   | 1100               | 116  | 100    | 50      | 57600              | 91                    | 1.3     | 45   | 0.8             | 2.1             | 1.2  |
| 947D551K112BLMSN | 550   | 1100               | 90   | 162    | 45      | 58500              | 61                    | 2.6     | 58   | 1.1             | 2.1             | 1.1  |
| 947D581K112CHRSN | 580   | 1100               | 100  | 136    | 50      | 58400              | 71                    | 2.1     | 50   | 1.0             | 2.1             | 1.2  |
| 947D621K112DFRSN | 620   | 1100               | 116  | 112    | 50      | 62000              | 90                    | 1.4     | 50   | 0.8             | 1.9             | 1.3  |
| 947D641K112CJRSN | 640   | 1100               | 100  | 150    | 50      | 62800              | 70                    | 2.2     | 54   | 1.0             | 1.9             | 1.3  |
| 947D701K112CLRSN | 700   | 1100               | 100  | 162    | 50      | 66600              | 69                    | 2.4     | 59   | 1.0             | 1.8             | 1.4  |
| 947D701K112DGRSN | 700   | 1100               | 116  | 126    | 50      | 67100              | 89                    | 1.5     | 55   | 0.8             | 1.8             | 1.5  |
| 947D781K112DHRSN | 780   | 1100               | 116  | 136    | 50      | 70700              | 87                    | 1.7     | 60   | 0.8             | 1.7             | 1.6  |
| 947D861K112DJRSN | 860   | 1100               | 116  | 150    | 50      | 75800              | 86                    | 1.8     | 65   | 0.8             | 1.6             | 1.7  |
| 947D941K112DLRSN | 940   | 1100               | 116  | 162    | 50      | 80200              | 85                    | 1.9     | 70   | 0.8             | 1.5             | 1.8  |
| 947D151K122ACGSN | 150   | 1200               | 85   | 75     | 32      | 31400              | 57                    | 1.8     | 30   | 1.5             | 3.8             | 0.5  |
| 947D181K122BCMSN | 180   | 1200               | 90   | 75     | 45      | 33900              | 62                    | 1.6     | 30   | 1.4             | 3.5             | 0.6  |
| 947D191K122ADGSN | 190   | 1200               | 85   | 87     | 32      | 34600              | 56                    | 2.0     | 34   | 1.4             | 3.5             | 0.6  |
| 947D221K122AEGSN | 220   | 1200               | 85   | 100    | 32      | 38100              | 55                    | 2.3     | 38   | 1.4             | 3.2             | 0.6  |
| 947D221K122BDMSN | 220   | 1200               | 90   | 87     | 45      | 37300              | 65                    | 1.6     | 33   | 1.2             | 3.2             | 0.6  |
| 947D221K122CCRSN | 220   | 1200               | 100  | 75     | 50      | 39300              | 73                    | 1.3     | 30   | 1.2             | 3.1             | 0.7  |
| 947D251K122BEMSN | 250   | 1200               | 90   | 100    | 45      | 41000              | 64                    | 1.8     | 37   | 1.1             | 2.9             | 0.7  |
| 947D261K122AFGSN | 260   | 1200               | 85   | 112    | 32      | 41300              | 54                    | 2.5     | 42   | 1.3             | 2.9             | 0.7  |
| 947D271K122CDRSN | 270   | 1200               | 100  | 87     | 50      | 43000              | 72                    | 1.5     | 34   | 1.2             | 2.8             | 0.8  |
| 947D291K122AGGSN | 290   | 1200               | 85   | 126    | 32      | 45000              | 54                    | 2.8     | 46   | 1.2             | 2.7             | 0.8  |
| 947D291K122BFMSN | 290   | 1200               | 90   | 112    | 45      | 44400              | 62                    | 2.0     | 41   | 1.1             | 2.7             | 0.8  |
| 947D311K122DCRSN | 310   | 1200               | 116  | 75     | 50      | 48500              | 90                    | 1.1     | 35   | 0.9             | 2.5             | 0.9  |
| 947D321K122CERSN | 320   | 1200               | 100  | 100    | 50      | 47100              | 71                    | 1.7     | 38   | 1.1             | 2.5             | 0.9  |
| 947D331K122AHGSN | 330   | 1200               | 85   | 136    | 32      | 47700              | 53                    | 3.0     | 50   | 1.2             | 2.5             | 0.8  |
| 947D331K122BGMSN | 330   | 1200               | 90   | 126    | 45      | 48300              | 61                    | 2.2     | 45   | 1.1             | 2.5             | 0.9  |
| 947D361K122AJGSN | 360   | 1200               | 85   | 150    | 32      | 51400              | 52                    | 3.3     | 54   | 1.2             | 2.3             | 0.9  |
| 947D371K122BHMSN | 370   | 1200               | 90   | 136    | 45      | 51200              | 60                    | 2.4     | 49   | 1.1             | 2.3             | 0.9  |
| 947D371K122CFRSN | 370   | 1200               | 100  | 112    | 50      | 50900              | 69                    | 1.9     | 42   | 1.1             | 2.4             | 1.0  |
| 947D371K122DDRSN | 370   | 1200               | 116  | 87     | 50      | 52800              | 88                    | 1.2     | 40   | 0.9             | 2.3             | 1.1  |
| 947D401K122ALGSN | 400   | 1200               | 85   | 162    | 32      | 54600              | 52                    | 3.5     | 59   | 1.1             | 2.2             | 1.0  |
| 947D411K122BJMSN | 410   | 1200               | 90   | 150    | 45      | 55100              | 59                    | 2.6     | 53   | 1.1             | 2.2             | 1.0  |

# Type 947D Polypropylene, High Energy Density, DC Link Capacitors

## High Current, High Capacitance for Inverter Applications

| PartNumber        | Cap  | Rated              | Can  | Can    | Lead    | Current            |                       | Thermal |      | Resistance      |                 | Max  |
|-------------------|------|--------------------|------|--------|---------|--------------------|-----------------------|---------|------|-----------------|-----------------|------|
|                   | C    | Voltage            | Dia  | Height | Spacing | Case               | T <sub>A</sub> =55 °C | Typ     | Typ  | Θ <sub>cc</sub> | Θ <sub>ca</sub> | Mass |
|                   | (μF) | (V <sub>DC</sub> ) | (mm) | (mm)   | (mm)    | (mm <sup>2</sup> ) | (A)                   | (mΩ)    | (nH) | (°C/W)          | (°C/W)          | (kg) |
| 947D421K122CGRSN  | 420  | 1200               | 100  | 126    | 50      | 55300              | 69                    | 2.1     | 46   | 1.1             | 2.2             | 1.1  |
| 947D441K122DERSN  | 440  | 1200               | 116  | 100    | 50      | 57600              | 87                    | 1.4     | 45   | 0.9             | 2.1             | 1.2  |
| 947D451K122BLMSN  | 450  | 1200               | 90   | 162    | 45      | 58500              | 58                    | 2.8     | 58   | 1.0             | 2.1             | 1.1  |
| 947D471K122CHRSN  | 470  | 1200               | 100  | 136    | 50      | 58400              | 67                    | 2.2     | 50   | 1.0             | 2.1             | 1.2  |
| 947D511K122DFRSN  | 510  | 1200               | 116  | 112    | 50      | 62000              | 86                    | 1.5     | 50   | 0.8             | 1.9             | 1.3  |
| 947D521K122CJRSN  | 520  | 1200               | 100  | 150    | 50      | 62800              | 67                    | 2.4     | 54   | 1.0             | 1.9             | 1.3  |
| 947D571K122CLRSN  | 570  | 1200               | 100  | 162    | 50      | 66600              | 66                    | 2.6     | 59   | 1.0             | 1.8             | 1.4  |
| 947D571K122DGRSN  | 570  | 1200               | 116  | 126    | 50      | 67100              | 85                    | 1.6     | 55   | 0.8             | 1.8             | 1.5  |
| 947D641K122DHRSN  | 640  | 1200               | 116  | 136    | 50      | 70700              | 83                    | 1.8     | 60   | 0.8             | 1.7             | 1.6  |
| 947D711K122DJRSN  | 710  | 1200               | 116  | 150    | 50      | 75800              | 82                    | 1.9     | 65   | 0.8             | 1.6             | 1.7  |
| 947D771K122DLRSN  | 770  | 1200               | 116  | 162    | 50      | 80200              | 81                    | 2.1     | 70   | 0.8             | 1.5             | 1.8  |
| 947D131K132ACGSN  | 130  | 1300               | 85   | 75     | 32      | 31400              | 54                    | 1.9     | 30   | 1.6             | 3.8             | 0.5  |
| 947D151K132BCMSN  | 150  | 1300               | 90   | 75     | 45      | 33900              | 60                    | 1.7     | 30   | 1.5             | 3.5             | 0.6  |
| 947D161K132ADGSN  | 160  | 1300               | 85   | 87     | 32      | 34600              | 53                    | 2.2     | 34   | 1.5             | 3.5             | 0.6  |
| 947D181K132BDMSEN | 180  | 1300               | 90   | 87     | 45      | 37300              | 62                    | 1.8     | 33   | 1.1             | 3.2             | 0.6  |
| 947D191K132AEGSN  | 190  | 1300               | 85   | 100    | 32      | 38100              | 53                    | 2.5     | 38   | 1.4             | 3.2             | 0.6  |
| 947D191K132CCRSN  | 190  | 1300               | 100  | 75     | 50      | 39300              | 70                    | 1.4     | 30   | 1.2             | 3.1             | 0.7  |
| 947D211K132AFGSN  | 210  | 1300               | 85   | 112    | 32      | 41300              | 52                    | 2.7     | 42   | 1.3             | 2.9             | 0.7  |
| 947D211K132BEMSEN | 210  | 1300               | 90   | 100    | 45      | 41000              | 61                    | 2.0     | 37   | 1.1             | 2.9             | 0.7  |
| 947D231K132CDRSN  | 230  | 1300               | 100  | 87     | 50      | 43000              | 69                    | 1.6     | 34   | 1.2             | 2.8             | 0.8  |
| 947D241K132AGGSN  | 240  | 1300               | 85   | 126    | 32      | 45000              | 51                    | 3.0     | 46   | 1.3             | 2.7             | 0.8  |
| 947D241K132BFMSN  | 240  | 1300               | 90   | 112    | 45      | 44400              | 60                    | 2.2     | 41   | 1.1             | 2.7             | 0.8  |
| 947D251K132DCRSN  | 250  | 1300               | 116  | 75     | 50      | 48500              | 87                    | 1.2     | 35   | 0.9             | 2.5             | 0.9  |
| 947D271K132AHGSN  | 270  | 1300               | 85   | 136    | 32      | 47700              | 50                    | 3.3     | 50   | 1.2             | 2.5             | 0.8  |
| 947D271K132CERSN  | 270  | 1300               | 100  | 100    | 50      | 47100              | 68                    | 1.8     | 38   | 1.2             | 2.5             | 0.9  |
| 947D281K132BGMSN  | 280  | 1300               | 90   | 126    | 45      | 48300              | 59                    | 2.4     | 45   | 1.0             | 2.5             | 0.9  |
| 947D301K132AJGSN  | 300  | 1300               | 85   | 150    | 32      | 51400              | 50                    | 3.5     | 54   | 1.2             | 2.3             | 0.9  |
| 947D311K132BHMSN  | 310  | 1300               | 90   | 136    | 45      | 51200              | 58                    | 2.7     | 49   | 1.0             | 2.3             | 0.9  |
| 947D311K132CFRSN  | 310  | 1300               | 100  | 112    | 50      | 50900              | 66                    | 2.0     | 42   | 1.1             | 2.4             | 1.0  |
| 947D311K132DDRSN  | 310  | 1300               | 116  | 87     | 50      | 52800              | 85                    | 1.3     | 40   | 0.9             | 2.3             | 1.1  |
| 947D331K132ALGSN  | 330  | 1300               | 85   | 162    | 32      | 54600              | 49                    | 3.8     | 59   | 1.2             | 2.2             | 1.0  |
| 947D341K132BJMSN  | 340  | 1300               | 90   | 150    | 45      | 55100              | 57                    | 2.9     | 53   | 1.0             | 2.2             | 1.0  |
| 947D351K132CGRSN  | 350  | 1300               | 100  | 126    | 50      | 55300              | 66                    | 2.2     | 46   | 1.1             | 2.2             | 1.1  |
| 947D371K132DERSN  | 370  | 1300               | 116  | 100    | 50      | 57600              | 84                    | 1.5     | 45   | 0.9             | 2.1             | 1.2  |
| 947D381K132BLMSN  | 380  | 1300               | 90   | 162    | 45      | 58500              | 56                    | 3.1     | 58   | 1.0             | 2.1             | 1.1  |
| 947D391K132CHRSN  | 390  | 1300               | 100  | 136    | 50      | 58400              | 64                    | 2.4     | 50   | 1.1             | 2.1             | 1.2  |
| 947D421K132DFRSN  | 420  | 1300               | 116  | 112    | 50      | 62000              | 82                    | 1.6     | 50   | 0.9             | 1.9             | 1.3  |
| 947D431K132CJRSN  | 430  | 1300               | 100  | 150    | 50      | 62800              | 64                    | 2.6     | 54   | 1.0             | 1.9             | 1.3  |
| 947D471K132CLRSN  | 470  | 1300               | 100  | 162    | 50      | 66600              | 63                    | 2.8     | 59   | 1.0             | 1.8             | 1.4  |
| 947D481K132DGRSN  | 480  | 1300               | 116  | 126    | 50      | 67100              | 82                    | 1.8     | 55   | 0.9             | 1.8             | 1.5  |
| 947D531K132DHRSN  | 530  | 1300               | 116  | 136    | 50      | 70700              | 80                    | 1.9     | 60   | 0.8             | 1.7             | 1.6  |
| 947D591K132DJRSN  | 590  | 1300               | 116  | 150    | 50      | 75800              | 79                    | 2.1     | 65   | 0.8             | 1.6             | 1.7  |
| 947D641K132DLRSN  | 640  | 1300               | 116  | 162    | 50      | 80200              | 78                    | 2.2     | 70   | 0.8             | 1.5             | 1.8  |

# **Type 947D Polypropylene, High Energy Density, DC Link Capacitors**

## **High Current, High Capacitance for Inverter Applications**

### **Expected Lifetime Predictions**

Capacitance:  $C$  ( $\mu\text{F}$ )  
Equivalent Series Resistance:  $\text{ESR}$  ( $\text{m}\Omega$ )  
Frequency:  $f$  ( $\text{kHz}$ )  
Ripple Current:  $I$  ( $\text{A}_{\text{rms}}$ )  
Ambient Temperature:  $T_A$  ( $^{\circ}\text{C}$ )  
Core Temperature:  $T_C$  ( $^{\circ}\text{C}$ )  
Total Thermal Resistance:  $\Theta$  ( $^{\circ}\text{C}/\text{W}$ )  
Thermal Resistance case-to-ambient:  $\Theta_{\text{CA}}$  ( $^{\circ}\text{C}/\text{W}$ )  
Thermal Resistance core-to-case:  $\Theta_{\text{CC}}$  ( $^{\circ}\text{C}/\text{W}$ )  
Airflow Speed:  $v$  ( $\text{m/s}$ )  
Applied Voltage:  $V_A$  ( $\text{V}_{\text{DC}}$ )  
Rated Voltage:  $V_R$  ( $\text{V}_{\text{DC}}$ )

Use the 10 kHz ESR from the ratings tables.


For operation below 10 kHz, the ESR will need to be adjusted using the following equation:  $\text{ESR} - 31.83 / (10C) + 31.83 / (fC)$ .

Compute  $\Theta = \Theta_{\text{CC}} + \Theta_{\text{CA}}$ . In the ratings tables,  $\Theta_{\text{CA}}$  is for still air. For moving air use the capacitor surface area  $A$  and airflow speed  $v$  to calculate  $\theta_{\text{ca}} = 1 / [A(5 + 17(v + 0.1)^{0.66})]$ .

Look up Expected Lifetime on the graph using  $V_A / V_R$  and  $T_C = T_A + I^2 (\text{ESR} / 1000) \Theta$

The maximum allowed temperature rise is  $40^{\circ}\text{C}$  and the maximum allowed core temperature is  $95^{\circ}\text{C}$ .

**Expected Lifetime vs Core Temperature and Applied DC Voltage**




# Type 947D Polypropylene, High Energy Density, DC Link Capacitors


## High Current, High Capacitance for Inverter Applications

### Typical Performance Curves


947D641K901AHGSN ESR vs Frequency and Temperature



947D641K901AHGSN Rated Ripple Current, Still Air, 7kh Life




947D421K112AHGSN ESR vs Frequency and Temperature




# Type 947D Polypropylene, High Energy Density, DC Link Capacitors

## High Current, High Capacitance for Inverter Applications


947D421K112AHGSN Rated Ripple Current, Still Air, 7kh Life



947D481K112ALGSN ESR vs Frequency and Temperature



947D481K112ALGSN Rated Ripple Current, Still Air, 7kh Life



**Notice and Disclaimer:** All product drawings, descriptions, specifications, statements, information and data (collectively, the “Information”) in this datasheet or other publication are subject to change. The customer is responsible for checking, confirming and verifying the extent to which the Information contained in this datasheet or other publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without any guarantee, warranty, representation or responsibility of any kind, expressed or implied. Statements of suitability for certain applications are based on the knowledge that the Cornell Dubilier company providing such statements (“Cornell Dubilier”) has of operating conditions that such Cornell Dubilier company regards as typical for such applications, but are not intended to constitute any guarantee, warranty or representation regarding any such matter – and Cornell Dubilier specifically and expressly disclaims any guarantee, warranty or representation concerning the suitability for a specific customer application, use, storage, transportation, or operating environment. The Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by Cornell Dubilier with reference to the use of any Cornell Dubilier products is given gratis (unless otherwise specified by Cornell Dubilier), and Cornell Dubilier assumes no obligation or liability for the advice given or results obtained. Although Cornell Dubilier strives to apply the most stringent quality and safety standards regarding the design and manufacturing of its products, in light of the current state of the art, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards (such as installation of protective circuitry or redundancies or other appropriate protective measures) in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage. Although all product-related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated in such warnings, cautions and notes, or that other safety measures may not be required.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9