

EC3BB

7.5 WATT WIDE INPUT DC-DC CONVERTERS



Features

- 7.5W Isolated Output
- Remote ON/OFF Option
- Efficiency to 82%
- 2:1 Input Range
- Regulated Outputs
- Continuous Short Circuit Protection
- Meets EN55022 Class B, Conducted
- Pi Input Filter

MODEL NUMBER	INPUT VOLTAGE	OUTPUT VOLTAGE	OUTPUT CURRENT	INPUT CURRENT NO LOAD	INPUT CURRENT FULL LOAD	% EFF.	CASE
EC3BB01		5 VDC	1500 mA	7.5 mA	820 mA	76	
EC3BB02		12 VDC	625 mA	7.5 mA	780 mA	80	
EC3BB03		15 VDC	500 mA	7.5 mA	780 mA	80	
EC3BB04	9-18 VDC	±12 VDC	±310 mA	12 mA	775 mA	80	B
EC3BB05		±15 VDC	±250 mA	12 mA	780 mA	80	
EC3BB06		±5 VDC	±750 mA	7.5 mA	820 mA	76	
EC3BB07		3.3 VDC	1500 mA	7.5 mA	557 mA	74	
EC3BB11		5 VDC	1500 mA	5 mA	400 mA	78	
EC3BB12		12 VDC	625 mA	5 mA	380 mA	82	
EC3BB13		15 VDC	500 mA	5 mA	380 mA	82	
EC3BB14	18-36 VDC	±12 VDC	±310 mA	7.5 mA	385 mA	81	B
EC3BB15		±15 VDC	±250 mA	7.5 mA	385 mA	81	
EC3BB16		±5 VDC	±750 mA	7.5 mA	400 mA	78	
EC3BB17		3.3 VDC	1500 mA	5 mA	271 mA	76	
EC3BB21		5 VDC	1500 mA	2 mA	200 mA	78	
EC3BB22		12 VDC	625 mA	2 mA	192 mA	81	
EC3BB23		15 VDC	500 mA	2 mA	192 mA	81	
EC3BB24	36-72 VDC	±12 VDC	±310 mA	3 mA	192 mA	81	B
EC3BB25		±15 VDC	±250 mA	3 mA	192 mA	81	
EC3BB26		±5 VDC	±750 mA	3 mA	200 mA	78	
EC3BB27		3.3 VDC	1500 mA	3 mA	136 mA	76	

NOTE: 1. Nominal Input Voltage 12, 24 or 48 VDC

Specifications

INPUT SPECIFICATIONS:

Input Voltage Range.....	12V.....	9-18V
	24V.....	18-36V
	48V.....	36-72V
Input Filter.....		Pi Type

OUTPUT SPECIFICATIONS:

Voltage Accuracy.....	± 2.0% max.
Voltage Balance (Dual).....	± 1.0% max.
Temperature Coefficient.....	± 0.05%/°C
Ripple and Noise, 20MHz BW.....	3.3V / 5V..... 100mV p-p max.
	12V / 15V..... 1% p-p max.
Short Circuit Protection.....	Continuous
Line Regulation, Single/Dual ¹	± 0.5%
Load Regulation, Single ²	± 0.5%
	Dual ³ ± 1.0%

GENERAL SPECIFICATIONS:


Efficiency.....	See Table
Isolation Voltage.....	1500 VDC min.
Isolation Resistance.....	10 ⁹ ohms
Switching Frequency.....	100kHz, min.
Operating Temperature Range.....	-25°C to + 71°C
Case Temperature.....	100°C max.
Cooling.....	Free-Air Convection
Storage Temperature Range.....	-40°C to + 100°C
EMI / RFI.....	Conductive EMI Meet EN55022 Class B
Dimensions.....	2 x 1 x 0.4 inches (50.8 x 25.4 x 10.2mm)
Case Material.....	Black Coated Copper With Non-Conductive Base
Weight.....	32.5g

NOTE:

1. Measured From High Line to Low Line
2. Measured From Full Load to 10% Load
3. Measured From Full Load to 1/4 Load
4. Suffix "T" to the Model Number with Remote ON/OFF

CASE B

All Dimensions in Inches(mm)
Tolerance .xx= ±0.04, .xxx= ±0.10



Remote On/Off Control

Logic Compatibility	CMOS or Open Collector TTL
Ec-On	>+5.5 VDC or Open Circuit
Ec-Off	<1.8 VDC
Shutdown Idle Current	10mA
Control Common	Referenced to Input Minus

PIN CONNECTION

Pin	Function
1.	+Input
2.	-Input
3.	+Output
4.	Common/NP
5.	-Output
6.	NP (Remote ON/OFF)

*NP-NO PIN

All Specifications Typical At Nominal Line, Full Load and 25°C Unless Otherwise Noted.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9