


**SURFACE MOUNT SCHOTTKY BARRIER DIODE ARRAYS**
**Features**

- Low Forward Voltage Drop
- Fast Switching
- Ultra-Small Surface Mount Package
- PN Junction Guard Ring for Transient and ESD Protection
- **Lead Free/RoHS Compliant (Note 3)**
- **Qualified to AEC-Q101 Standards for High Reliability**
- **"Green" Device (Notes 4 and 5)**

**Mechanical Data**

- Case: SOT-363
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020D
- Terminals: Solderable per MIL-STD-202, Method 208
- Lead Free Plating (Matte Tin Finish annealed over Alloy 42 leadframe).
- Polarity: See Diagrams Below
- Marking Information: See Page 3
- Ordering Information: See Page 3
- Weight: 0.006 grams (approximate)


**Maximum Ratings** @T<sub>A</sub> = 25°C unless otherwise specified

| Characteristic                                       | Symbol              | Value | Unit |
|------------------------------------------------------|---------------------|-------|------|
| Peak Repetitive Reverse Voltage                      | V <sub>RRM</sub>    |       |      |
| Working Peak Reverse Voltage                         | V <sub>RWM</sub>    | 40    | V    |
| DC Blocking Voltage                                  | V <sub>R</sub>      |       |      |
| RMS Reverse Voltage                                  | V <sub>R(RMS)</sub> | 28    | V    |
| Forward Continuous Current (Note 1)                  | I <sub>FM</sub>     | 200   | mA   |
| Non-Repetitive Peak Forward Surge Current @ t < 1.0s | I <sub>FSM</sub>    | 600   | mA   |





**Thermal Characteristics**

| Characteristic                                      | Symbol           | Value       | Unit |
|-----------------------------------------------------|------------------|-------------|------|
| Power Dissipation (Note 1)                          | P <sub>D</sub>   | 200         | mW   |
| Thermal Resistance Junction to Ambient Air (Note 1) | R <sub>θJA</sub> | 625         | °C/W |
| Operating Temperature Range                         | T <sub>J</sub>   | -55 to +125 | °C   |
| Storage Temperature Range                           | T <sub>STG</sub> | -65 to +125 | °C   |

**Electrical Characteristics** @T<sub>A</sub> = 25°C unless otherwise specified

| Characteristic                     | Symbol             | Min | Max         | Unit | Test Condition                                                                                            |
|------------------------------------|--------------------|-----|-------------|------|-----------------------------------------------------------------------------------------------------------|
| Reverse Breakdown Voltage (Note 2) | V <sub>(BR)R</sub> | 40  | —           | V    | I <sub>R</sub> = 10μA                                                                                     |
| Forward Voltage                    | V <sub>F</sub>     | —   | 380<br>1000 | mV   | I <sub>F</sub> = 1.0mA, t <sub>p</sub> < 300μs<br>I <sub>F</sub> = 40mA, t <sub>p</sub> < 300μs           |
| Reverse Current (Note 2)           | I <sub>R</sub>     | —   | 200         | nA   | V <sub>R</sub> = 30V                                                                                      |
| Total Capacitance                  | C <sub>T</sub>     | —   | 5.0         | pF   | V <sub>R</sub> = 0, f = 1.0MHz                                                                            |
| Reverse Recovery Time              | t <sub>rr</sub>    | —   | 5.0         | ns   | I <sub>F</sub> = I <sub>R</sub> = 10mA,<br>I <sub>rr</sub> = 0.1 x I <sub>R</sub> , R <sub>L</sub> = 100Ω |

- Notes:
1. Part mounted on FR-4 board with recommended pad layout, which can be found on our website at <http://www.diodes.com/datasheets/ap02001.pdf>.
  2. Short duration pulse test used to minimize self-heating effect.
  3. No purposefully added lead.
  4. Diodes Inc.'s "Green" policy can be found on our website at [http://www.diodes.com/products/lead\\_free/index.php](http://www.diodes.com/products/lead_free/index.php).
  5. Product manufactured with Date Code UO (week 40, 2007) and newer are built with Green Molding Compound. Product manufactured prior to Date Code UO are built with Non-Green Molding Compound and may contain Halogens or Sb2O3 Fire Retardants




## Ordering Information (Note 6)

| Part Number    | Case    | Packaging        |
|----------------|---------|------------------|
| BAS40TW-7-F    | SOT-363 | 3000/Tape & Reel |
| BAS40DW-04-7-F | SOT-363 | 3000/Tape & Reel |
| BAS40DW-05-7-F | SOT-363 | 3000/Tape & Reel |
| BAS40DW-06-7-F | SOT-363 | 3000/Tape & Reel |
| BAS40BRW-7-F   | SOT-363 | 3000/Tape & Reel |

Notes: 6. For packaging details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

## Marking Information



Kxx = Product Type Marking Code

K43 = BAS40TW

K44 = BAS40DW-04

K45 = BAS40DW-05

K46 = BAS40DW-06

K47 = BAS40BRW

For Asymmetrical Configuration, orientation indicator as shown

For Symmetrical Configuration, no orientation indicator

YM = Date Code Marking

Y = Year (ex: N = 2002)

M = Month (ex: 9 = September)


Date Code Key

| Year | 2000 | 2001 | 2002 | 2003 | 2004 | 2005 | 2006 | 2007 | 2008 | 2009 | 2010 | 2011 | 2012 | 2013 | 2014 | 2015 |
|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| Code | L    | M    | N    | P    | R    | S    | T    | U    | V    | W    | X    | Y    | Z    | A    | B    | C    |


| Month | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Code  | 1   | 2   | 3   | 4   | 5   | 6   | 7   | 8   | 9   | O   | N   | D   |

## Package Outline Dimensions



| SOT-363              |              |      |
|----------------------|--------------|------|
| Dim                  | Min          | Max  |
| A                    | 0.10         | 0.30 |
| B                    | 1.15         | 1.35 |
| C                    | 2.00         | 2.20 |
| D                    | 0.65 Nominal |      |
| F                    | 0.40         | 0.45 |
| H                    | 1.80         | 2.20 |
| J                    | 0            | 0.10 |
| K                    | 0.90         | 1.00 |
| L                    | 0.25         | 0.40 |
| M                    | 0.10         | 0.22 |
| α                    | 0°           | 8°   |
| All Dimensions in mm |              |      |

## Suggested Pad Layout



| Dimensions | Value (in mm) |
|------------|---------------|
| Z          | 2.5           |
| G          | 1.3           |
| X          | 0.42          |
| Y          | 0.6           |
| C          | 1.9           |
| E          | 0.65          |

**IMPORTANT NOTICE**

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

**LIFE SUPPORT**

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9