

LTPD/CAPD Series Low Voltage **Printer** Mechanisms



Designing mobile devices is increasingly challenging. Customers expect each new product generation to be smaller and faster, with long battery life. To be competitive, device manufacturers must reduce product size and increase speed. Time to market is crucial and reliability is non-negotiable.

New low voltage LTPD/CAPD series printer mechanisms tackle these challenges with dramatic advances in design flexibility, reliability, and printing performance.

Small

LTPD/CAPD series mechanisms free up critical design real estate. The new mechanisms provide a smaller overall form factor, innovative angled paper guide requiring less depth, and a smaller pitch flexible print circuit (FPC) cable.

Fast

LTPD/CAPD series mechanisms are fast, rated for up to 100 mm/second print speeds. This gives mobile devices a much needed performance boost.


Reliable

LTPD/CAPD series mechanisms offer a minimum of 50 km of total printing and 100 million pulses. CAPD models offer a new built-in auto-cutter design, improving cutter reliability. The result: reliable media output, every time.


Flexible

LTPD/CAPD series mechanisms offer a wide array of form factor choices to provide versatility and flexibility for smoother integration. Options include EZ-OP clamshell-style and auto-loading models, ASIC and interface board solutions, and both horizontal and vertical mechanical orientation designs.

- **2" and 3" print width models**
- **High speed printing (up to 100 mm/second)**
- **Choice of horizontal and vertical orientations**
- **EZ-OP clamshell and auto-loading paper replacement options**
- **Platen latch for better shock absorption**
- **Built-in auto-cutter (CAPD models)**



2" LTPD model and 2" CAPD model.



Product Specifications

Model	LTPD245	LTPD345	CAPD245	CAPD345	
Printing	Method Thermal line dot printing				
	Number of dots/line	384	576	384	
	Resolution(dots/mm)	8			
	Paper width (mm)	58 ⁺⁰⁻¹	80 ⁺⁰⁻¹	58 ⁺⁰⁻¹	80 ⁺⁰⁻¹
	Printing width (mm)	48	72	48	72
	Speed (max mm/sec)	100	80	100	80
Sensors	Paper path Curved				
	Head temperature By thermistor				
	Platen position detection By mechanical switch				
	Out of paper detection By photo interrupter				
Power supply (V)	Cutter home position detection -				
	By photo interrupter				
Peak current (A)	Operating Voltage (Vdd) 2.7 to 3.6/4.75 to 5.25				
	Operating Voltage (Vp) -				
Service life	Head 3.66 (9.5V/64dots)				
	Motor 0.6				
Operating temperature (°C)	Cutter motor -				
	Pulse activation (pulses) 100 million				
Dimensions (WxDxH mm)*	Abrasion resistance (km)* 50 *				
	-10 to 50				
Mass(g)	Horizontal 69.0 x 30.0 x 15.0 **				
	Vertical 69.0 x 15.0 x 30.0 **				
Auto-cutter	Approx. 40				
	Approx. 58				
	Approx. 125				
	Approx. 148				
	Method Slide cutting				
	Paper thickness (um) -				
Life span	Cutting type -				
	Operating time (sec/cycle) -				
	Minimum paper cutting length (mm) -				
	Cutting frequency (max cuts/min) -				
Life span	Paper cutting (cuts) -				
	500,000 *				

*Use recommended thermal paper. **Excluding convex section.

***Excluding mounting part. Specifications are subject to change without notice.

IF Board Specifications

	IFD501-01UK-E	IFD501-01SK-E
CPU	PTD50P01-E	
Corresponding Model	LTPD245, LTPD345 Series CAPD245, CAPD345 Series	
Operating Voltage (V)	Vp:4.75 to 9.5	
Character matrix (H x W dots)	16 dots character: 16 x 8, 16 x 16	
	24 dots character: 24 x 12, 24 x 24	
Character Type	Optional font	Yes
	Downloaded character	Yes
	User-defined character	Yes
	Extend graphics character set	Yes
	Katakana character set	Yes
	Codepage 1252	Yes
	JIS 1&2 level kanji	Yes
Communication interface	USB(2.0)	Serial (RS-232C)
Dimensions (W x D x H mm)	69.0 x 50.0 x 14.0	

ASIC Specifications:

	PTD50P01-E
Corresponding model	LTPD245, LTPD345 series CAPD245, CAPD345 series
Package form	120pin QFP
Operating voltage (V)	Vp:4.75 to 9.5, Vcc:3.0 to 3.6
Operating frequency (MHz)	12MHz±0.01%
Configuration	C-MOS LSI
Communication interface	Parallel, Serial, USB
Character type	Extended graphics character set Other characters available With CGs or external memory
Character matrix (H x W dots)	16 dot character: 16 x 8, 16 x 16
	24 dot character: 24 x 12, 24 x 24
Dimensions (W x D x H mm)	16.0 x 16.0 x 1.7

Optional Cables

Accessory	Product
Power Cable	DC-04100A-E
Switch Cable	OC-D1430A-E
Serial Cable	OC-D0730A-E
USB Cable	IFC-U01-1-E

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9