



963E Benchtop Air Ionizer

Technical Information

BT 0686-1101
Nov 2001

The use of ionized air in electronics work environments eliminates the build up of potentially damaging static charges. Air ionizers are primarily used to control static charge on nonconductive materials. Grounding is normally used to control charge on conductive objects and personnel, however, nonconductors cannot be grounded to drain electrostatic charge. Ionization is the only method of neutralizing a static charge on a nonconductor. Ionized air can neutralize static charges on circuit board substrates, insulating tapes and plastic objects found in the work area. The 3M™ 963E Benchtop Air Ionizer blankets the benchtop with ionized air to help prevent static from damaging sensitive electronics.

New version of Benchtop Air Ionizer available

The 963E Benchtop Air Ionizer includes a universal power transformer, to convert local electrical power into DC 24V (power line cord not included). The 963E features a two-speed fan, power indicator lamp, static-dissipative plastic housing, and a combination metal-plastic stand that can also double as a mounting bracket.



Rapid neutralization of electrostatic charge

The ion-generation technology present in the 963E Benchtop Air Ionizer is capable of producing extremely large amounts of ions, resulting in nearly instantaneous static charge neutralization. The 3M 963E is capable of reducing a static charge of 1000V to 100V in less than one second, at a 0.3 m distance, when tested* at the high fan speed. In addition, the powerful fan allows the generated ions to be carried at high speed for long distances. At a distance of 0.9 m, the discharge time only increases to approximately five seconds.

* When tested according to ANSI/ESD S3.1-1991

Intrinsically balanced, maintenance-free

3M ionizers have a proprietary, intrinsically balanced ion generation system which ensures that equal levels of positive and negative ions are produced despite variations in line voltage, fan speed, and emitter point condition. No adjustment or calibration is required to maintain ion balance. This allows the unit to generate a balanced mix of positive and negative ions - even if the emitter points become dirty.

The 963E is virtually maintenance free. The ionizer's unique design requires only periodic cleaning of emitter points to maintain optimum performance. The points do not require replacement and the unit does not require adjustment before or after cleaning.

Quiet and comfortable air flow

The two-speed fan in the 963E Benchtop Air Ionizer is extremely quiet at low speed. Where industrial noise may irritate personnel and lower productivity, the 963E may be used without contributing significantly to the ambient noise. The fan's gentle airflow does not disturb paper or delicate parts. The high-speed fan setting can be used for more rapid neutralization of static charges in environments where faster decay rates are required.

Static-dissipative housing safe to use in ESD sensitive areas

The injection-molded plastic case is constructed of static-dissipative plastic. The conductivity of the case prevents a static charge from building up on the surface of the housing, a common problem with ionizers. This "ESD-safe" design allows the ionizer to be part of your overall static-safeguarded electronic workstation.

Meets Global Regulatory Requirements

Global usage of electronic products are often dependent on the product meeting regulatory requirements for the country of usage. To achieve this end, the model 963E has been tested to, and have passed, regulatory requirements for the European Union. The 963E carry the UL, C-UL, NOM and CE marks.

Basic Features

- Neutralizes static charges on nonconductive objects
- Maintains equal balance of positive-negative ions
- Two-speed fan
- Static-dissipative housing
- UL, C-UL, NOM certification. CE-marked.

963E Benchtop Air Ionizer Typical Properties

Item	Typical Properties
Power Ratings	DC 24 V, 0.42 A, 10 W through included universal power transformer
Power inlet	Mini DIN Socket
Power Transformer	Input: AC 100V-240V, 0.4A, 50/60 Hz Into IEC320 Socket Output: DC24V, 0.5A 0.9 m cord with Mini DIN plug
Power Outlet Cord	Not Included
Dimensions (w/ mounting base)	18 cm (W) x 23 cm (H) x 10 cm (D)
Weight	1.1 kg
Air Volume	
low speed	2.15 m ³ / minute
high speed	3.17 m ³ / minute
Static discharge time * @ 30 cm	< 1 second
Certifications and approvals	UL, C-UL, NOM, CE

* When tested according to ANSI/ESD S3.1-1991 at high fan speed

New From 3M

Ensure that your Benchtop Air Ionizer is operating at peak performance. When used with the 3M™ 718 Static Sensor, the 3M™ 718A Air Ionizer Test Kit can provide periodic verification of air ionizer performance. The system as a whole is designed to meet the guidelines specified in ESD Association Draft Standard D3.3. Call our Customer Services for more information on these static control products.



Important Notice: All statements, technical information and recommendations related to the Seller's products are based on information believed to be reliable, but the accuracy or completeness thereof is not guaranteed. Before utilizing the product, the user should determine the suitability of the product for its intended use. The user assumes all risks and liability whatsoever in connection with such use.

All statements or recommendations of the Seller which are not contained in the Seller's current publications shall have no force or effect unless contained in an agreement signed by an authorized officer of the Seller. The statements contained herein are made in lieu of all warranties, expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose which warranties are hereby expressly disclaimed.

SELLER SHALL NOT BE LIABLE TO THE USER OR ANY OTHER PERSON UNDER ANY LEGAL THEORY, INCLUDING BUT NOT LIMITED TO NEGLIGENCE OR STRICT LIABILITY, FOR ANY INJURY OR FOR ANY DIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES SUSTAINED OR INCURRED BY REASON OF THE USE OF ANY OF THE SELLER'S PRODUCTS.



3M France Electronic Handling & Protection

Boulevard de l'Oise
95006 Cergy Pontoise Cedex
Tél. : + 33 (0) 1 30 31 68 09 - Fax : + 33 (0) 1 30 31 61 81

SAS au capital de 8 400 000 euros - 542 078 555 RCS Pontoise APE 246C -
n° Identification TVA : FR 25 542 078 555 - CCP n° 30041 00001 0143470B020 03 Paris

Distributed by: SJM Eurostat

45 route d'Orgelet, 39130 Pont de Poitte, France
Tel. : + 33 (0) 3 84 87 02 39 — Fax : + 33 (0) 3 84 48 30 00

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9