


LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
AD	0		S2	REVISED PER ECO-15-006450	28APR2015	NK	RH



SPECIFICATIONS:

MATERIAL
BASE, PPS, UL94V-0, BLACK
COVER, PPS, UL94V-0, BLACK
ACTUATOR, PA6T, UL94V-0, WHITE
FIXED CONTACT/TERMINAL, CU ALLOY-GOLD FLASH OVER NICKEL
MOVING CONTACT, CU ALLOY, PLATE-GOLD FLASH/NICKEL

ELECTRICAL
MAX CONTACT RATING SWITCHING, 100MILLIAMP @ 24 VDC
MIN CONTACT RATING SWITCHING, .1MICROAMP @ 1 MILLIVOLT
MAX CONTACT NON-SWITCHING, 1AMP @ 5 VDC
INITIAL CONTACT RESISTANCE, 50 MILLIOHMS MAX.
CONTACT RESISTANCE (AFTER ENVIRONMENTAL TEST), 100 MILLIOHMS
CONTACT RESISTANCE (AFTER GAS TEST), 300 MILLIOHMS
INSULATION RESISTANCE, 1,000 MEGOHMS MIN. @ 100 VDC
DIELECTRIC STRENGTH, 500 VAC RMS @ SEA LEVEL
LIFE EXPECTANCY, 1,000 CYCLES



MECHANICAL
OPERATING FORCE, LESS THAN 800 GRAMS
CONTACT PRESSURE, 280,000 PSI

ENVIRONMENTAL
OPERATING TEMPERATURE, -30 TO +85 DEGREES C
STORAGE TEMPERATURE, -45 TO +105 DEGREES C
CLEANING, AQUEOUS OR SOLVENT
SOLDER HEAT RESISTANCE, PER 109-201,COND B, SWITCH "OFF".
SOLDERABILITY PER JIS C 0050 & JIS C 0053

- SWITCHES TO BE RECEIVED IN THE "OFF" POSITION AND PACKAGED IN CLEAR TUBES TO ACCOMMODATE AUTO-INSERTION.
- TOP SURFACE TO BE CLEARLY MARKED AS SHOWN.
- SWITCHES TO BE BLACK WITH WHITE ACTUATORS AND MARKINGS.
- TERMINAL OPTION: OLD T&B P/N ADExxS, SA OR SB
S= OUTSIDE "L" TERMINALS; SA= INSIDE "L" TERMINALS;
SB= BUTT TERMINALS.
- ALL MATERIALS AND FINISHES SHALL COMPLY WITH EU DIRECTIVE 2002/95/EC OF 27JAN2003 (ROHS).
- OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI.
- TAPE AND REEL PACKING PER PAGE 3 SPECIFICATIONS.

SEE SHEET 2 FOR PART NUMBER TABLE
AND MOUNTING OPTIONS

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN B.S.VISWESWARA	10FEB05	TE Connectivity			
DIMENSIONS: mm [INCHES]		CHK M.SARVER	-	NAME			
		APVD M.SARVER	-				
		PRODUCT SPEC	-	DIP SWITCH, ADE-SMT SERIES			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC	-				
MATERIAL		WEIGHT	-	SIZE A2	CAGE CODE -	DRAWING NO C=1825058	RESTRICTED TO -
FINISH		CUSTOMER DRAWING	-	SCALE 4:1	SHEET 1 OF 3	REV S2	



B

1825058

	ADE12STR04	3.61	[.142]	32.51	[1.280]	12	4–1825058–1
	ADE10STR04	3.50	[.138]	27.30	[1.075]	10	4–1825058–0
	ADE09STR04	3.50	[.138]	24.54	[.978]	9	3–1825058–9
	ADE08STR04	3.50	[.138]	22.30	[.878]	8	3–1825058–8
	ADE07STR04	3.50	[.138]	19.76	[.778]	7	3–1825058–7
	ADE06STR04	3.50	[.138]	17.22	[.678]	6	3–1825058–6
	ADE05STR04	3.50	[.138]	14.68	[.578]	5	3–1825058–5
	ADE04STR04	3.50	[.138]	12.14	[.478]	4	3–1825058–4
	ADE03STR04	3.50	[.138]	9.60	[.378]	3	3–1825058–3
	ADE02STR04	3.50	[.138]	7.00	[.276]	2	3–1825058–2
	ADE04SATR04	3.50	[.138]	12.14	[.478]	4	3–1825058–1
	ADE12SB04	3.61	[.142]	32.51	[1.280]	12	3–1825058–0
	ADE12SA04	3.61	[.142]	32.51	[1.280]	12	2–1825058–9
	ADE12S04	3.61	[.142]	32.51	[1.280]	12	2–1825058–8
	ADE10SB04	3.50	[.138]	27.30	[1.075]	10	2–1825058–7
	ADE10SA04	3.50	[.138]	27.30	[1.075]	10	2–1825058–6
	ADE10S04	3.50	[.138]	27.30	[1.075]	10	2–1825058–5
	ADE09SB04	3.50	[.138]	24.54	[.978]	9	2–1825058–4
	ADE09SA04	3.50	[.138]	24.54	[.978]	9	2–1825058–3
	ADE09S04	3.50	[.138]	24.54	[.978]	9	2–1825058–2
	ADE08SB04	3.50	[.138]	22.30	[.878]	8	2–1825058–1
	ADE08SA04	3.50	[.138]	22.30	[.878]	8	2–1825058–0
	ADE08S04	3.50	[.138]	22.30	[.878]	8	1–1825058–9
OBSOLETE	ADE07SB04	3.50	[.138]	19.76	[.778]	7	1–1825058–8
	ADE07SA04	3.50	[.138]	19.76	[.778]	7	1–1825058–7
	ADE07S04	3.50	[.138]	19.76	[.778]	7	1–1825058–6
	ADE06SB04	3.50	[.138]	17.22	[.678]	6	1–1825058–5
	ADE06SA04	3.50	[.138]	17.22	[.678]	6	1–1825058–4
	ADE06S04	3.50	[.138]	17.22	[.678]	6	1–1825058–3
OBSOLETE	ADE05SB04	3.50	[.138]	14.68	[.578]	5	1–1825058–2
	ADE05SA04	3.50	[.138]	14.68	[.578]	5	1–1825058–1
	ADE05S04	3.50	[.138]	14.68	[.578]	5	1–1825058–0
	ADE04SB04	3.50	[.138]	12.14	[.478]	4	1825058–9
	ADE04SA04	3.50	[.138]	12.14	[.478]	4	1825058–8
	ADE04S04	3.50	[.138]	12.14	[.478]	4	1825058–7
	ADE03SB04	3.50	[.138]	9.60	[.378]	3	1825058–6
	ADE03SA04	3.50	[.138]	9.60	[.378]	3	1825058–5
	ADE03S04	3.50	[.138]	9.60	[.378]	3	1825058–4
	ADE02SB04	3.50	[.138]	7.00	[.276]	2	1825058–3
	ADE02SA04	3.50	[.138]	7.00	[.276]	2	1825058–2
	ADE02S04	3.50	[.138]	7.00	[.276]	2	1825058–1
	T&B P/N	DIM H		DIM L	POSITION	PART NO.	

A

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm [INCHES]

0 PLC ± –
1 PLC ± –
2 PLC ± 0.30[.012]
3 PLC ± –
4 PLC ± –
ANGLES ± –

TOLERANCES UNLESS OTHERWISE SPECIFIED:

FINISH –

MATERIAL –

–

DWN B.S.VISWESWARA 10FEB05

CHK M.SARVER

APVD M.SARVER

PRODUCT SPEC –

APPLICATION SPEC –

WEIGHT –

CUSTOMER DRAWING

TE Connectivity

DIP SWITCH, ADE–SMT SERIES

SIZE A2

CAGE CODE –

DRAWING NO C=1825058





RESTRICTED TO –

SCALE 4:1

SHEET 2 OF 3

REV S2

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
AD	0						
			—	SEE SHEET 1	—	—	—



	DESCRIPTION	MATERIAL	DIMENSION	FINISH	REMARKS
1	REEL	SIDE: CARDBOARD CORE: STYLOFOAM	MENTIONED BELOW		
2	EMBOSSED TAPE	–	MENTIONED BELOW	ANTISTATIC	BLACK
3	TOP COVER TAPE	–	MENTIONED BELOW	ANTISTATIC	TRANSPARENT

4P	ø330.00±2.10 [12.992±.082]	ø100 [3.940]	24.40 ^{+2.00} ₀ [.960 ^{+7.90} _{.000}]	30.40 [1.997]
NO OF POSITION	A	N (MIN)	W1	W2 (MAX)

4P	ø1.50 ^{+0.10} ₀ [ø.059 ^{+.003} _{.000}]	4.00±0.10 [.157±.003]	16.00±0.10 [.629±.003]	2.00±0.15 [.078±.005]	11.50±0.10 [.453±.003]	7.40±0.10 [.291±.003]
NO OF POSITION	D1	P0	P1	P2	F	K

4P	24.00±0.30 [.944±.011]	12.90±0.10 [.507±.003]	1.75±0.10 [.068±.003]	0.50±0.05 [.020±.001]	12.14±0.50 [.477±.020]	ø1.50 ^{+0.10} ₀ [ø.059 ^{+.003} _{.000}]
NO OF POSITION	W	B	E	T	L	DO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN B.S.VISWESWARA CHK M.SARVER APVD M.SARVER PRODUCT SPEC APPLICATION SPEC WEIGHT –	10FEB05 – – – – – –	TE Connectivity			
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME DIP SWITCH, ADE–SMT SERIES			
		0 PLC ± – 1 PLC ± – 2 PLC ± 0.30[.012] 3 PLC ± – 4 PLC ± – ANGLES ± – FINISH		SIZE A2	CAGE CODE –	DRAWING NO C=1825058	RESTRICTED TO –
MATERIAL –		–		CUSTOMER DRAWING			
				SCALE 4:1	SHEET 3 OF 3	REV S2	

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9