

1.5SMC6.8A  
THRU  
1.5SMC220A

SURFACE MOUNT SILICON  
UNI-DIRECTIONAL  
GLASS PASSIVATED JUNCTION  
TRANSIENT VOLTAGE SUPPRESSORS  
1500 WATT, 6.8 THRU 220 VOLT



www.centrasemi.com


#### DESCRIPTION:

The CENTRAL SEMICONDUCTOR 1.5SMC6.8A series devices are surface mount uni-directional glass passivated junction Transient Voltage Suppressors designed to protect voltage sensitive components from high voltage transients.

**THIS DEVICE IS MANUFACTURED WITH A GLASS PASSIVATED CHIP FOR OPTIMUM RELIABILITY.**

Note: For bi-directional devices, please refer to the 1.5SMC6.8CA series data sheet.

**MARKING CODE: SEE ELECTRICAL CHARACTERISTICS TABLE**



• This series is UL listed, UL file number E130224

**MAXIMUM RATINGS:** ( $T_A=25^\circ\text{C}$  unless otherwise noted)

Peak Power Dissipation (Note 1)

Peak Forward Surge Current (JEDEC Method)

Operating and Storage Junction Temperature

**SYMBOL**

$P_{PK}$

$I_{FSM}$

$T_J, T_{stg}$

1500

200

-65 to +150

**UNITS**

W

A

$^\circ\text{C}$

**ELECTRICAL CHARACTERISTICS:** ( $T_A=25^\circ\text{C}$  unless otherwise noted)

| TYPE       | BREAKDOWN VOLTAGE |       |       | TEST CURRENT | WORKING PEAK REVERSE VOLTAGE | MAXIMUM REVERSE LEAKAGE CURRENT | MAXIMUM REVERSE SURGE CURRENT (Note 1) | MAXIMUM REVERSE VOLTAGE | MAXIMUM TEMPERATURE COEFFICIENT | MARKING CODE |
|------------|-------------------|-------|-------|--------------|------------------------------|---------------------------------|----------------------------------------|-------------------------|---------------------------------|--------------|
|            | $V_{BR} @ I_T$    |       |       | $I_T$        | $V_{RWM}$                    | $I_R @ V_{RWM}$                 | $I_{RSM}$                              | $V_{RSM} @ I_{RSM}$     | $\theta V_{BR}$                 |              |
|            | MIN V             | NOM V | MAX V | mA           | V                            | $\mu\text{A}$                   | A                                      | V                       | % / $^\circ\text{C}$            |              |
| 1.5SMC6.8A | 6.45              | 6.8   | 7.14  | 10           | 5.8                          | 1000                            | 143                                    | 10.5                    | 0.057                           | C6V8A        |
| 1.5SMC7.5A | 7.13              | 7.5   | 7.88  | 10           | 6.4                          | 500                             | 132                                    | 11.3                    | 0.061                           | C7V5A        |
| 1.5SMC8.2A | 7.79              | 8.2   | 8.61  | 10           | 7.02                         | 200                             | 124                                    | 12.1                    | 0.065                           | C8V2A        |
| 1.5SMC9.1A | 8.65              | 9.1   | 9.55  | 1.0          | 7.78                         | 50                              | 112                                    | 13.4                    | 0.068                           | C9V1A        |
| 1.5SMC10A  | 9.5               | 10    | 10.5  | 1.0          | 8.55                         | 10                              | 103                                    | 14.5                    | 0.073                           | C10A         |
| 1.5SMC11A  | 10.5              | 11    | 11.6  | 1.0          | 9.4                          | 5                               | 96                                     | 15.6                    | 0.075                           | C11A         |
| 1.5SMC12A  | 11.4              | 12    | 12.6  | 1.0          | 10.2                         | 5                               | 90                                     | 16.7                    | 0.078                           | C12A         |
| 1.5SMC13A  | 12.4              | 13    | 13.7  | 1.0          | 11.1                         | 5                               | 82                                     | 18.2                    | 0.081                           | C13A         |
| 1.5SMC15A  | 14.3              | 15    | 15.8  | 1.0          | 12.8                         | 5                               | 71                                     | 21.2                    | 0.084                           | C15A         |
| 1.5SMC16A  | 15.2              | 16    | 16.8  | 1.0          | 13.6                         | 5                               | 67                                     | 22.5                    | 0.086                           | C16A         |
| 1.5SMC18A  | 17.1              | 18    | 18.9  | 1.0          | 15.3                         | 5                               | 59.5                                   | 25.2                    | 0.088                           | C18A         |
| 1.5SMC20A  | 19.0              | 20    | 21.0  | 1.0          | 17.1                         | 5                               | 54                                     | 27.7                    | 0.090                           | C20A         |
| 1.5SMC22A  | 20.9              | 22    | 23.1  | 1.0          | 18.8                         | 5                               | 49                                     | 30.6                    | 0.092                           | C22A         |
| 1.5SMC24A  | 22.8              | 24    | 25.2  | 1.0          | 20.5                         | 5                               | 45                                     | 33.2                    | 0.094                           | C24A         |
| 1.5SMC27A  | 25.7              | 27    | 28.4  | 1.0          | 23.1                         | 5                               | 40                                     | 37.5                    | 0.096                           | C27A         |
| 1.5SMC30A  | 28.5              | 30    | 31.5  | 1.0          | 25.6                         | 5                               | 36                                     | 41.4                    | 0.097                           | C30A         |
| 1.5SMC33A  | 31.4              | 33    | 34.7  | 1.0          | 28.2                         | 5                               | 33                                     | 45.7                    | 0.098                           | C33A         |
| 1.5SMC36A  | 34.2              | 36    | 37.8  | 1.0          | 30.8                         | 5                               | 30                                     | 49.9                    | 0.099                           | C36A         |
| 1.5SMC39A  | 37.1              | 39    | 41    | 1.0          | 33.3                         | 5                               | 28                                     | 53.9                    | 0.100                           | C39A         |

Notes: (1) Non-repetitive 10x1,000 $\mu\text{s}$  pulse.

R7 (11-September 2013)

1.5SMC6.8A  
THRU  
1.5SMC220A




SURFACE MOUNT SILICON  
UNI-DIRECTIONAL  
GLASS PASSIVATED JUNCTION  
TRANSIENT VOLTAGE SUPPRESSORS  
1500 WATT, 6.8 THRU 220 VOLT



ELECTRICAL CHARACTERISTICS - Continued: ( $T_A=25^\circ\text{C}$  unless otherwise noted)

| TYPE       | BREAKDOWN VOLTAGE |       |       | TEST CURRENT | WORKING PEAK REVERSE VOLTAGE | MAXIMUM REVERSE LEAKAGE CURRENT | MAXIMUM REVERSE SURGE CURRENT (Note 1) | MAXIMUM REVERSE VOLTAGE | MAXIMUM TEMPERATURE COEFFICIENT | MARKING CODE |
|------------|-------------------|-------|-------|--------------|------------------------------|---------------------------------|----------------------------------------|-------------------------|---------------------------------|--------------|
|            | $V_{BR} @ I_T$    |       |       | $I_T$        | $V_{RWM}$                    | $I_R @ V_{RWM}$                 | $I_{RSM}$                              | $V_{RSM} @ I_{RSM}$     | $\theta V_{BR}$                 |              |
|            | MIN V             | NOM V | MAX V | mA           | V                            | $\mu\text{A}$                   | A                                      | V                       | % / $^\circ\text{C}$            |              |
| 1.5SMC43A  | 40.9              | 43    | 45.2  | 1.0          | 36.8                         | 5                               | 25.3                                   | 59.3                    | 0.101                           | C43A         |
| 1.5SMC47A  | 44.7              | 47    | 49.4  | 1.0          | 40.2                         | 5                               | 23.2                                   | 64.8                    | 0.101                           | C47A         |
| 1.5SMC51A  | 48.5              | 51    | 53.6  | 1.0          | 43.6                         | 5                               | 21.4                                   | 70.1                    | 0.102                           | C51A         |
| 1.5SMC56A  | 53.2              | 56    | 58.8  | 1.0          | 47.8                         | 5                               | 19.5                                   | 77                      | 0.103                           | C56A         |
| 1.5SMC62A  | 58.9              | 62    | 65.1  | 1.0          | 53.0                         | 5                               | 17.7                                   | 85                      | 0.104                           | C62A         |
| 1.5SMC68A  | 64.6              | 68    | 71.4  | 1.0          | 58.1                         | 5                               | 16.3                                   | 92                      | 0.104                           | C68A         |
| 1.5SMC75A  | 71.3              | 75    | 78.8  | 1.0          | 64.1                         | 5                               | 14.6                                   | 103                     | 0.105                           | C75A         |
| 1.5SMC82A  | 77.9              | 82    | 86.1  | 1.0          | 70.1                         | 5                               | 13.3                                   | 113                     | 0.105                           | C82A         |
| 1.5SMC91A  | 86.5              | 91    | 95.5  | 1.0          | 77.8                         | 5                               | 12                                     | 125                     | 0.106                           | C91A         |
| 1.5SMC100A | 95.0              | 100   | 105   | 1.0          | 85.5                         | 5                               | 11                                     | 137                     | 0.106                           | C100A        |
| 1.5SMC110A | 104.5             | 110   | 115.5 | 1.0          | 94.0                         | 5                               | 9.9                                    | 152                     | 0.107                           | C110A        |
| 1.5SMC120A | 114               | 120   | 126   | 1.0          | 102                          | 5                               | 9.1                                    | 165                     | 0.107                           | C120A        |
| 1.5SMC130A | 123.5             | 130   | 136.5 | 1.0          | 111                          | 5                               | 8.4                                    | 179                     | 0.107                           | C130A        |
| 1.5SMC150A | 142.5             | 150   | 157.5 | 1.0          | 128                          | 5                               | 7.2                                    | 207                     | 0.108                           | C150A        |
| 1.5SMC160A | 152               | 160   | 168   | 1.0          | 136                          | 5                               | 6.8                                    | 219                     | 0.108                           | C160A        |
| 1.5SMC170A | 161.5             | 170   | 178.5 | 1.0          | 145                          | 5                               | 6.4                                    | 234                     | 0.108                           | C170A        |
| 1.5SMC180A | 171               | 180   | 189   | 1.0          | 154                          | 5                               | 6.1                                    | 246                     | 0.108                           | C180A        |
| 1.5SMC200A | 190               | 200   | 210   | 1.0          | 171                          | 5                               | 5.5                                    | 274                     | 0.108                           | C200A        |
| 1.5SMC220A | 209               | 220   | 231   | 1.0          | 185                          | 5                               | 4.6                                    | 328                     | 0.108                           | C220A        |

#### SMC CASE - MECHANICAL OUTLINE



| SYMBOL | INCHES |       | MILLIMETERS |      |
|--------|--------|-------|-------------|------|
|        | MIN    | MAX   | MIN         | MAX  |
| A      | 0.030  | 0.060 | 0.76        | 1.52 |
| B      | 0.002  | 0.008 | 0.05        | 0.20 |
| C      | 0.305  | 0.320 | 7.75        | 8.13 |
| D      | 0.006  | 0.012 | 0.15        | 0.31 |
| E      | 0.079  | 0.103 | 2.00        | 2.62 |
| F      | 0.260  | 0.280 | 6.60        | 7.11 |
| G      | 0.108  | 0.128 | 2.75        | 3.25 |
| H      | 0.220  | 0.245 | 5.59        | 6.22 |

SMC (REV: R2)

R7 (11-September 2013)





1.5SMC6.8A  
THRU  
1.5SMC220A



SURFACE MOUNT SILICON  
UNI-DIRECTIONAL  
GLASS PASSIVATED JUNCTION  
TRANSIENT VOLTAGE SUPPRESSORS  
1500 WATT, 6.8 THRU 220 VOLT



## TYPICAL ELECTRICAL CHARACTERISTICS



R7 (11-September 2013)

---

**PRODUCT SUPPORT**

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

---

**DESIGNER SUPPORT/SERVICES**

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

---

**CONTACT US**

**Corporate Headquarters & Customer Support Team**

Central Semiconductor Corp.  
145 Adams Avenue  
Hauppauge, NY 11788 USA  
Main Tel: (631) 435-1110  
Main Fax: (631) 435-1824  
Support Team Fax: (631) 435-3388  
[www.centrasemi.com](http://www.centrasemi.com)

**Worldwide Field Representatives:**  
[www.centrasemi.com/wwreps](http://www.centrasemi.com/wwreps)

**Worldwide Distributors:**  
[www.centrasemi.com/wwdistributors](http://www.centrasemi.com/wwdistributors)

---

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: [www.centrasemi.com/terms](http://www.centrasemi.com/terms)

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9