

NEW



OMRON

Proximity Sensors

E2V-X□

30 Years of Innovation

**Long-distance Detection of Aluminum or Iron
A Proximity Sensor with a NEW Detection Principle**



Smartclick
Pre-wired Connector Models
Standard Models

realizing


CE

Aluminum Detection Distance: 1.5 to 2 Times Previous Models


*In-house comparison of M18 Shielded Long-distance Models

Immunity against aluminum chips has enabled achieving long-distance detection of aluminum workpieces. The same detection distance has also been achieved for iron, allowing the E2V-X□ to be separated from workpieces made of either metal farther than any other Proximity Sensor.

Aluminum Excellent Performance, with Aluminum Chip Immunity!




Iron Also Detects Iron at Long Distances!



Detection Made Visible

An operation indicator that is visible from any direction is provided as a standard feature.


This indicator flashes under unstable conditions for easy installation condition verification at a glance.



Embeddable in Metal.

The first Long-distance Sensor that is shielded. Possible to be completely embedded in metal.


Embedded Mounting in Metal




Applications



Long-distance Detection of Crankshafts



Cylinder Block Seating Detection




Detect Passing Parts

Ordering Information


Standard-distance Sensors, DC 3-wire, Pre-wired Models (Standard Cable Length: 2 m)

Models with 5-m cables are also available and are ordered by adding "5M" to the end of the model number (e.g., E2V-X2B1 5M).


Appearance		Sensing distance	Output	Model	
				Operation mode NO	Operation mode NC
	M12	 2mm	PNP	E2V-X2B1	E2V-X2B2
			NPN	E2V-X2C1	E2V-X2C2
	M18	 5mm	PNP	E2V-X5B1	E2V-X5B2
			NPN	E2V-X5C1	E2V-X5C2
	M30	 10mm	PNP	E2V-X10B1	E2V-X10B2
			NPN	E2V-X10C1	E2V-X10C2

Long-distance Sensors, DC 3-wire, Pre-wired Models (Standard Cable Length: 2 m)


Models with 5-m cables are also available and are ordered by adding "5M" to the end of the model number (e.g., E2V-X4B1 5M).

Appearance		Sensing distance	Output	Model	
				Operation mode NO	Operation mode NC
	M12	 4mm	PNP	E2V-X4B1	E2V-X4B2
			NPN	E2V-X4C1	E2V-X4C2
	M18	 8mm	PNP	E2V-X8B1	E2V-X8B2
			NPN	E2V-X8C1	E2V-X8C2
	M30	 15mm	PNP	E2V-X15B1	E2V-X15B2
			NPN	E2V-X15C1	E2V-X15C2


Long-distance Sensors, DC 3-wire, Connector Models

Appearance		Sensing distance	Output	Model	
				Operation mode NO	Operation mode NC
	M12	 4mm	PNP	E2V-X4B1-M1	E2V-X4B2-M1
			NPN	E2V-X4C1-M1	E2V-X4C2-M1
	M18	 8mm	PNP	E2V-X8B1-M1	E2V-X8B2-M1
			NPN	E2V-X8C1-M1	E2V-X8C2-M1
	M30	 15mm	PNP	E2V-X15B1-M1	E2V-X15B2-M1
			NPN	E2V-X15C1-M1	E2V-X15C2-M1

Long-distance Sensors, DC 3-wire, Smartclick Pre-wired Connector (M12) Models

Appearance		Sensing distance	Output	Model
				Operation mode NO
	M12	 4mm	PNP	E2V-X4B1-M1TJ
			NPN	E2V-X4C1-M1TJ
	M18	 8mm	PNP	E2V-X8B1-M1TJ
			NPN	E2V-X8C1-M1TJ
	M30	 15mm	PNP	E2V-X15B1-M1TJ
			NPN	E2V-X15C1-M1TJ

Standard "Twist-and-Click" Smartclick Connectors



Appearance	Type	Cable length (m)	Model	Applicable Proximity Sensor Models
	Standard cable	2	XS5F-D421-D80-A	E2V-X□□□-M1/M1TJ
		5	XS5F-D421-G80-A	E2V-X□□□-M1/M1TJ
	Vibration-proof robot cable	2	XS5F-D421-D80-F	E2V-X□□□-M1/M1TJ
		5	XS5F-D421-G80-F	E2V-X□□□-M1/M1TJ
	Oil-resistant polyurethane cable	2	XS5F-D421-D80-P	E2V-X□□□-M1/M1TJ
		5	XS5F-D421-G80-P	E2V-X□□□-M1/M1TJ


Ratings and Specifications

Size		M12		M18		M30	
Item \ Model		E2V-X2□□	E2V-X4□□	E2V-X5□□	E2V-X8□□	E2V-X10□□	E2V-X15□□
Sensing distance		2mm±10%	4mm±10%	5mm±10%	8mm±10%	10mm±10%	15mm±10%
Set distance		0 to 1.6 mm	0 to 3.2 mm	0 to 4.0 mm	0 to 6.4 mm	0 to 8.0 mm	0 to 12.0 mm
Differential travel		10% max. of sensing distance					
Detectable object		Ferrous metals and non-ferrous metals (The sensing distance depends on the material of the sensing object. Refer to <i>Engineering Data (Typical)</i> .)					
Standard sensing object		Aluminum: 12 × 12 × 3 mm	Aluminum: 12 × 12 × 3 mm	Aluminum: 18 × 18 × 3 mm	Aluminum: 24 × 24 × 3 mm	Aluminum: 30 × 30 × 3 mm	Aluminum: 45 × 45 × 3 mm
Response frequency*		150Hz	40Hz	70Hz	40Hz	70Hz	30Hz
Power supply voltage (operating voltage range)		12 to 24 VDC (10 to 30 VDC), ripple (p-p): 10% max.					
Current consumption		450 mW max. (Current consumption: 15 mA max. at power supply voltage of 30 V)					
Control	Load current	Open-collector output, 100 mA max.					
	Residual voltage	2 V max. (Load current: 100 mA, Cable length: 2 m)					
Indicators		NO Models: Operation indicator (yellow) (flashing), Setting indicator (yellow) (lit); NC Models: Operation indicator (yellow) (lit)					
Operation mode		B1/C1 Models: NO B2/C2 Models: NC (Refer to the timing charts under <i>I/O Circuit Diagrams</i> for details.)					
Protection circuits		Power supply reverse polarity protection, reversed output polarity protection, load short-circuit protection, surge suppressor					
Ambient temperature		Operating/Storage: −25 to 70°C (with no icing or condensation)					
Ambient humidity		Operating/Storage: 35% to 95% (with no condensation)					
Temperature influence		Based on the sensing distance at 23°C in the temperature range of −25 to 70°C					
		±10% max.	±15% max.	±10% max.	±15% max.	±10% max.	±15% max.
Voltage influence		±1.5% max. of sensing distance at rated voltage in the rated voltage ±15% range					
Insulation resistance		50 MΩ min. (at 500 VDC) between current-carrying parts and case					
Dielectric strength		1,000 VAC, 50/60 Hz for 1 minute between current-carrying parts and case					
Vibration resistance		Destruction: 10 to 55 Hz, 1.5-mm double amplitude for 2 hours each in X, Y, and Z directions					
Shock resistance		Destruction: 1,000 m/s ² 10 times each in X, Y, and Z directions					
Degree of protection		IEC IP67 (Pre-wired Models and Pre-wired Connector Models are oil-resistant to the OMRON in-house standard.)					
Connection method		Pre-wired Models (Standard cable length: 2 m), Connector Models, Pre-wired Connector Models (Standard cable length: 300 mm)					
Weight (packed state)	Cable	Approx. 120 g		Approx. 150 g		Approx. 200 g	
	Connector	Approx. 30 g		Approx. 45 g		Approx. 120 g	
	Pre-wired Connector Models	Approx. 50 g		Approx. 70 g		Approx. 140 g	
Materials	Case	Nickel-plated brass					
	Sensing surface	Heat-resistant ABS					
	Clamping nuts	Nickel-plated brass					
	Toothed washer	Zinc-plated iron					
Accessories		Instruction manual					


* The response frequency is an average value.
Measurement conditions are as follows: Standard sensing object, a distance between target objects of twice the size of the standard sensing object, and a set distance of half the sensing distance.

Engineering Data (Typical)


■ Influence of Sensing Object Size and Material



■ Influence of Sensing Object Size and Material






■ Sensing Area



I/O Circuit Diagrams and Timing Charts

■ Output Circuit Diagrams and Connections



Safety Precautions

WARNING

This product is not designed or rated for ensuring safety of persons. Do not use it for such purposes.

Never use the product with an AC power supply. Otherwise, explosion may result.

Influence of Surrounding Metal

When embedding the Sensor in metal, be sure that the clearances given in the following table are maintained.




Table 1. Influence of Surrounding Metal (Unit: mm)

Item	Model	E2V-X2	E2V-X5	E2V-X10
l		0	0	0
d dia.		12	18	30
D		0	0	0
m		12	24	45
n		18	27	45

Item	Model	E2V-X4	E2V-X8	E2V-X15
l		0	0	0 (See Note 1.)
d dia.		12	18	30 (See Note 1.)
D		0	0	0 (See Note 1.)
m		12	24	45
n		18	27	45

Note 1: If the thickness of the mounting bracket (t) exceeds 5 mm, be sure to install the Sensor so that $l \geq 2$, d (dia.) ≥ 45 , and $D \geq 2$.

Mutual Interference

When installing Sensors face-to-face or side-by-side, be sure that the minimum distances given in table 2 are maintained.




Chart 2. Mutual Interference (Unit: mm)

Item	Model	E2V-X2	E2V-X5	E2V-X10
A		30	50	100
B		20	30	50

Item	Model	E2V-X4	E2V-X8	E2V-X15
A		35	60	120
B		25	35	70

Other Information


Sensing Distance

- The sensing distance depends on the sensing object size, material, and thickness.
 - If the sensing object has a thickness of less than 1 mm, the sensing distance will decrease.
 - In some cases, it may not be possible to detect stainless steel.
- Use the following graph and the *Influence of Sensing Object Size and Material* information in *Engineering Data (Typical)* as a reference.

Aluminum and Iron Cuttings

Normally aluminum or iron cuttings will not be detected even if they adhere to or accumulate on the sensing surface. Detection signals may be output for the following. If this occurs, remove the cuttings from the sensing surface.

Diameter of cutting = d and diameter of sensing surface = D
Cuttings in center of sensing surface with $d \geq 2/3D$




Model	Size	D
E2V-X2□/X4□		10
E2V-X5□/X8□		16
E2V-X10□/X15□		28

Tightening Torque

Do not tighten the nut with excessive force.

A washer must be used with the nut.




Model	Tightening Torque	Part A		Part B
		Dimension(mm)	Torque	Torque
E2V-X2/X4		17	5.9N•m	9.8N•m
E2V-X5/X8		22	15N•m	45N•m
E2V-X10/X15		26	39N•m	78N•m

Dimensions


(Unit:mm)

Pre-wired Models


E2V-X2/X4



E2V-X5/X8




E2V-X10/X15




*1 NO Models: Operation indicator (yellow) (flashing)
Setting indicator (yellow) (ON)
NC Models: Operation indicator (yellow) (ON)

Connector Models


E2V-X4□-M1



E2V-X8□-M1




E2V-X15□-M1



* Setting indicator (ON)
Operation indicator (flashing)

Pre-wired Connector Models



Pre-wired Connector Models

Item	Model	E2V-X4□-M1TJ	E2V-X8□-M1TJ	E2V-X15□-M1TJ
A		M12x1	M18x1	M30x1.5
B		60	60	60
C		---	52	52
D		47	42	42
E		21 dia.	29 dia.	42 dia.
F		17	24	36
G		4	4	5

Mounting Hole Dimensions

Proximity Sensor dimensions	M12	M18	M30
Dimension H (mm)	12.5 $^{+0.5}_0$ dia.	18.5 $^{+0.5}_0$ dia.	30.5 $^{+0.5}_0$ dia.

This document provides information mainly for selecting suitable models. Please read the document Instruction Sheet carefully for information that the user must understand and accept before purchase, including information on warranty, limitations of liability, and precautions.

OMRON Corporation

Industrial Automation Company

Sensing Devices Division H.Q.

Industrial Sensors Division

Shiohara, Shimogyo-ku,
Kyoto, 600-8530 Japan
Tel: (81)75-344-7022
Fax: (81)75-344-7107

Regional Headquarters

OMRON EUROPE B.V.

Sensor Business Unit
Carl-Benz-Str. 4, D-71154 Nufringen,
Germany
Tel: (49) 7032-811-0/Fax: (49) 7032-811-199

OMRON ELECTRONICS LLC

One Commerce Drive Schaumburg,
IL 60173-5302 U.S.A.
Tel: (1) 847-843-7900/Fax: (1) 847-843-7787

OMRON ASIA PACIFIC PTE. LTD.

No. 438A Alexandra Road # 05-05/08 (Lobby 2),
Alexandra Technopark, Singapore 119967
Tel: (65) 6835-3011/Fax: (65) 6835-2711

OMRON (CHINA) CO., LTD.

Room 2211, Bank of China Tower,
200 Yin Cheng Zhong Road,
Pu Dong New Area, Shanghai, 200120, China
Tel: (86) 21-5037-2222/Fax: (86) 21-5037-2200

Authorized Distributor:

Note: Specifications subject to change without notice.

Cat. No. D107-E1-01

0907

Read and Understand This Catalog

Please read and understand this catalog before purchasing the products. Please consult your OMRON representative if you have any questions or comments.

Warranty and Limitations of Liability

WARRANTY

OMRON's exclusive warranty is that the products are free from defects in materials and workmanship for a period of one year (or other period if specified) from date of sale by OMRON.

OMRON MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, REGARDING NON-INFRINGEMENT, MERCHANTABILITY, OR FITNESS FOR PARTICULAR PURPOSE OF THE PRODUCTS. ANY BUYER OR USER ACKNOWLEDGES THAT THE BUYER OR USER ALONE HAS DETERMINED THAT THE PRODUCTS WILL SUITABLY MEET THE REQUIREMENTS OF THEIR INTENDED USE. OMRON DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED.

LIMITATIONS OF LIABILITY

OMRON SHALL NOT BE RESPONSIBLE FOR SPECIAL, INDIRECT, OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS, OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED ON CONTRACT, WARRANTY, NEGLIGENCE, OR STRICT LIABILITY.

In no event shall responsibility of OMRON for any act exceed the individual price of the product on which liability is asserted.

IN NO EVENT SHALL OMRON BE RESPONSIBLE FOR WARRANTY, REPAIR, OR OTHER CLAIMS REGARDING THE PRODUCTS UNLESS OMRON'S ANALYSIS CONFIRMS THAT THE PRODUCTS WERE PROPERLY HANDLED, STORED, INSTALLED, AND MAINTAINED AND NOT SUBJECT TO CONTAMINATION, ABUSE, MISUSE, OR INAPPROPRIATE MODIFICATION OR REPAIR.

Application Considerations

SUITABILITY FOR USE

OMRON shall not be responsible for conformity with any standards, codes, or regulations that apply to the combination of products in the customer's application or use of the product.

At the customer's request, OMRON will provide applicable third party certification documents identifying ratings and limitations of use that apply to the products. This information by itself is not sufficient for a complete determination of the suitability of the products in combination with the end product, machine, system, or other application or use.

The following are some examples of applications for which particular attention must be given. This is not intended to be an exhaustive list of all possible uses of the products, nor is it intended to imply that the uses listed may be suitable for the products:

- Outdoor use, uses involving potential chemical contamination or electrical interference, or conditions or uses not described in this catalog.
- Nuclear energy control systems, combustion systems, railroad systems, aviation systems, medical equipment, amusement machines, vehicles, safety equipment, and installations subject to separate industry or government regulations.
- Systems, machines, and equipment that could present a risk to life or property.

Please know and observe all prohibitions of use applicable to the products.

NEVER USE THE PRODUCTS FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND THAT THE OMRON PRODUCT IS PROPERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.

Disclaimers

CHANGE IN SPECIFICATIONS

Product specifications and accessories may be changed at any time based on improvements and other reasons.

It is our practice to change model numbers when published ratings or features are changed, or when significant construction changes are made. However, some specifications of the product may be changed without any notice. When in doubt, special model numbers may be assigned to fix or establish key specifications for your application on your request. Please consult with your OMRON representative at any time to confirm actual specifications of purchased product.

DIMENSIONS AND WEIGHTS

Dimensions and weights are nominal and are not to be used for manufacturing purposes, even when tolerances are shown.

ERRORS AND OMISSIONS

The information in this catalog has been carefully checked and is believed to be accurate; however, no responsibility is assumed for clerical, typographical, or proofreading errors, or omissions.

PERFORMANCE DATA

Performance data given in this catalog is provided as a guide for the user in determining suitability and does not constitute a warranty. It may represent the result of OMRON's test conditions, and the users must correlate it to actual application requirements. Actual performance is subject to the OMRON Warranty and Limitations of Liability.

PROGRAMMABLE PRODUCTS

OMRON shall not be responsible for the user's programming of a programmable product, or any consequence thereof.

COPYRIGHT AND COPY PERMISSION

This catalog shall not be copied for sales or promotions without permission.

This catalog is protected by copyright and is intended solely for use in conjunction with the product. Please notify us before copying or reproducing this catalog in any manner, for any other purpose. If copying or transmitting this catalog to another, please copy or transmit it in its entirety.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9