Type ESRD Solid Polymer Aluminum SMT Capacitors

Filtering power of 3 or more tantalum chips and 50 year life



Solid Polymer Aluminum capacitors combine the high capacitance capability of an electrolytic component with the high frequency performance of film capacitors. When the need for low impedance at high frequency is critical for your design, one ESRD chip is capable of replacing several liquid electrolyte aluminum or tantalum capacitors connected in parallel. This is due to the ultra-low ESR which results in significantly lower impedance than either aluminum or tantalum capacitors at frequencies of 100 kHz and above. There is no longer a need to stack capacitors to lower the impedance at high frequency. The low ESR and high capacitance make them ideal for bypassing high frequency noise, and for switching frequency filtering in DC/ DC conversion. ESRD capacitors are packaged in a molded resin case with the same footprint (7.3 x 4.3 mm) as the industry standard tantalum "D" and "E" case sizes. The solid electrolyte results in a capacitor with stable impedance and equivalent series resistance over the entire operating temperature range and they have more than twice the ripple current handling capability of tantalum capacitors. In addition, the solid electrolyte delivers a typical expected operating life of more than 50 years, and it is ignition free.

Applications

Motherboard By-Pass
Switching Supply Input/Output Filters
Power Supply Decoupling
High Frequency Noise Reduction
Laptop LCD Displays
Automotive Digital Equipment
Portable Electronic Equipment

Markings



Capacitance
("R" = Decimal Point)

Lot Code

Polarity Stripe (Anode)
+

W.V. Code

D = 2.0 V	**K** = 8.0 V
E = 2.5 V	**B** = 12.5 V
G = 4.0 V	**C** = 16.0 V
J = 6.3 V	

Ordering Information

ESRD **4R7** **M** **16** **R**

CDE Type

Capacitance Code
4R7 = 4.7 µF
220 = 22 µF
101 = 100 µF

Capacitance Tolerance
M = ± 20%

WVDC Code

02 = 2.0 Vdc	**08** = 8.0 Vdc
0E = 2.5 Vdc	**12** = 12.5 Vdc
04 = 4.0 Vdc	**16** = 16.0 Vdc
06 = 6.3 Vdc	

Packaging Code
R = Tape & Reel
ESRD (1.8 mm Ht.): 3500 pcs/reel
ESRD (2.8 mm Ht.): 2000 pcs/reel

Type ESRD Solid Polymer Aluminum SMT Capacitors

High Voltage

Outline Drawing



Dimensions in mm

Ratings

Capacitance (µF)	Catalog Part Number (Tape & Reel)	Maximum E.S.R 100 kHz/20 °C (Ω)	Maximum1 Ripple Current 100 kHz/105 °C (Amps)	Case Height H (mm)
		2.0 Vdc		
100	ESRD101M02R	0.018	2.5	1.8 ±0.1
120	ESRD121M02XR	0.015	2.7	1.8 ±0.1
180	ESRD181M02R	0.015	3.0	2.8 ±0.2
220	ESRD221M02R	0.015	3.0	2.8 ±0.2
270	ESRD271M02XR	0.012	3.3	2.8 ±0.2
		2.5 Vdc		
82	ESRD820M0ER	0.018	2.5	1.8 ±0.1
100	ESRD101M0EXR	0.015	2.7	1.8 ±0.1
150	ESRD151M0ER	0.015	3.0	2.8 ±0.2
180	ESRD181M0ER	0.015	3.0	2.8 ±0.2
220	ESRD221M0EXR	0.012	3.3	2.8 ±0.2
		4.0 Vdc		
56	ESRD560M04R	0.018	2.5	1.8 ±0.1
82	ESRD820M04XR	0.015	2.7	1.8 ±0.1
120	ESRD121M04R	0.015	3.0	2.8 ±0.2
150	ESRD151M04XR	0.012	3.3	2.8 ±0.2
		6.3 Vdc		
10	ESRD100M06R	0.055	1.4	1.8 ±0.1
22	ESRD220M06R	0.040	1.6	1.8 ±0.1
33	ESRD330M06R	0.028	2.0	1.8 ±0.1
47	ESRD470M06R	0.018	2.5	1.8 ±0.1
68	ESRD680M06XR	0.015	2.7	1.8 ±0.1
100	ESRD101M06R	0.015	3.0	2.8 ±0.2
120	ESRD121M06XR	0.012	3.3	2.8 ±0.2
		8.0 Vdc		
8.2	ESRD8R2M08R	0.055	1.4	1.8 ±0.1
15	ESRD150M08R	0.040	1.6	1.8 ±0.1
22	ESRD220M08R	0.028	2.0	1.8 ±0.1
33	ESRD330M08R	0.018	2.5	1.8 ±0.1
68	ESRD680M08R	0.015	3.0	2.8 ±0.2
		12.5 Vdc		
4.7	ESRD4R7M12R	0.080	1.0	1.8 ±0.1
10	ESRD100M12R	0.060	1.0	1.8 ±0.1
15	ESRD150M12R	0.050	1.3	1.8 ±0.1
22	ESRD220M12R	0.030	1.6	1.8 ±0.1
		16.0 Vdc		
2.2	ESRD2R2M16R	0.110	1.0	1.8 ±0.1
4.7	ESRD4R7M16R	0.080	1.0	1.8 ±0.1
6.8	ESRD6R8M16R	0.070	1.0	1.8 ±0.1
8.2	ESRD8R2M16R	0.045	1.3	1.8 ±0.1

Specifications

Operating Temperature Range:
–55 °C to +105 °C, at 100% rated voltage

Surge Voltage:
125% of the rated working Vdc

Capacitance Range:
2.2 µF to 270 µF

Capacitance Tolerance:
±20% at 120 Hz and +20 °C

DC Leakage Current (DCL):
After a two minute application of the rated working voltage at +20 °C:

2V — 4V: $I \leq 0.06CV$
6.3V — 16V: $I \leq 0.04CV$ or 3 µA
(whichever greater)

Dissipation Factor (DF):
The ratio of the capacitorís equivalent series resistance to its reactance at 120Hz and +20 ºC
ESRD (1.8 mm ht.): DF is 0.06 Max.
ESRD (2.8 mm ht.): DF is 0.10 Max.

Resistance to Soldering Heat:
Heat the capacitors at 235 ºC in an oven for 200 seconds. The capacitors will meet the following limits after stabilizing at 20 ºC:

ΔC = ±10% of the initial measured value
DF ≤ the initial specified value
DCL ≤ the initial specified value

Vibration:
No abnormal change shall occur to capacitors that have been soldered (and attached) to a board when subjected to a vibration of 1.5 mm amplitude that is varied from 10 Hz to 2000 Hz in 20 min. cycles. The test duration is 2 hours for each right angle direction (total 6 hours). Capacitance is monitored during the last cycle of the test for stablilty.

Moisture Resistance:
After 500 hours storage at +60 ºC and 90% to 95% RH without load, the capacitor will meet the following limits:

ΔC = +70%/–20% of the initial measured value (2.0 Vdc, 2.5 Vdc), +60%/–20% of the initial measured value (4.0 Vdc), +50%/–20% of the initial measured value (6.3 Vdc), +40%/–20% of the initial measured value (all other voltages)
DF ≤ two times the initial specified value
DCL ≤ the initial specified value

Life Test:
Apply rated DC working voltage at 105 ºC for 1000 hours, and then stabilize them to +20 ºC. Capacitors will meet the following limits:

ΔC = ±10% of the initial measured value
DF ≤ the initial specified value
DCL ≤ the initial specified value

Shelf Life Test:
Shelf life is typically 5 to 10 years. Accelerated test: after 500 hours at 105 ºC, capacitors will meet the following limits after stabilization at 20 ºC:

ΔC = ±10% of the initial measured value
DF ≤ the initial specified value
DCL ≤ the initial specified value

Shear Test:
No damage shall be visible after subjecting a mounted capacitor to a side force of 5 N for 10 seconds

(For more information on this product please see the Solid Polymer Aluminum Capacitors Application Guide)

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9