

## Lower Voltage Ceramic Singlelayer DC Disc Capacitors 1 kV<sub>DC</sub> to 3 kV<sub>DC</sub> Low Dissipation Factor


**RoHS**  
COMPLIANT

**FEATURES**

- Low losses
- High stability
- Low DF minimizes self heating at HF
- Ideal for high switching to 100 kHz
- Radial leads
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)

**APPLICATIONS**

- SMPS
- HF ballast
- Snubber and HV circuits

**DESIGN**

The capacitors consist of a ceramic disc of which both sides are silver-plated. Connection leads are made of tinned copper having diameters of 0.022" (0.51 mm) or 0.025" (0.64 mm).

The capacitors may be supplied with radial kinked or straight leads having lead spacing of 0.250" (6.35 mm) or 0.375" (9.5 mm).

The standard tolerances are  $\pm 5\%$ ,  $\pm 10\%$ .

Coating is made of flammable retardant epoxy resin in accordance with "UL 94 V-0".

**CAPACITANCE RANGE**

10 pF to 6800 pF

**RATED VOLTAGE**

1000 V<sub>DC</sub> (500 V<sub>RMS</sub>)  
 2000 V<sub>DC</sub> (1000 V<sub>RMS</sub>)  
 3000 V<sub>DC</sub> (1500 V<sub>RMS</sub>)

**DIELECTRIC STRENGTH BETWEEN LEADS**

Component test:

1000 V<sub>DC</sub>      2500 V<sub>DC</sub>, 2 s  
 2000 V<sub>DC</sub>      4000 V<sub>DC</sub>, 2 s  
 3000 V<sub>DC</sub>      6000 V<sub>DC</sub>, 2 s

**CERAMIC DIELECTRIC**

C0G, N1500, N2000, N2200, N2500, N2800 (Class 1)

| QUICK REFERENCE DATA       |  |      |      |
|----------------------------|--|------|------|
| DESCRIPTION                | VALUE                                  |      |      |
| Ceramic Class              | 1                                      |      |      |
| Ceramic Dielectric         | C0G, N1500, N2000, N2200, N2500, N2800 |      |      |
| Voltage (V <sub>DC</sub> ) | 1000                                   | 2000 | 3000 |
| Min. Capacitance (pF)      | 10                                     | 10   | 10   |
| Max. Capacitance (pF)      | 6800                                   | 6800 | 4700 |
| Mounting                   | Radial                                 |      |      |

**INSULATION RESISTANCE**

Min. 50 000 M $\Omega$

**TOLERANCE ON CAPACITANCE**

$\pm 5\%$ ,  $\pm 10\%$

**DISSIPATION FACTOR**

0.1 % max. at 1 kHz; 1 V

**CATEGORY TEMPERATURE RANGE**

-55 °C to +125 °C

**CLIMATIC CATEGORY ACC. TO EN 60068-1**

55/125/21

**OPERATING TEMPERATURE RANGE**

-55 °C to +105 °C



| <b>ORDERING INFORMATION, CERAMIC 1 kV<sub>DC</sub> LOW DISSIPATION FACTOR</b> |             |  |   |   |  |           |              |      |                  |             |             |
|---|-------------|--|---|---|--|-----------|--------------|------|------------------|-------------|-------------|
| C<br>(pF)   | TOL.<br>(%) | D <sub>max.</sub><br>DIAMETER<br>INCH (mm) | T <sub>max.</sub><br>THICKNESS<br>INCH (mm) | LS<br>LEAD SPACE<br>INCH (mm)<br>± 1 mm | LO<br>LEAD OFFSET<br>INCH (mm)<br>± 0.5 mm | WIRE SIZE |              | FIG. | ORDERING<br>CODE |             |             |
|   |             |  |   |   |  | AWG       | INCH (mm)    |      |                  |             |             |
| <b>C0G (NPO)</b>  |             |  |   |   |  |           |              |      |                  |             |             |
| 10  | ± 5         | 0.250 (6.4)                                | 0.156 (4.0)                                 | 0.250 (6.4)                             | 0.043 (1.1)                                | 22        | 0.025 (0.64) | 1    | 561R1DF0Q10      |             |             |
| 12  |             |  |   |   | 0.051 (1.3)                                |           |              |      | 561R1DF0Q12      |             |             |
| <b>N1500</b>  |             |  |   |   |  |           |              |      |                  |             |             |
| 22  | ± 5         | 0.250 (6.4)                                | 0.156 (4.0)                                 | 0.250 (6.4)                             | 0.043 (1.1)                                | 22        | 0.025 (0.64) | 1    | 561R1DF0Q22      |             |             |
| 47  |             |  |   |   | 0.071 (1.8)                                |           |              |      | 561R1DF0Q47      |             |             |
| 56  |             |  |   |   | 0.055 (1.4)                                |           |              |      | 561R1DF0Q56      |             |             |
| 68  |             |  |   |   | 0.059 (1.5)                                |           |              |      | 561R1DF0Q68      |             |             |
| 82  |             |  |   |   | 0.047 (1.2)                                |           |              |      | 561R1DF0Q82      |             |             |
| <b>N2200</b>  |             |  |   |   |  |           |              |      |                  |             |             |
| 33  | ± 10        | 0.250 (6.4)                                | 0.156 (4.0)                                 | 0.250 (6.4)                             | 0.043 (1.1)                                | 22        | 0.025 (0.64) | 1    | 561R1DF0Q33      |             |             |
| <b>N2000</b>  |             |  |   |   |  |           |              |      |                  |             |             |
| 100   | ± 10        | 0.250 (6.4)                                | 0.156 (4.0)                                 | 0.250 (6.4)                             | 0.059 (1.5)                                | 22        | 0.025 (0.64) | 1    | 561R1DF0T10      |             |             |
| 120   |             |  |   |   | 0.055 (1.4)                                |           |              |      | 561R1DF0T12      |             |             |
| 150   |             |  |   |   | 0.043 (1.1)                                |           |              |      | 561R1DF0T15      |             |             |
| 180   |             |  |   |   | 0.043 (1.1)                                |           |              |      | 561R1DF0T18      |             |             |
| <b>N2500</b>  |             |  |   |   |  |           |              |      |                  |             |             |
| 220   | ± 10        | 0.250 (6.4)                                | 0.156 (4.0)                                 | 0.250 (6.4)                             | 0.059 (1.5)                                | 22        | 0.025 (0.64) | 1    | 561R1DF0T22      |             |             |
| 270   |             |  |   |   | 0.043 (1.1)                                |           |              |      | 561R1DF0T27      |             |             |
| <b>N2800</b>  |             |  |   |   |  |           |              |      |                  |             |             |
| 330   | ± 10        | 0.250 (6.4)                                | 0.156 (4.0)                                 | 0.250 (6.4)                             | 0.047 (1.2)                                | 22        | 0.025 (0.64) | 1    | 561R1DF0T33      |             |             |
| 390   |             |  |   |   | 0.047 (1.2)                                |           |              |      | 561R1DF0T39      |             |             |
| 470   |             |  |   |   | 0.290 (7.4)                                |           |              |      | 0.059 (1.5)      | 561R1DF0T47 |             |
| 560   |             |  |   |   |  |           |              |      | 0.055 (1.4)      | 561R1DF0T56 |             |
| 680   |             |  |   |   |  |           |              |      | 0.047 (1.2)      | 561R1DF0T68 |             |
| 820   |             | 0.370 (9.4)                                |   |   | 0.043 (1.1)                                |           |              |      | 561R1DF0T82      |             |             |
| 1000  |             |  |   |   | 0.055 (1.4)                                |           |              |      | 561R1DF0D10      |             |             |
| 1200  |             |  |   |   | 0.047 (1.2)                                |           |              |      | 561R1DF0D12      |             |             |
| 1500  |             |  |   |   | 0.047 (1.2)                                |           |              |      | 561R1DF0D15      |             |             |
| 1800  |             |  |   |   | 0.047 (1.2)                                |           |              |      | 561R1DF0D18      |             |             |
| 2200  |             | 0.051 (1.3)                                |   |   | 561R1DF0D22                                |           |              |      |                  |             |             |
| 2700  |             | 0.047 (1.2)                                |   |   | 561R1DF0D27                                |           |              |      |                  |             |             |
| 3300  |             | 0.047 (1.2)                                |   |   | 561R1DF0D33                                |           |              |      |                  |             |             |
| 3900  |             | 0.560 (14.2)                               |   |   | 0.156 (4.0)                                |           |              |      | 0.375 (9.5)      | 0.047 (1.2) | 561R1DF0D39 |
| 4700  |             |  |   |   |  |           |              |      |                  | 0.047 (1.2) | 561R1DF0D47 |
| 5600  | 0.047 (1.2) |  | 561R1DF0D56                                 |   |  |           |              |      |                  |             |             |
| 6800  | 0.047 (1.2) |  | 561R1DF0D68                                 |   |  |           |              |      |                  |             |             |
| 6800  | 0.047 (1.2) |  | 561R1DF0D68                                 |   |  |           |              |      |                  |             |             |

**Note**

- Alternate lead spacings of 5 mm, 7.5 mm or 10 mm are available on request.



| ORDERING INFORMATION, CERAMIC 2 kV <sub>DC</sub> LOW DISSIPATION FACTOR |             |  |   |   |  |           |              |      |                  |
|---|-------------|--|---|---|--|-----------|--------------|------|------------------|
| C<br>(pF)   | TOL.<br>(%) | D <sub>max.</sub><br>DIAMETER<br>INCH (mm) | T <sub>max.</sub><br>THICKNESS<br>INCH (mm) | LS<br>LEAD SPACE<br>INCH (mm)<br>± 1 mm | LO<br>LEAD OFFSET<br>INCH (mm)<br>± 0.5 mm | WIRE SIZE |              | FIG. | ORDERING<br>CODE |
|   |             |  |   |   |  | AWG       | INCH (mm)    |      |                  |
| <b>N1500</b>  |             |  |   |   |  |           |              |      |                  |
| 33  | ± 5         | 0.290 (7.4)                                | 0.195 (5.0)                                 | 0.250 (6.4)                             | 0.098 (2.5)                                | 20        | 0.032 (0.81) | 1    | 564R2DF0Q33      |
| 39  |             |  | 0.180 (4.6)                                 |   | 0.083 (2.1)                                |           |              |      | 564R2DF0Q39      |
| 47  |             |  | 0.170 (4.3)                                 |   | 0.071 (1.8)                                |           |              |      | 564R2DF0Q47      |
| <b>N2000</b>  |             |  |   |   |  |           |              |      |                  |
| 56  | ± 5         | 0.290 (7.4)                                | 0.210 (5.3)                                 | 0.250 (6.4)                             | 0.110 (2.8)                                | 20        | 0.032 (0.81) | 1    | 564R2DF0Q56      |
| 68  |             |  | 0.190 (4.8)                                 |   | 0.091 (2.3)                                |           |              |      | 564R2DF0Q68      |
| 82  |             |  | 0.175 (4.5)                                 |   | 0.075 (1.9)                                |           |              |      | 564R2DF0Q82      |
| 100   |             |  | 0.170 (4.3)                                 |   | 0.071 (1.8)                                |           |              |      | 564R2DF0T10      |
| <b>N2500</b>  |             |  |   |   |  |           |              |      |                  |
| 120   | ± 10        | 0.290 (7.4)                                | 0.185 (4.7)                                 | 0.250 (6.4)                             | 0.087 (2.2)                                | 20        | 0.032 (0.81) | 1    | 564R2DF0T12      |
| 150   |             |  | 0.170 (4.3)                                 |   | 0.071 (1.8)                                |           |              |      | 564R2DF0T15      |
| 180   |             |  | 0.185 (4.7)                                 |   | 0.071 (1.8)                                |           |              |      | 564R2DF0T18      |
| 270   |             | 0.330 (8.4)                                | 0.170 (4.3)                                 |   | 0.079 (2.0)                                |           |              |      | 564R2DF0T27      |
| 470   |             | 0.400 (10.2)                               | 0.170 (4.3)                                 |   | 0.075 (1.9)                                |           |              |      | 564R2DF0T47      |
| <b>N2800</b>  |             |  |   |   |  |           |              |      |                  |
| 220   | ± 10        | 0.290 (7.4)                                | 0.170 (4.3)                                 | 0.250 (6.4)                             | 0.087 (2.2)                                | 20        | 0.032 (0.81) | 1    | 564R2DF0T22      |
| 330   |             | 0.330 (8.4)                                | 0.185 (4.7)                                 |   | 0.083 (2.1)                                |           |              |      | 564R2DF0T33      |
| 390   |             | 0.330 (8.4)                                | 0.175 (4.5)                                 |   | 0.075 (1.9)                                |           |              |      | 564R2DF0T39      |
| 560   |             | 0.400 (10.2)                               | 0.185 (4.7)                                 |   | 0.087 (2.2)                                |           |              |      | 564R2DF0T56      |
| 680   |             | 0.400 (10.2)                               | 0.170 (4.3)                                 |   | 0.075 (1.9)                                |           |              |      | 564R2DF0T68      |
| 820   |             | 0.430 (10.9)                               | 0.175 (4.5)                                 |   | 0.075 (1.9)                                |           |              |      | 564R2DF0T82      |
| 1000  |             | 0.460 (11.7)                               | 0.170 (4.3)                                 |   | 0.075 (1.9)                                |           |              |      | 564R2DF0D10      |
| 1500  |             | 0.530 (13.5)                               |   |   | 0.071 (1.8)                                |           |              |      | 564R2DF0D15      |
| 1800  |             | 0.560 (14.2)                               | 0.170 (4.3)                                 |   | 0.071 (1.8)                                |           |              |      | 564R2DF0D18      |
| 2200  |             | 0.680 (17.3)                               | 0.180 (4.6)                                 | 0.375 (9.5)                             | 0.083 (2.1)                                |           |              |      | 564R2DF0D22      |
| 2300  |             |  | 0.175 (4.5)                                 |   | 0.079 (2.0)                                |           |              |      | 564R2DF0D23      |
| 2400  |             |  | 0.175 (4.5)                                 |   | 0.075 (1.9)                                |           |              |      | 564R2DF0D24      |
| 2700  |             |  | 0.170 (4.3)                                 |   | 0.071 (1.8)                                |           |              |      | 564R2DF0D27      |
| 3300  |             |  | 0.720 (18.3)                                |   | 0.170 (4.3)                                |           |              |      | 0.071 (1.8)      |
| 3900  |             | 0.790 (20.1)                               | 0.180 (4.6)                                 | 0.075 (1.9)                             | 564R2DF0D39                                |           |              |      |                  |
| 4700  |             | 0.900 (22.9)                               |   | 0.083 (2.1)                             | 564R2DF0D47                                |           |              |      |                  |
| 5600  |             | 0.900 (22.9)                               |   | 0.170 (4.3)                             | 0.075 (1.9)                                |           |              |      | 564R2DF0D56      |
| 6800  |             | 0.950 (24.1)                               | 0.170 (4.3)                                 | 0.071 (1.8)                             | 564R2DF0D68                                |           |              |      |                  |

**Note**

- Alternate lead spacings of 5 mm, 7.5 mm or 10 mm are available on request.



| ORDERING INFORMATION, CERAMIC 3 kV <sub>DC</sub> LOW DISSIPATION FACTOR |             |  |   |   |  |           |              |      |                  |             |
|---|-------------|--|---|---|--|-----------|--------------|------|------------------|-------------|
| C<br>(pF)   | TOL.<br>(%) | D <sub>max.</sub><br>DIAMETER<br>INCH (mm) | T <sub>max.</sub><br>THICKNESS<br>INCH (mm) | LS<br>LEAD SPACE<br>INCH (mm)<br>± 1 mm | LO<br>LEAD OFFSET<br>INCH (mm)<br>± 0.5 mm | WIRE SIZE |              | FIG. | ORDERING<br>CODE |             |
|   |             |  |   |   |  | AWG       | INCH (mm)    |      |                  |             |
| <b>N1500</b>  |             |  |   |   |  |           |              |      |                  |             |
| 10  | ± 5         | 0.290 (7.4)                                | 0.185 (4.7)                                 | 0.250 (6.4)                             | 0.087 (2.2)                                | 20        | 0.032 (0.81) | 1    | 564R3DF0Q10      |             |
| 27  |             |  | 0.220 (5.6)                                 |   | 0.122 (3.1)                                |           |              |      | 564R3DF0Q27      |             |
| 33  |             |  | 0.195 (5.0)                                 |   | 0.098 (2.5)                                |           |              |      | 564R3DF0Q33      |             |
| 39  |             |  | 0.190 (4.8)                                 |   | 0.094 (2.4)                                |           |              |      | 564R3DF0Q39      |             |
| 47  |             |  | 0.225 (5.7)                                 |   | 0.126 (3.2)                                |           |              |      | 564R3DF0Q47      |             |
| <b>N2200</b>  |             |  |   |   |  |           |              |      |                  |             |
| 12  | ± 5         | 0.290 (7.4)                                | 0.210 (5.3)                                 | 0.250 (6.4)                             | 0.110 (2.8)                                | 20        | 0.032 (0.81) | 1    | 564R3DF0Q12      |             |
| 22  |             | 0.330 (8.4)                                | 0.210 (5.3)                                 |   | 0.110 (2.8)                                |           |              |      | 564R3DF0Q22      |             |
| <b>N2000</b>  |             |  |   |   |  |           |              |      |                  |             |
| 56  | ± 5         | 0.290 (7.4)                                | 0.210 (5.3)                                 | 0.250 (6.4)                             | 0.110 (2.8)                                | 20        | 0.032 (0.81) | 1    | 564R3DF0Q56      |             |
| 68  |             |  | 0.190 (4.8)                                 |   | 0.098 (2.5)                                |           |              |      | 564R3DF0Q68      |             |
| 82  |             |  | 0.185 (4.7)                                 |   | 0.091 (2.3)                                |           |              |      | 564R3DF0Q82      |             |
| <b>N2500</b>  |             |  |   |   |  |           |              |      |                  |             |
| 100   | ± 10        | 0.290 (7.4)                                | 0.205 (5.2)                                 | 0.250 (6.4)                             | 0.106 (2.7)                                | 20        | 0.032 (0.81) | 1    | 564R3DF0T10      |             |
| 120   |             | 0.290 (7.4)                                | 0.190 (4.8)                                 |   | 0.091 (2.3)                                |           |              |      | 564R3DF0T12      |             |
| 220   |             | 0.330 (8.4)                                | 0.190 (4.8)                                 |   | 0.091 (2.3)                                |           |              |      | 564R3DF0T22      |             |
| <b>N2800</b>  |             |  |   |   |  |           |              |      |                  |             |
| 150   | ± 10        | 0.290 (7.4)                                | 0.200 (5.1)                                 | 0.250 (6.4)                             | 0.091 (2.3)                                | 20        | 0.032 (0.81) | 1    | 564R3DF0T15      |             |
| 180   |             | 0.290 (7.4)                                | 0.190 (4.8)                                 |   | 0.091 (2.3)                                |           |              |      | 564R3DF0T18      |             |
| 270   |             | 0.330 (8.4)                                | 0.205 (5.2)                                 |   | 0.110 (2.8)                                |           |              |      | 564R3DF0T27      |             |
| 330   |             | 0.330 (8.4)                                | 0.190 (4.8)                                 |   | 0.091 (2.3)                                |           |              |      | 564R3DF0T33      |             |
| 390   |             | 0.400 (10.2)                               | 0.215 (5.5)                                 |   | 0.102 (2.6)                                |           |              |      | 564R3DF0T39      |             |
| 470   |             | 0.400 (10.2)                               | 0.195 (5.0)                                 |   | 0.087 (2.2)                                |           |              |      | 564R3DF0T47      |             |
| 560   |             | 0.430 (10.9)                               | 0.200 (5.1)                                 |   | 0.102 (2.6)                                |           |              |      | 564R3DF0T56      |             |
| 680   |             | 0.460 (11.7)                               | 0.195 (5.0)                                 |   | 0.087 (2.2)                                |           |              |      | 564R3DF0T68      |             |
| 820   |             | 0.490 (12.5)                               | 0.195 (5.0)                                 |   | 0.102 (2.6)                                |           |              |      | 564R3DF0T82      |             |
| 1000  |             | 0.530 (13.5)                               | 0.190 (4.8)                                 | 0.091 (2.3)                             | 564R3DF0D10                                |           |              |      |                  |             |
| 1200  |             | 0.560 (14.2)                               | 0.190 (4.8)                                 | 0.375 (9.5)                             | 0.091 (2.3)                                |           |              |      | 564R3DF0D12      |             |
| 1500  |             | 0.620 (15.8)                               |   |   | 0.091 (2.3)                                |           |              |      | 564R3DF0D15      |             |
| 1800  |             | 0.680 (17.3)                               |   |   | 0.098 (2.5)                                |           |              |      | 564R3DF0D18      |             |
| 2200  |             | 0.720 (18.3)                               |   |   | 0.094 (2.4)                                |           |              |      | 564R3DF0D22      |             |
| 2700  |             | 0.790 (20.1)                               |   |   | 0.190 (4.8)                                |           |              |      | 0.087 (2.2)      | 564R3DF0D27 |
| 3300  |             | 0.900 (22.9)                               |   |   | 0.200 (5.1)                                |           |              |      | 0.102 (2.6)      | 564R3DF0D33 |
| 4700  |             | 0.950 (24.1)                               |   |   | 0.185 (4.7)                                |           |              |      | 0.087 (2.2)      | 564R3DF0D47 |

**Note**

- Alternate lead spacings of 5 mm, 7.5 mm or 10 mm are available on request.

**TAPE AND REEL OPTIONS**

Part number codes and specifications for tape and reel packaging are found in the general information document - find web-link below.



Power Rating - 1DFO Series 500 V<sub>RMS</sub> Low DF - Note 1



Note 2

Power Rating - 2DFO Series 1000 V<sub>RMS</sub> Low DF - Note 1



Note 2

Power Rating - 3DFO Series 1500 V<sub>RMS</sub> Low DF - Note 1



Note 2

**Note 1**

Power ratings are based on still air 60 °C ambient with additional 30 °C rise due to self heating. Thermal effects such as forced air cooling, component encapsulation or other heat-sinking techniques will alter ratings. Actual circuit for application recommended.

**Note 2**

For convenience, power rating charts are shown to 100 kHz. Higher frequency operation is permissible with appropriate derating. Consult us for application suggestions.

Temperature Characteristics for 1DFO, 2DFO & 3DFO Series



**RELATED DOCUMENTS**

General Information

[www.vishay.com/doc?23140](http://www.vishay.com/doc?23140)



## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9