



The CA178 cable assemblies offered by Laird are engineered for peak performance up to 6 GHz. They are tested 100% and certified to meet performance specifications. Equipment manufacturers require certified cable assemblies to minimize system losses to within known parameters and these cable assemblies meet those requirements. The manufacturing processes and raw materials are well controlled in order to provide very consistent performance from lot to lot.

FEATURES

- Consistent low loss design construction
- 100% tested and certified to meet specifications
- Various connector options available
- Flexible high temperature kink resistant cable jacket

MARKETS

- High performance wireless systems
- OEM equipment
- WiMAX

INSERTION LOSS BY FREQUENCY



| PARAMETER | CA178-NFB-UFL-8 | CA178-NFB-UFL-12 |
|-------------------------------|-------------------------|-------------------------|
| Insertion loss (700-5825 MHz) | -1.5 dB max | -2.5 dB max |
| Length | 8 in (203 mm) | 12 in (305 mm) |
| Weight | 1.4 oz (40 gm) | 1.5 oz (43 gm) |
| Connector types | N female bulkhead - UFL | N female bulkhead - UFL |
| N connector seal | O-ring | O-ring |
| Contact plating | Gold | Gold |
| Operating temperature | -40 to +125°C | -40 to +125°C |

SYSTEM ORDERING

- CA178-NFB-UFL-8 N Female Bulkhead to U.FL 8 in
- CA178-NFB-UFL-12 N Female Bulkhead to U.FL
- CA178-NM-UFL-8 12 in N Male to U.FL 8 in
- CA178-NM-UFL-12 N Male to U.FL 12 in

Americas: +1.847 839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941
IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127
IAS-AsiaSales@lairdtech.com

www.lairdtech.com



Smart Technology. Delivered.

RF Cable Assembly

CA178

700 MHz to 5.82 GHz

| PART NUMBER | CONNECTOR 1 | CONNECTOR 2 | CABLE LENGTH (INCHES) | CABLE TYPE | MAX INSERTION LOSS (DB) |
|------------------------|---------------------------------------|---------------------------|-----------------------|---------------------|-------------------------|
| CA100-NFB-MC-12 | N female bulkhead | MC-card | 12 | LMR100 (equivalent) | 1.5 |
| CA100-NFB-MMCX-12 | N female bulkhead | MMCX | 12 | LMR100 (equivalent) | 1.5 |
| CA100-NFB-RASMAM-12 | N female bulkhead | Right angle SMA male | 12 | LMR100 (equivalent) | 1 |
| CA100-NFB-RMMCX-12 | N female bulkhead | Reverse polarity MMCX | 12 | LMR100 (equivalent) | 1.5 |
| CA100-NFB-RSMAM-12 | N female bulkhead | Reverse polarity SMA male | 12 | LMR100 (equivalent) | 1 |
| CA100-NFB-RTNCM-12 | N female bulkhead | Reverse polarity TNC male | 12 | LMR100 (equivalent) | 1 |
| CA100-NFB-SMAM-8 | N female bulkhead | SMA male | 8 | LMR100 (equivalent) | 0.8 |
| CA100-NM-MC-12 | N male | MC-card | 12 | LMR100 (equivalent) | 1 |
| CA100-NM-MMCX-12 | N male | MMCX | 12 | LMR100 (equivalent) | 1 |
| CA100-NM-RASMAM-12 | N male | Right angle SMA male | 12 | LMR100 (equivalent) | 1 |
| CA100-NM-RSMAM-12 | N male | Reverse polarity SMA male | 12 | LMR100 (equivalent) | 1 |
| CA100-NM-RTNCM-12 | N male | Reverse polarity TNC male | 12 | LMR100 (equivalent) | 1 |
| CA100-RPSMAM-RASMAM-12 | Reverse polarity SMA male | Right angle SMA male | 12 | LMR100 (equivalent) | 1 |
| CA100-RPTNCF-NC-6 | Reverse polarity TNC female bulkhead | No connector | 6 | LMR100 (equivalent) | 0.5 |
| CA100-RPTNCM-RASMAM-12 | Reverse polarity TNC male | Right angle SMA male | 12 | LMR100 (equivalent) | 1 |
| CA100-TNCF-NC-6 | TNC female bulkhead | No connector | 6 | LMR100 (equivalent) | 0.5 |
| CA178-NFB-UFL-12 | N female bulkhead | U.FL | 12 | RG178 hi freq | 2 |
| CA178-NFB-UFL-8 | N female bulkhead | U.FL | 8 | RG178 hi freq | 1.5 |
| CA178-NM-UFL-12 | N male | U.FL | 12 | RG178 hi freq | 2 |
| CA178-NM-UFL-8 | N male | U.FL | 8 | RG178 hi freq | 1.5 |
| CA178-RTNCB-MMCX-4 | Reverse polarity TNC bulkhead (black) | | 4 | RG178 hi freq | 0.8 |
| CA178-RTNCB-MMCX-6 | MMCX Reverse polarity TNC bulkhead | | 6 | RG178 hi freq | 1 |
| CA178-RTNCB-UFL-6 | (black) MMCX Reverse polarity TNC | | 6 | RG178 hi freq | 1 |
| CA400-NM-NM-48 | N male bulkhead (black) | U.FL N male | 48 | LMR400 (equivalent) | 0.8 |
| CA58-NM-MCX-197 | N male | MCX | 197 | RG58/u (white) | 5 |
| CA58-SMA-MCX-96 | Right angle SMA male | MCX | 96 | RG58/u (white) | 2.5 |
| CA58-SMA-NF-96 | Right angle SMA male | N female bulkhead | 96 | RG58/u (white) | 2.5 |
| CA58-SMA-RSMA-96 | Right angle SMA male | Reverse polarity SMA male | 96 | RG58/u (white) | 2.5 |
| CA58-SMA-RTNC-96 | Right angle SMA male | Reverse polarity TNC male | 96 | RG58/u (white) | 2.5 |
| CA58-SMA-SMAF-96 | Right angle SMA male | SMA female bulkhead | 96 | RG58/u (white) | 2.5 |

Americas: +1.847.839.6907
 IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941
 IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127
 IAS-AsiaSales@lairdtech.com

www.lairdtech.com

ANT-DS-CA178 0115

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9