

D

C

B


A

D

C

B

A



SPECIFICATIONS:
MAKE-BEFORE-BREAK

MATERIALS:
FRAME: STEEL, ZINC PLATE
ACTUATOR: POM UL94HB, BLACK
FIXED CONTACT/TERMINAL: COPPER ALLOY,SILVER OVER NICKEL PLATE
MOVING CONTACT: COPPER ALLOY, SILVER CLAD
COIL SPRING: TEMPERED STEEL WIRE
BALL- TEMPERED CARBON STEEL
TERMINAL BOARD: PHENOLIC, UL94HB
TERMINAL SEAL: EPOXY

ELECTRICAL:
CONTACT RATING: 250 MILLIAMPS@125V AC
CONTACT RESISTANCE: 30 MILLIOHMS MAX (INITIAL),
60 MILLIOHMS AFTER TEST
INSULATION RESISTANCE: 500 MEGOHMS MIN AT 500V DC
DIELECTRIC STRENGTH: 500 VAC RMS AT SEA LEVEL
LIFE EXPECTANCY: 10,000 CYCLES MIN. NO LOAD

MECHANICAL:
ACTUATION FORCE: 250 +150/-100 GRAMS
TRAVEL: .098 (2.49MM)

ENVIRONMENTAL:
OPERATING TEMPERATURE: -10°C TO +60°C
STORAGE TEMPERATURE: -10°C TO +60°C
RESISTANCE TO SOLDER HEAT: 260°C FOR 10 SEC PER 109-202, COND. B
SOLDERABILITY: PER EIA-364-56A, PROCEDURE 3, COND. B

- NOTES:
- ALL MATERIALS AND FINISHES SHALL COMPLY WITH EU DIRECTIVE 2002/95/EC OF 27JAN2003 (ROHS)
 - ALL PERFORMANCE SPECIFICATIONS WERE TESTED IN ACCORDANCE WITH JIS-C-5441 UNLESS OTHERWISE STATED.

EXAMPLES: MIN-MAX
TRAVEL OF SWITCH

STS 260PC (DP6T)	23.00 [.906]	17.50 [.689]	6 PLCS
STS 250PC (DP5T)	20.50 [.807]	15.00 [.591]	5 PLCS
STS 240PC (DP4T)	18.00 [.709]	12.50 [.492]	4 PLCS
STS 230PC (DP3T)	15.50 [.610]	10.00 [.394]	3 PLCS
STS 220PC (DP2T)	13.00 [.512]	7.50 [.295]	2.50 [.098]
PART IDENTIFICATION	A DIM	B DIM	X PLC

6	17.50 [.689]	23.00 [.906]	DP6T	STS260PC04	1825163-5
5	15.00 [.591]	20.50 [.807]	DP5T	STS250PC04	1825163-4
4	12.50 [.492]	18.00 [.709]	DP4T	STS240PC04	1825163-3
3	10.00 [.394]	15.50 [.610]	DP3T	STS230PC04	1825163-2
2	7.50 [.295]	13.00 [.512]	DPDT	STS220PC04	1825163-1
X PLC	DIM B	DIM A	FUNCTION	T&B P/N	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN B.S.VISWESWARA 31MAR05		TE Connectivity	
DIMENSIONS: mm [INCHES]		CHK M S SARVER		NAME	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD M S SARVER		PRODUCT SPEC	
0 PLC ± -		APPLICATION SPEC		SIZE CAGE CODE DRAWING NO	
1 PLC ± -		WEIGHT -		RESTRICTED TO	
2 PLC ± .008(0.20)		CUSTOMER DRAWING		SCALE 2:1 SHEET 1 OF 2 REV A3	
3 PLC ± -					
4 PLC ± -					
ANGLES ± 1°					
FINISH -					

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
AD	00						
			-	SEE SHEET 1	-	-	-

PART NUMBER




POSITION

BOTTOM VIEW

FUNCTION DIAGRAM




-1

2








-2

3









-3

4










-4

5



-5

6



THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm [INCHES]

MATERIAL
-

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± -
1 PLC ± -
2 PLC ± .008(0.20)
3 PLC ± -
4 PLC ± -
ANGLES ± 1°
FINISH
-

DWN
B.S.VISWESWARA
CHK
M S SARVER
APVD
M S SARVER
PRODUCT SPEC
APPLICATION SPEC
WEIGHT
-

31MAR05

TE Connectivity

NAME
SWITCH-SLIDE (DP*T)
P/N STS2*0PC

SIZE
A2

CAGE CODE
00779

DRAWING NO
C=1825163

RESTRICTED TO
-

CUSTOMER DRAWING

SCALE
2:1

SHEET
2 OF 2

REV
A3

1471-9 (3/11)

1825163

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9