



### Main

|                              |                                                             |
|------------------------------|-------------------------------------------------------------|
| Range of product             | Square D Pumptrol                                           |
| Pressure sensor name         | 9013GH                                                      |
| Pressure sensor size         | 200 psi (40...170 psi)                                      |
| Value of setting             | 110...125 psi                                               |
| Electrical circuit type      | Power circuit                                               |
| Product specific application | Control electrically driven water pumps and air compressors |
| Quantity per set             | 1                                                           |
| Type of packing              | Individual                                                  |

### Complementary

|                                     |                                                                                                                                                                                                                                                                                                                                                                               |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Pressure sensor type                | Electromechanical pressure switch                                                                                                                                                                                                                                                                                                                                             |
| Controlled fluid                    | Air (-22...257 °F)<br>Fresh water (-22...257 °F)                                                                                                                                                                                                                                                                                                                              |
| Adjustable range on rising pressure | 65...200 psi                                                                                                                                                                                                                                                                                                                                                                  |
| Approximate adjustable differential | 20...40 psi                                                                                                                                                                                                                                                                                                                                                                   |
| Destruction pressure                | 300 psi                                                                                                                                                                                                                                                                                                                                                                       |
| Pressure actuator                   | Diaphragm                                                                                                                                                                                                                                                                                                                                                                     |
| Pressure switch type of operation   | Regulation between 2 thresholds                                                                                                                                                                                                                                                                                                                                               |
| Scale type                          | Adjustable differential                                                                                                                                                                                                                                                                                                                                                       |
| Setting                             | Internal                                                                                                                                                                                                                                                                                                                                                                      |
| Local display                       | Without                                                                                                                                                                                                                                                                                                                                                                       |
| Contacts type and composition       | 2 NC, snap action, DPST-DB, Form YY                                                                                                                                                                                                                                                                                                                                           |
| Cable entry number                  | 3 knock-outs for 1/2" conduit UL 508                                                                                                                                                                                                                                                                                                                                          |
| Electrical connection               | Screw-clamp terminals, clamping capacity: 10 AWG<br>Screw-clamp terminals, clamping capacity: 5.261 mm <sup>2</sup>                                                                                                                                                                                                                                                           |
| Fluid connection type               | 0.25 inch NPSF internal conforming to UL 508                                                                                                                                                                                                                                                                                                                                  |
| Short-circuit protection            | 20 A by cartridge fuse, type gG                                                                                                                                                                                                                                                                                                                                               |
| Materials in contact with fluid     | Zinc plated steel or equivalent flange<br>Nitrile (Buna-N) or equivalent rubber diaphragm                                                                                                                                                                                                                                                                                     |
| Material                            | Polypropylene cover<br>Noryl thermoplastic resin or equivalent cover                                                                                                                                                                                                                                                                                                          |
| Operating position                  | Any position                                                                                                                                                                                                                                                                                                                                                                  |
| Motor power kW                      | 1.5 kW (2 hp) at 115 V AC, 1 phase<br>2.2 kW (3 hp) at 115 V AC, 3 phases<br>2.2 kW (3 hp) at 230 V AC, 1 phase<br>0.75 kW (1 hp) at 115 V DC<br>0.75 kW (1 hp) at 230 V DC<br>3.75 kW (5 hp) at 230 V AC, 3 phases<br>3.7 kW (5 hp) at 460 V AC, 1 phase<br>3.7 kW (5 hp) at 460 V AC, 3 phases<br>3.7 kW (5 hp) at 575 V AC, 1 phase<br>3.7 kW (5 hp) at 575 V AC, 3 phases |
| Electrical durability               | 100000 cycles at 10 cyc/mn                                                                                                                                                                                                                                                                                                                                                    |
| Mechanical durability               | 300000 cycles                                                                                                                                                                                                                                                                                                                                                                 |
| Terminal block type                 | 4 terminals                                                                                                                                                                                                                                                                                                                                                                   |
| Operating rate                      | 10 cyc/mn                                                                                                                                                                                                                                                                                                                                                                     |
| [Ui] rated insulation voltage       | 575 V conforming to UL 508                                                                                                                                                                                                                                                                                                                                                    |
| Product weight                      | 2.25 lb(US)                                                                                                                                                                                                                                                                                                                                                                   |
| Repeat accuracy                     | +/- 3 %                                                                                                                                                                                                                                                                                                                                                                       |
| Terminals description ISO n°1       | L1-T1<br>L2-T2                                                                                                                                                                                                                                                                                                                                                                |
| Width                               | 4.19 in                                                                                                                                                                                                                                                                                                                                                                       |

|                      |                              |
|----------------------|------------------------------|
| Height               | 5.4 in                       |
| Depth                | 3.88 in                      |
| Factory modification | 2-way pressure release valve |

## Environment

|                                       |                                           |
|---------------------------------------|-------------------------------------------|
| standards                             | CE<br>UL 508<br>NSF ANSI 372              |
| ambient air temperature for operation | -33...257 °F                              |
| ambient air temperature for storage   | -33...257 °F                              |
| protective treatment                  | None                                      |
| NEMA degree of protection             | NEMA 1 conforming to UL 50                |
| IP degree of protection               | IP20 conforming to IEC 60529              |
| product certifications                | UL listed file E12158<br>CSA file LR25490 |

## Offer Sustainability

|                                                                                                                                  |                                                                                                                                  |
|----------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Not Green Premium product                                                                                                        | Not Green Premium product                                                                                                        |
| Will not be Compliant                                                                                                            | Will not be Compliant                                                                                                            |
| Reference contains SVHC above the threshold - go to CaP for more details                                                         | Reference contains SVHC above the threshold                                                                                      |
| Available                                                                                                                        | Available                                                                                                                        |
| Available                                                                                                                        | Available                                                                                                                        |
| WARNING: This product can expose you to chemicals including:                                                                     | WARNING: This product can expose you to chemicals including:                                                                     |
| Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. | Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. |
| Di-isodecyl phthalate (DIDP) which is known to the State of California to cause birth defects or other reproductive harm.        | Di-isodecyl phthalate (DIDP) which is known to the State of California to cause birth defects or other reproductive harm.        |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                                    | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                                    |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9