

Raychem S200 Shield Terminators

High-Performance, High-Temperature Cable Terminators



Heat-Shrinkable Sleeve for Fast, Reliable, Economical Cable Shield Termination and Grounding

An important extension of the Raychem SolderSleeve family, S200 shield termination devices were developed specifically to address the need for high-temperature connecting, insulating, and sealing for applications in the aerospace and defense industry.



LET'S CONNECT

We make it easy to connect with our experts and are ready to provide all the support you need. Just call your local support number or visit te.com to chat with a Product Information Specialist.

Technical Support

te.com/support-center

North America	+1 800 522 6752	Asia Pacific	+86 400 820 6015
North America (Toll)	+1 717 986 7777	Japan	+81 044 844 8180
EMEA/South Africa	+800 0440 5100	Australia	+61 2 9554 2695
EMEA (Toll)	+31 73 624 6999	New Zealand	+64 (0) 9 634 4580
India (Toll-Free)	+800 440 5100		

te.com/ADM

AMP, AGASTAT, CII, DEUTSCH, HARTMAN, KILOVAC, LL ROWE, MICRODOT, NANONICS, POLAMCO, Raychem, SEACON, SolderSleeve, TE, TE Connectivity and the TE connectivity (logo) are trademarks of the TE Connectivity Corporation. Other products, logos, and company names mentioned herein may be trademarks of their respective owners.

While TE Connectivity (TE) has made every reasonable effort to ensure the accuracy of the information herein, nothing herein constitutes any guarantee that such information is error-free, or any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. The TE entity issuing this publication reserves the right to make any adjustments to the information contained herein at any time without notice. All implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose are expressly disclaimed. The dimensions herein are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice.

Consult TE for the latest dimensions and design specifications.

© 2017 TE Connectivity Corporation All Rights Reserved.

1-1773851-1 07/17

AEROSPACE, DEFENSE & MARINE /// Raychem S200 SHIELD TERMINATORS



Raychem S200 Shield Terminators

Fast, Easy Shield Termination and Grounding to 200°C

AEROSPACE, DEFENSE & MARINE /// Raychem S200 SHIELD TERMINATORS



Wide Selection

Offered in various sizes and ground lead configurations, our S200 shield termination devices provide environmentally protected shield termination on cables with a minimum temperature rating of 150°C, and silver or nickel-plated shields. They are also available with bi-alloy or thermochromic indicators

Fast Installation and Lower Costs

Convenient to use, the one-piece design of S200 shield termination devices help ensure reliable environmental protection and greatly simplified installation for a lower total installed cost.

MATERIALS

- **Solder:** Tin 96%/Silver 4% bi-alloy solder
- **Tubing:** Heat-shrinkable modified fluoropolymer
- **Inserts:** Thermoplastic fluoropolymer

STANDARDS AND SPECIFICATIONS

- **Industry Standards:**
SAE-AMS-DTL-23053/13 (applies to heat-shrinkable insulation sleeve only)
SAE-AS83519 (modified for 200°C applications)
EU RoHS/ELV compliant
- **TE Instruction Sheet:** RCPS-100-71
- **TE Qualification and Test Report:** Available on request

MECHANICAL/ENVIRONMENTAL

- **Operating Temperature:** 150°C to 200°C
- **Durability:** Heat-shrinkable sleeve adheres and seals to provide a completely soldered, strain-relieved termination

TE Components . . . TE Technology . . . TE Know-how . . .

AMP | AGASTAT | CII | HARTMAN | KILOVAC | MICRODOT | NANONICS | POLAMCO | Raychem | Rochester | DEUTSCH
SEACON Phoenix | LL ROWE | Phoenix Optix | AFP | SEACON

Empower Engineers to Solve Problems, Moving the World Forward.



ORDERING INFORMATION (TC indicates that this part has a thermochromic indicator)

Without ground lead

Jacket OD (mm)	Shield (mm)	Product Description	Raychem Part Number	SAE AS83519
1.90	0.90	S200-1-00	F92583-000	
1.90	0.90	S200-1-00-TC	CN5417-000	
2.67	1.40	S200-2-00	F94898-000	
2.67	1.40	S200-2-00-TC	CN5418-000	
4.32	2.15	S200-3-00	A65903-000	
4.32	2.15	S200-3-00-TC	CN5419-000	
5.97	3.30	S200-4-00	E32454-000	
5.97	3.30	S200-4-00-TC	CN5420-000	
6.98	4.30	S200-5-00	D12074-000	
6.98	4.30	S200-5-00-TC	CN5421-000	

With pre-installed braid: Nickel-plated copper strands in accordance to AA59569F36N0031. (6 Inches)

Jacket OD (mm)	Shield (mm)	Product Description	Raychem Part Number	SAE AS83519
1.90	0.90	S200-1-01	CS5526-000	M83519/5-1
2.67	1.40	S200-2-01	D08259-000	M83519/5-2
4.32	2.15	S200-3-01	A77145-000	M83519/5-3
5.97	3.30	S200-4-01	F26506-000	M83519/5-4
6.98	4.30	S200-5-01	A18826-000	M83519/5-5

With pre-installed braid: Ni-plated copper strands per ASTM B355, Class 4. CMA = 1200. (6 Inches)

Jacket OD (mm)	Shield (mm)	Product Description	Raychem Part Number	SAE AS83519
1.90	0.90	S200-1-9020	CJ1037-000	M83519/5-11
1.90	0.90	S200-1-9020-TC	CP7589-000	M83519/5-16
2.67	1.40	S200-2-9020	CJ1039-000	M83519/5-12
2.67	1.40	S200-2-9020-TC	CP4262-000	M83519/5-17
4.32	2.15	S200-3-9020	CJ1041-000	M83519/5-13
4.32	2.15	S200-3-9020-TC	CP6063-000	M83519/5-18
5.97	3.30	S200-4-9020	CJ1042-000	M83519/5-14
5.97	3.30	S200-4-9020-TC	CP6893-000	M83519/5-19
6.98	4.30	S200-5-9020	CJ1043-000	M83519/5-15
6.98	4.30	S200-5-9020-TC	CP7313-000	M83519/5-20

With pre-installed braid: Ni-plated copper strands per ASTM B355, Class 4. CMA = 1800. (6 Inches)

Jacket OD (mm)	Shield (mm)	Product Description	Raychem Part Number	SAE AS83519
1.90	0.90	S200-1-9030	CA7639-000	
2.67	1.40	S200-2-9030	CA7640-000	
4.32	2.15	S200-3-9030	CA7641-000	
5.97	3.30	S200-4-9030	CA7642-000	
6.98	4.30	S200-5-9030	CA7643-000	
6.98	4.30	S200-5-9030-TC	CP7417-000	



With pre-installed braid: High nickel-plated copper strands per ASTM-B355 Class 7. CMA = 640. (10 Inches)

Jacket OD (mm)	Shield (mm)	Product Description	Raychem Part Number	SAE AS83519
1.90	0.90	S200-1-01-100HN	D89883-000	
2.67	1.40	S200-2-01-100HN	A87947-000	
4.30	2.15	S200-3-01-100HN	A59779-000	
5.95	3.30	S200-4-01-100HN	C69495-000	
6.90	4.30	S200-5-01-100HN	D92195-000	

With pre-installed braid: Stranded nickel-plated copper wire in accordance with SAE-AS22759/41.

Jacket OD (mm)	Shield (mm)	Product Description	Raychem Part Number	SAE AS83519
1.90	0.90	S200-1-55-22-9	EH1934-000	
2.67	1.40	S200-2-55-22-9	EH1935-000	
4.30	2.15	S200-3-55-22-9	EH1936-000	
5.95	3.30	S200-4-55-22-9	EH1938-000	
6.90	4.30	S200-5-55-22-9	EH1939-000	

With pre-installed braid: Stranded nickel-plated copper wire in accordance with SAE-AS22759/41.

Jacket OD (mm)	Shield (mm)	Product Description	Raychem Part Number	SAE AS83519
1.90	0.90	S200-1-55-20-9	EH1940-000	
2.67	1.40	S200-2-55-20-9	EH1941-000	
4.30	2.15	S200-3-55-20-9	EH1942-000	
5.95	3.30	S200-4-55-20-9	EH1943-000	
6.90	4.30	S200-5-55-20-9	EH1944-000	

With pre-installed braid: Stranded nickel-plated copper wire in accordance with SAE-AS22759/41.

Jacket OD (mm)	Shield (mm)	Product Description	Raychem Part Number	SAE AS83519
1.90	0.90	S200-1-55-18-9	EH1945-000	
2.67	1.40	S200-2-55-18-9	EH1946-000	
4.30	2.15	S200-3-55-18-9	EH1948-000	
5.95	3.30	S200-4-55-18-9	EH1949-000	
6.90	4.30	S200-5-55-18-9	EH1950-000	

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9