

# 33502A 2-Channel 50 Vpp Isolated Amplifier



## Introduction

The Keysight Technologies, Inc. 33502A is a dual-channel, high voltage output amplifier. It has an isolated analog front end with up to 50 Vpp ( $\pm 25$  V) output voltage range. It is also a very low-distortion amplifier with  $< 0.01\%$  @ 10 kHz and 40 Vpp. The 33502A is designed to work as a companion for function generators to offer low-distortion, higher voltage outputs.

The 33502A has a fully isolated front end, which offers superior 5X voltage amplification to other amplifiers.

You can independently configure input coupling (AC|DC) and input impedance ( $50 \Omega | 1 M\Omega$ ) to match your circuit. The input path can also be switched from amplified to direct (unamplified) without removing or connecting cables.

The 33502A, in a 2 unit, half-rack mechanical form factor, fits well on both your bench and in your test system. It also is configured with LAN (LXI Class-C compliant) and USB interfaces to meet your computer IO needs.

The 33502A provides both a programmable interface and a softkey-driven front panel for flexibility in configuring.

The 33502A is compatible with existing Keysight function/arbitrary waveform generators including the 33120A, 33210A, 33220A, and 33250A. It can also be used to amplify signals from non-Keysight function and arbitrary waveform generators.

## Features

- Full-power BW 100 kHz @ 50 Vpp
- Small-signal BW  $> 300$  kHz
- Slew Rate  $20 V/\mu s$  min.
- THD+N  $< 0.01\%$  @ 10 kHz, 40 Vpp.
- Output drive 200 mA max.
- Isolation floats  $\pm 42$  Vpk to earth

Table 1.

Feature	Characteristic
<b>General</b>	
Number of channels	2
Channel to channel ground connection	Not connected in BYPASS ON. Connected with both channels OFF or in Gain of 5x
Floating Voltage	±42 Vpk to earth
<b>Input configuration &amp; specification</b>	
<b>Input coupling</b>	
AC coupling	Programmable
DC coupling	Default, programmable
<b>Input Impedance</b>	
1 MΩ	Default, programmable
50 Ω	Programmable
<b>Input voltage range</b>	
Maximum voltage range	±5 Vpk for gain of 5x, ±30 Vpk for bypass
Damage level	±10 Vpk for 50 Ω input ±35 Vpk for 1 MΩ input
Input path	Programmable gain of 5x, bypass (1x), or off state
Input gain 5X	5X, Fixed, Non-inverting
Gain accuracy <sup>2</sup>	±0.1% @ 1 KHz
Flatness DC coupling <sup>1</sup>	0.1% : dc - 10 KHz 1% : dc - 40 KHz 5% : dc - 100 KHz
Flatness AC coupling <sup>1</sup>	0.1% : 30 Hz - 10 KHz 1% : 10 Hz - 40 KHz 5% : 3 Hz - 100 KHz
Small signal bandwidth <sup>1</sup>	> 300 KHz (-3 db)
Full power bandwidth <sup>1</sup>	100 KHz @ 50 Vpp output
<b>Input bypass</b>	
Bandwidth for 50 Ω system	> 300 MHz (-3 db)
Maximum current	0.2 Apk
<b>Noise</b>	
Input referred noise	< 40 nV/ rt-Hz @ 1 kHz
<b>Output configuration &amp; specification</b>	
Output current	200 mA. (150 mA for continuous output from -8 V to +8 V)
DC output resistance	< 2 Ω
Max output level <sup>1</sup>	±25 Vpk
Output DC offset	<1 0 mV
Output slew rate <sup>1</sup>	> 20 V/us
THD + N <sup>1</sup>	< 0.01% @ 10kHz, 40 Vpp
Aberrations <sup>1</sup>	<5% for waveforms with <3V input step or non slewing output
Transition time <sup>1</sup> (Final value ±1% of step size)	2.5uSec+ 50nSec/volt of output step
Channel to channel isolation for gains of 5x	> 75dB
Capacitive Load for no oscillation	< 1 nF
Output protection	Continuous short circuit protection Thermal overload shutdown. Over temperature status flag.

1. For all loads &gt; 250 ohms and &lt; 400 pF of capacitance

2. Measured with ≥ 1 Mohm load and 1 Mohm input selection.

Table 2.

<b>General characteristics</b>	
Power supply	100 V/120 V/220 V/240 V ±10%
Power line frequency	50–60 Hz ±10%, 400 Hz ±10%.
Power consumption	100 VA peak (typical value depends on configuration and load)
Operating environment	Full accuracy for 0 to 55 °C Full accuracy to 80% R.H. at 40 °C Non-condensing
Storage temperature	-40 to 70 °C
Operating altitude	Up to 3000 m
Bench Dimensions (W x H x D)	261.2 mm x 103.8 mm x 303.2 mm
Weight	3.1 kg (6.8 lbs)
Safety	Complies with European Low Voltage Directive and carries the CE-marking Conforms to UL 61010-1, CSA C22.2 61010-1, and IEC 61010-1:2001
EMC	Complies with European EMC Directive for test and measurement products. - IEC/EN 61326-1 - CISPR Pub 11 Group 1, class A - AS/NZS CISPR 11 - ICES/NMB-001
	Complies with Australian standard and carries C-Tick mark This ISM device complies with Canadian ICES-001. Cet appareil ISM est conforme à la norme NMB-001 du Canada
Acoustic noise	Normal operating mode: SPL 35db(A)
Display	4.3" Color TFT WQVGA (480x272), LED backlight
Remote interfaces	10/100Mbit LAN USB 2.0 Standard
Language	SCPI – 1994.0, IEEE-488.2
LXI compliance	LXI Class C, Version 1.0
Number of channels	2
Channel to channel ground connection	Not connected in BYPASS ON. Connected with both channels OFF or in Gain of 5x
Floating Voltage	±42 Vpk to earth

## Accessories

<b>Accessories available</b>	
1CM124A	Rackmount kit
1CM107A	2U dual flange kit
34194A	Dual lock link kit

Learn more at: [www.keysight.com](http://www.keysight.com)

For more information on Keysight Technologies' products, applications or services,  
please contact your local Keysight office. The complete list is available at:

[www.keysight.com/find/contactus](http://www.keysight.com/find/contactus)



**Данный компонент на территории Российской Федерации****Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибуторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ Р В 0015-002 и ЭС РД 009

**Офис по работе с юридическими лицами:**

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru  
moschip.ru\_4

moschip.ru\_6  
moschip.ru\_9