

PCIE-1813

38.4 kS/s, 26-Bit, 4-Ch, Simultaneous Sampling, Universal Bridge Input, Multifunction PCI Express Card

NEW



FCC CE RoHS

Features

- 4 simultaneous sampling analog inputs, up to 38.4 kS/s, 26-bit resolution
- Full, half, and quarter-bridge sensor input with built-in anti-aliasing filter
- 2 analog outputs, up to 3 MS/s, 16-bit resolution
- Four 32-bit programmable encoder counters/ timers/ encoder counters
- 32 programmable DI/Os with interrupt functions
- Board ID switch
- Full automatic calibration

Introduction

PCIE-1813 is a 26-bit high-resolution multifunction data acquisition PCI Express card specifically designed for bridge sensor inputs, such as strain gauges, load cells, pressure sensors, and torque sensors. PCIE-1813 also features 2-ch, 16-bit analog outputs with waveform generation capability and supports simultaneous waveform generation and analog input functions.

Specifications

Analog Input Overview

- Channels 4
- Resolution 26 bits
- Sample Rate 38.4 kS/s max. simultaneous

Voltage Input

- Input Ranges $\pm 10\text{ V}$, $\pm 5\text{ V}$, $\pm 2.5\text{ V}$, $\pm 1.25\text{ V}$, $\pm 625\text{ mV}$, $\pm 312.5\text{ mV}$
- Accuracy $\pm 0.01\%$ of FSR

Bridge Input

- Input Ranges $\pm 31.25\text{ mV/V}$, $\pm 62.5\text{ mV/V}$, $\pm 125\text{ mV/V}$, $\pm 250\text{ mV/V}$, $\pm 500\text{ mV/V}$, and $\pm 1\text{ V/V}$
- Bridge Mode Full, half, quarter
- Bridge Resistance 120 Ω , 350 Ω , 1 k Ω
- Shunt Calibration 33.333 k Ω , 50 k Ω , 100 k Ω
- Excitation Voltage 0 ~ 10 V
- Remote Sensing Yes

Analog Output

- Channels 2
- Resolution 16 bits
- Output Rate 3 MSPS max.
- Output Range Software programmable

Internal Reference	Unipolar	0 ~ 5 V, 0 ~ 10 V
	Bipolar	-5 V ~ 5 V, -10 V ~ 10 V
External Reference		0 ~ +x V @ -x V (-10 \leq x \leq 10)

- Slew Rate 20 V/ μ s
- Driving Capability 5 mA
- Operation Mode Static update, waveform generation
- Accuracy $\pm 0.01\%$ of FSR

Analog Trigger

- Channels 2
- Resolution 16 bits
- Input Range -10 V ~ +10 V
- Hysteresis Yes. Hysteresis range is configurable
- Trigger Edge Rising edge or falling edge, selected by software

Digital Trigger

- Channels 2

- Input Voltage Logic 0: 1.5 V max.
Logic 1: 3.5 V min.
- Trigger Edge Rising edge or falling edge, selected by software

Digital I/O

- Channels 32 (shared)
- Input Voltage Logic 0: 1.5 V max.
Logic 1: 3.5 V min.
- Output Voltage Low 0.5 V max. @ +20 mA (sink)
High 4.5 V min. @ -20 mA (source)

Counter/ Timer/ Encoder Counter

- Channels 4
- Resolution 32 bits
- Input/Output Voltage Same as that for digital I/O
- Max. Input Frequency 10 MHz
- Counter/Timer Functions Frequency measurement, pulse width measurement, pulse output, PWM output
- Encoder Functions Quadrature (X1, X2, X4), dual pulse (CW/CCW), signed pulse (OUT/DIR)

General

- Form Factor PCI Express x1
- I/O Connector 100-pin SCSI female ribbon-type connector
- Dimensions (L x W) 167 x 100 mm (6.6" x 3.9")
- Operating Temperature 0 ~ 60 $^{\circ}\text{C}$ (32 ~ 140 $^{\circ}\text{F}$) (refer to IEC 68-2-1, 2)
- Storage Temperature -40 ~ 70 $^{\circ}\text{C}$ (-40 ~ 158 $^{\circ}\text{F}$)
- Storage Humidity 5 ~ 95% RH non-condensing (refer to IEC 68-2-3)
- Board ID TM switch

Ordering Information

- PCIE-1813-AE 38.4 kS/s, 26-bit, 4-ch, simultaneous sampling, universal bridge input, multifunction PCI Express card

Accessories

- PCL-101100R-1E 100-pin SCSI shielded cable, 1 m
- PCL-101100R-2E 100-pin SCSI shielded cable, 2 m
- ADAM-39100-BE 100-pin DIN rail SCSI wiring board
- PCLD-8810-AE Low-Pass Active Filter Board
- PCLD-8813-AE 6Advanced Signal Conditioning Board for PCIE-1812/PCIE-1813
- PCLD-8811-AE Low-Pass Active Filter Board

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9