

## 1808A Coax - High-Flex S-Video Cable



For more Information  
please call

1-800-Belden1



### Description:

30 AWG stranded (7x38) .012" tinned copper conductors, foam HDPE insulation, tinned copper serve shield (90% coverage), PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

##### AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
2	30	7x38	TC - Tinned Copper	.013

Total Number of Conductors: 2

#### Insulation

##### Insulation Material:

Insulation Material	Dia. (in.)
FHDPE - Foam High Density Polyethylene	.058

#### Inner Shield

##### Inner Shield Material:

Type	Inner Shield Material	Coverage (%)
Spiral Serve	TC - Tinned Copper	90

#### Inner Jacket

##### Inner Jacket Material:

Inner Jacket Material	Nom. Dia. (in.)
PVC - Polyvinyl Chloride	.100

##### Inner Jacket Color Code Chart:

Number	Color
1	Black
2	Yellow

#### Outer Jacket

##### Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

#### Overall Cable

Overall Nominal Diameter: 0.255 in.

### Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +75°C

UL Temperature Rating: 60°C

Non-UL Temperature Rating: 75°C

Bulk Cable Weight: 29 lbs/1000 ft.

Max. Recommended Pulling Tension: 11.700 lbs.

Min. Bend Radius/Minor Axis: 1 in.

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

AWM Specification:	UL Style 1354
EU CE Mark:	No
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

### Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

Impedance (Ohm)
75

### Nom. Inductance:

Inductance (µH/ft)
0.097

### Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)
17.3

### Nominal Velocity of Propagation:

VP (%)
78

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
100.0

### Nom. Inner Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
7.5

### Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1	.6
5	1.4
10	2.1
30	3.8
50	5.1
100	7.6
200	11.3
400	16.9
700	23.3
900	26.9
1000	28.6

### Max. Operating Voltage - UL:

<b>Voltage</b>
30 V RMS

**Max. Operating Voltage - Non-UL:**

<b>Voltage</b>
300 V RMS

## Notes (Overall)

**Notes:** Inner Jacket Separator Material: Paper Tape.

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1808A B59U1000	1,000 FT	31.000 LB	BLACK, MATTE		2 #30 FHDPE SRV PVC PVC
1808A B59U500	500 FT	16.500 LB	BLACK, MATTE		2 #30 FHDPE SRV PVC PVC
1808A B591000	1,000 FT	33.000 LB	BLACK, MATTE	C	2 #30 FHDPE SRV PVC PVC
1808A B59500	500 FT	14.500 LB	BLACK, MATTE	C	2 #30 FHDPE SRV PVC PVC

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 2    Revision Date: 04-11-2008

© 2012 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9