

Scotch® Barricade Tapes 300 Series

Data Sheet

December 2013

Description	Scotch® Barricade Tapes 300 Series are nominal 2-mil, 3-mil and 4-mil tapes, without adhesive, made with polyethylene film. As a product for displaying warning information, they shall be opaque, orange, yellow or red and printed with the appropriate words.																
Agency Approvals & Self Certifications	Meets the requirements of: RoHS 2011/695/EC "RoHS 2011/65/EU" means that the product or part does not contain any of the substances in excess of the maximum concentration values ("MCVs") in EU RoHS Directive 2011/65/EU. The MCVs are by weight in homogeneous materials. This information represents 3M's knowledge and belief, which may be based in whole or in part on information provided by third party suppliers to 3M.																
Typical Properties	Not for specifications. Values are typical, not to be considered minimum or maximum. Properties measured at room temperature 73°F (23°C) unless otherwise stated.																
	<table><thead><tr><th>Physical Property (Test Method)</th><th>Typical Value US units (metric)</th></tr></thead><tbody><tr><td>Color, Width, Thickness</td><td>Variable (see availability chart)</td></tr><tr><td>Adhesive</td><td>None</td></tr><tr><td>Density (ASTM D-1505)</td><td>0.922 g/cc</td></tr><tr><td>Dart Impact Strength (ASTM D-1709)</td><td>140 gram/mil</td></tr><tr><td>Secant Modulus (ASTM D-882)</td><td>MD 29,000 psi / TM 33,000 psi</td></tr><tr><td>Tensile Strength at Break (ASTM D-882)</td><td>MD 4,400 psi / TD 3,900 psi</td></tr><tr><td>Elongation (% at break) (ASTM D-882)</td><td>MD 400% / TD 500%</td></tr></tbody></table>	Physical Property (Test Method)	Typical Value US units (metric)	Color, Width, Thickness	Variable (see availability chart)	Adhesive	None	Density (ASTM D-1505)	0.922 g/cc	Dart Impact Strength (ASTM D-1709)	140 gram/mil	Secant Modulus (ASTM D-882)	MD 29,000 psi / TM 33,000 psi	Tensile Strength at Break (ASTM D-882)	MD 4,400 psi / TD 3,900 psi	Elongation (% at break) (ASTM D-882)	MD 400% / TD 500%
Physical Property (Test Method)	Typical Value US units (metric)																
Color, Width, Thickness	Variable (see availability chart)																
Adhesive	None																
Density (ASTM D-1505)	0.922 g/cc																
Dart Impact Strength (ASTM D-1709)	140 gram/mil																
Secant Modulus (ASTM D-882)	MD 29,000 psi / TM 33,000 psi																
Tensile Strength at Break (ASTM D-882)	MD 4,400 psi / TD 3,900 psi																
Elongation (% at break) (ASTM D-882)	MD 400% / TD 500%																
Specifications	<p>The tape shall be of good manufacturing quality in terms of appearance. It shall not gap or telescope more than 0.1 inches when stored at temperatures below 49°C. It must be flexible or not be stiff or brittle in applications ranging from below 0°C to about 38°C. The tape must be removable from the roll without difficulty.</p> <p>The tape shall be smooth, uniform, and free of defects and irregularities. The print shall be uniform, the lettering free of lumps, free of visibly large voids and foreign materials. The warning words shall be legible, correctly spelled and fully printed. The ink shall be dry, firmly bonded to the substrate, and not transferable to non-printed parts of the film.</p>																
Shelf Life & Storage	This product has a 5-year shelf life from date of manufacture when stored in a humidity controlled storage (10°C/50°F to 27°C/80°F and <75% relative humidity).																

Scotch® Barricade Tapes 300 Series

Availability

Please contact your local distributor; available from 3M.com/electrical [Where to Buy] or call 1-800-245-3573.

Product	Text	Length	Color	Thickness	Width
Scotch 300	CAUTION	1000 ft.	Yellow	2-mil	3 in.
Scotch 301		300 ft.			
Scotch 330	CAUTION		Yellow	3-mil	3 in.
Scotch 331	DANGER		Red	3-mil	3 in.
Scotch 333	CAUTION DO NOT ENTER		Yellow	3-mil	3 in.
Scotch 356		300 ft.			
Scotch 357	DANGER	1000 ft.	Red	2-mil	3 in.
Scotch 358	CAUTION HIGH VOLTAGE		Yellow	2-mil	3 in.
Scotch 361	CAUTION DO NOT ENTER				
Scotch 362	DANGER DO NOT ENTER	1000 ft.	Red	2-mil	3 in.
Scotch 374	CAUTION DO NOT ENTER	300 ft.	Yellow	2-mil	3 in.
Scotch 302		1000 ft.			
Scotch 303	CAUTION BURIED ELECTRIC LINE BELOW	300 ft.	Red	4-mil	3 in.
Scotch 363	CAUTION HIGH VOLTAGE CABLE BURIED BELOW	1000 ft.	Red	4-mil	3 in.
Scotch 364	CAUTION BURIED ELECTRIC LINE BELOW	1000 ft.	Yellow	4-mil	3 in.
Scotch 365	CAUTION BURIED FIBER OPTIC LINE BELOW				
Scotch 366	CAUTION BURIED CABLE TV LINE BELOW				
Scotch 367	CAUTION BURIED TELEPHONE LINE BELOW				
Scotch 368	CAUTION BURIED ELECTRIC LINE BELOW				
Scotch 369	CAUTION HIGH VOLTAGE CABLE BURIED BELOW	1000 ft.	Red	4-mil	6 in.
Scotch 370	CAUTION BURIED ELECTRIC LINE BELOW	1000 ft.	Yellow	4-mil	6 in.
Scotch 371	CAUTION BURIED FIBER OPTIC LINE BELOW	1000 ft.	Orange	4-mil	6 in.

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product, which are not contained in 3M's current publications, or any contrary statements contained on your purchase order, shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability

This product will be free from defects in material and manufacture at the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**

3M and Scotch are trademarks of 3M Company.



Electrical Markets Division

6801 River Place Boulevard
Austin, TX 78726-9000

800.245.3573 / 651.737.7222 (24 hours)
Fax: 800.245.0329
www.3m.com/electrical

Please recycle
© 3M 2013 All rights reserved
78-8125-9670-4 F

Данный компонент на территории Российской Федерации**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибуторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ Р В 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9