



## AMB-55, AMB-110 High Voltage Digital Megohmmeters – Insulation Resistance Testers

Amprobe Industrial High-Voltage Insulation Testers have all necessary features for advanced professional insulation diagnostics. Automated calculation of PI, DD and DAR, combined with a possibility to perform a step voltage test make these instruments suitable for the most demanding customers and applications. Large LCD display allows real time R(t) graphs to be displayed. Windows compatible PC Software and either RS232 or USB communications ports serve for connecting the instrument to the PC and management of the recorded test data.

### No hassle warranty

*No waiting.*

*No shipping  
charges.*



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)

- Test insulation of wires, cables, transformers, motors, surge arrestors and generators
- Selectable testing voltages - one testing instrument for low and high voltage systems:
  - AMB-55 from 250V to 5000V with 25V increments
  - AMB-110 from 500V to 10,000V with 25V increments
- Insulation resistance measurement up to 10TΩ
  - R(t) graph - Real time resistance against time graph plotting facility to graphically illustrate the response of a material to an applied test voltage
  - User selectable Programmable Timer (1s to 99 min)
  - Automatic discharge of test object after completion of measurement
  - Capacitance Measurement
- Diagnostic tools
  - Polarization index (PI)
  - Dielectric discharge (DD)
  - Dielectric Absorption Ratio (DAR) with automated resistance ranging (AR).
- Step voltage test - Insulation resistance will be measured at five different, equality sequenced test voltages for in-depth insulation system diagnostics

**AMB-55, AMB-110**  
**High Voltage Digital Megohmmeters – Insulation Resistance Testers**

- All parameters can be measured and displayed in one single measurement.
- High charging capacity - With 5 mA charging current insulation systems up to 50  $\mu$ F can be quickly charged and tested.
- High EM (noise) immunity - Built in noise rejection filters and shielded test leads supplied in a standard set make the instrument suitable for accurate insulation testing in environments with high EM interferences like HV switchyards or similar environments
- Handy, rugged carrying case
- Dual power source – receptacle or rechargeable batteries
- Built in internal memory storing 1000 measurements with time and date
- CAT IV 600V overvoltage category for industrial applications

**General Specifications**

Feature	AMB-55	AMB-110	Accuracy
Insulation Resistance	0 – 999 k $\Omega$ 1.00 – 9.99, 10.0 – 99.9, 100 – 999 M $\Omega$ 1.00 – 9.99, 10.0 – 99.9, 100 – 999 G $\Omega$ 1.00 – 10.00 T $\Omega$		$\pm$ (5% rdg + 3 dgts) below 1T $\Omega$ $\pm$ (15% rdg + 3 dgts) @ 1T $\Omega$ and above
DC Test Voltage and Step Voltage	250 V to 5 kV, steps by 25 V	500 V to 10 kV, steps by 25 V	
Display Range Test Voltage	0 – 5500V	0 – 9999V	$\pm$ (3% rdg + 3V)
		$\geq$ 10kV	$\pm$ (3% of reading)
Current Display Range	0.00 – 9.99, 10.0 – 99.9, 100 – 999 nA 1.00 – 9.99, 10.0 – 99.9, 100 – 999 $\mu$ A 1.00 – 5.5 mA		$\pm$ (5% rdg + 0.05 nA)
Dielectric Absorption Ratio (DAR)	0 – 99.9		$\pm$ (5% rdg + 2 dgts)
Polarization Index (PI)	0 – 99.9		$\pm$ (5% rdg + 2 dgts)
Dielectric Discharge Test (DD)	0 – 99.9		$\pm$ (5% rdg + 2 dgts)
Leakage Current Display Range	0 – 5.50 mA		$\pm$ (5% rdg + 2 dgts)
External Voltage Measurement	0 – 600V		$\pm$ (3% rdg + 4V) @ 45 to 65Hz and DC
Capacitance Measurement	0.0– 99.9, 100 – 999 nF 1.00 – 50.00 $\mu$ F		$\pm$ (5% rdg + 4 nF)
Discharging Resistance	300 k $\Omega$	425 k $\Omega$	$\pm$ 10%
Mains Power Supply	90 - 260VAC, 45 - 60 Hz, 60VA		
Battery Power Supply	6 x 1.2V Ni-MH, IEC LR14	6 x 1.2V Ni-MH, IEC LR20	
Dimension (w x h x d)	31 x 13 x 25 cm (12 x 5 x 10 in)	36 x 16 x 33 cm (14.2 x 6.3 x 13 in)	
Weight (without accessories, with batteries)	3 kg (6.6 lb)	5.5 kg (12.1 lb)	

**Amprobe® Test Tools**  
 website: [www.Amprobe.com](http://www.Amprobe.com)  
 email: [info@amprobe.com](mailto:info@amprobe.com)  
 Everett, WA 98203  
 Tel: 877-AMPROBE

**Amprobe® Test Tools Europe**  
 In den Engematten 14  
 79286 Glottertal, Germany  
 Tel.: +49 (0) 7684 8009 - 0

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9