(APV1122, APV1121S, APV2121S)

Photovoltaic MOSFET drivers of wide variation

Photovoltaic MOSFET Driver (APV1, 2)



RoHS compliant

FEATURES

1. High-speed switching
Since release time is Typ. 0.1 ms, the MOSFET can be turned off quickly in a urgent situation.

2. High insulation
DIP type: 5,000 Vrms
SOP type: 2,500 Vrms
SSOP type: 1,500 Vrms

3. Extensive product lineup
Products include SSOP, SOP4-pin and DIP6-pin.

TYPICAL APPLICATIONS

- Power supply (Vcc) for electronic circuits
- Driving MOSFET

TYPES

Output rating		Package	Part No.				Packing quantity	
			Through hole terminal	Surface-mount terminal				
					Tape and reel packing style			
Drop-out voltage (Typ.)	Short circuit current (Typ.)		Tube packing style	Tube packing style	Picked from 1/2/3-pin side*1	Picked from 4/5/6-pin side*2	Tube	Tape and reel
8.7V	14μA	DIP6-pin	APV1122	APV1122A	APV1122AX	APV1122AZ	1 tube contains 50 pcs. 1 batch contains 500 pcs.	1,000 pcs.
8.7V	14μA	SOP4-pin*3	—	APV1121S	APV1121SX	APV1121SZ	1 tube contains 100 pcs. 1 batch contains 2,000 pcs.	
8.2V	8μA		—	APV2121S	APV2121SX	APV2121SZ		
8.2V	8μA	SSOP*4	—	—	APV2111VY	APV2111VW	—	3,500 pcs.

Notes: *1 SOP type is picked from 1/2-pin side, SSOP type is picked from 1/4-pin side.
*2 SOP type is picked from 3/4-pin side, SSOP type is picked from 2/3-pin side.
*3 For space reasons, the two initial letters of the part number "AP", package (SOP) indicator "S" and the packing style indicator "X" or "Z" are not marked on the device. (Ex. the label for product number APV1121SX is V1121).
*4 Tape and reel package is the standard packing style. Packing quantity of 1,000 pieces is possible. Please contact our sales office.
For space reasons, the two initial letters of the part number "AP", package (SSOP) indicator "V" and the packing style are not marked on the device. (Ex. the label for product number APV2111VY is V2111).

RATING

1. Absolute maximum ratings (Ambient temperature: 25°C 77°F)

Item		Symbol	APV1122(A)	APV1121S	APV2121S	APV2111V	Remarks
Input	LED forward current	I_F	50mA				
	LED reverse voltage	V_R	5V				
	Peak forward current	I_{FP}	1A				f = 100 Hz, Duty Ratio = 0.1%
	Power dissipation	P_{in}	75mW				
I/O isolation voltage		V_{iso}	5,000Vrms	2,500Vrms	2,500Vrms	1,500Vrms	
Ambient temperature	Operating	T_{opr}	–40 to +85°C –40 to +185°F				(Non-icing at low temperatures)
	Storage	T_{stg}	–40 to +100°C –40 to +212°F				

© Panasonic Corporation 2017

2. Electrical characteristics (Ambient temperature: 25°C 77°F)

Item			Symbol	APV1122(A)	APV1121S	APV2121S	APV2111V	Condition
Input	LED operate current	Typical	I_{Fon}	0.6mA		0.85mA		V_{OC} = 5V
		Maximum		3mA				
	LED turn off current	Minimum	I_{Foff}	0.2mA				V_{OC} = 1V
		Typical		0.5mA		0.75mA		
	LED dropout voltage	Typical	V_F	1.15V				I_F = 10mA
		Maximum		1.5V				
Output	Drop-out voltage*	Minimum	V_{OC}	6V		5V		I_F = 10mA
		Typical		8.7V		8.2V		
	Short circuit current**	Minimum	I_{SC}	5μA		3μA		I_F = 10mA
		Typical		14μA		8μA		
Transfer characteristics	Turn on time***	Typical	T_{on}	0.4ms		0.8ms		I_F = 10mA, C_L = 1,000pF
	Turn off time***	Typical	T_{off}	0.1ms				I_F = 10mA, C_L = 1,000pF
	I/O capacitance	Typical	C_{iso}	0.8pF				V_B = 0V, f = 1MHz
		Maximum		1.5pF				
	Initial I/O isolation resistance	Minimum	R_{iso}	1,000MΩ				500V DC

*Drop-out voltage measurement circuit

APV1122(A)



APV1121S, APV2121S, APV2111V



**Short circuit current measurement circuit

APV1122(A)



APV1121S, APV2121S, APV2111V



***Turn on/Turn off time measurement circuit

APV1122(A)



APV1121S, APV2121S, APV2111V



***Turn on time



3. Recommended operating conditions (Ambient temperature: 25°C 77°F)

Please use under recommended operating conditions to obtain expected characteristics.

Item	Symbol	Min.	Max.	Unit
LED current	I_F	10	30	mA

■ **These products are not designed for automotive use.**
If you are considering to use these products for automotive applications, please contact your local Panasonic Corporation technical representative.

© Panasonic Corporation 2017

REFERENCE DATA

1. Drop-out voltage vs. ambient temperature characteristics
Input current: 10mA



2. Short circuit current vs. ambient temperature characteristics
Input current: 10mA



3. LED operate current vs. ambient temperature characteristics
Drop-out voltage: 5V



4. LED turn off current vs. ambient temperature characteristics
Drop-out voltage: 1V



5. LED dropout voltage vs. ambient temperature characteristics
LED forward current: 10 to 50mA



6. Turn on time vs. ambient temperature characteristics
LED forward current: 10mA
Load capacity: 1,000pF; output voltage: 5V



7. Turn off time vs. ambient temperature characteristics
LED forward current: 10mA
Load capacity: 1,000pF; output voltage: 1V



8. Turn on time vs. LED forward current characteristics
Load capacity: 1,000pF; output voltage: 5V



9. Turn off time vs. LED forward current characteristics
Load capacity: 1,000pF; output voltage: 1V



10. Drop-out voltage vs. LED forward current characteristics



11. Short circuit current vs. LED forward current characteristics



© Panasonic Corporation 2017

"PhotoMOS®", "PhotoMOS" and "PHOTOMOS" are registered trademarks of Panasonic Corporation.
*Recognized in Japan, the United States, all member states of European Union and other countries.

Please contact .....

Panasonic Corporation
Electromechanical Control Business Division
■ 1006, Oaza Kadoma, Kadoma-shi, Osaka 571-8506, Japan
industrial.panasonic.com/ac/e/

Panasonic®

©Panasonic Corporation 2017

ASCTB124E 201703-T

Specifications are subject to change without notice.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panasonic:
APV1121SX APV1121SZ APV1122AX APV1122AZ APV2111VW APV2111VY APV2121S APV2121SX APV2121SZ APV2111V

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9