


## TDR SERIES

### Relay Output, Recycling Time Delay Relay



8-PIN

### Wiring Diagram



Relay contacts are isolated

### Description

The TDR Series of time-delay relays are comprised of digital circuitry and an isolated, 10A relay output. The ON and OFF delays are selected by means of two, ten position binary switches, which allow the setting of the desired delay to be precise every time.

#### Operation (Recycling - ON Time First)

Upon application of input voltage, the green LED glows, the output relay is energized, the red LED glows, and the T1 ON time begins. At the end of the ON time, the output de-energizes, the red LED turns OFF and the T2, OFF time begins. At the end of the OFF time, the output relay energizes and the cycle repeats as long as input voltage is applied.

**Reset:** Removing input voltage resets the output and time delays, and returns the sequence to the first delay.

#### Operation (Recycling - OFF Time First)

Upon application of input voltage, the green LED glows, the T1 OFF time begins, the load is OFF. At the end of the OFF time, the T2 ON time begins, the load energizes, and the red LED glows. At the end of the ON time the load de-energizes and the red LED turns OFF. The cycle repeats until input voltage is removed.

**Reset:** Removing input voltage resets the output and the sequence to the OFF time.

### Features & Benefits

FEATURES	BENEFITS
<b>ON &amp; OFF time delay settings</b>	Independent adjustment allows for greater flexibility
<b>3 Time Ranges Available (0.1s to 2.8h)</b>	Makes it versatile for use in many applications
<b>Microcontroller based</b>	Repeat Accuracy +/- 0.1% or 20 ms, whichever is greater; Setting Accuracy +/- 2% or 50 ms, whichever is greater
<b>DIP switch adjustment</b>	Provides first time setting accuracy
<b>Isolated output contacts</b>	Allows control of loads for AC or DC voltages
<b>LED indication (select models)</b>	Provides visual indication of relay status

### Ordering Information

MODEL	INPUT VOLTAGE	LED	SEQUENCE	ON TIME (SEC)	OFF TIME (SEC)
TDR1A22	12VDC		ON time first	1-1023 in 1s increments	1-1023 in 1s increments
TDR2A23	24VAC	X	ON time first	1-1023 in 1s increments	10-10230 in 10s increments
TDR4A11	120VAC	X	ON time first	0.1-102.3 in 0.1s increments	0.1-102.3 in 0.1s increments
TDR4A12	120VAC	X	ON time first	0.1-102.3 in 0.1s increments	1-1023 in 1s increments
TDR4A13	120VAC	X	ON time first	0.1-102.3 in 0.1s increments	10-10230 in 10s increments
TDR4A22	120VAC	X	ON time first	1-1023 in 1s increments	1-1023 in 1s increments
TDR4A23	120VAC	X	ON time first	1-1023 in 1s increments	10-10230 in 10s increments
TDR4A33	120VAC	X	ON time first	10-10230 in 10s increments	10-10230 in 10s increments
TDR4B22	120VAC	X	OFF time first	1-1023 in 1s increments	1-1023 in 1s increments
TDR4B23	120VAC	X	OFF time first	1-1023 in 1s increments	10-10230 in 10s increments
TDR6A22	230VAC	X	ON time first	1-1023 in 1s increments	1-1023 in 1s increments

If you don't find the part you need, call us for a custom product 800-843-8848

# TDR SERIES

## Accessories



**BZ1 Front Panel Mount Kit**  
Provides an easy method of through-the-panel mounting of 8- or 11-pin plug-in timers, flashers, and other controls.



**NDS-8 Octal 8-pin Socket**  
8-pin 35mm DIN rail or surface mount. Rated at 10A @ 300VAC. Surface mounted with two #6 (M 3.5 x 0.6) screws or snaps onto a 35 mm DIN rail. Uses PSC8 hold-down clips.



**PSC8 Hold-down Clips**  
Securely mounts plug-in controls in any position. Provides protection against vibration. Use with NDS-8 Octal Socket. Sold in pairs.



**C103PM (AL) DIN Rail**  
35 mm aluminum DIN rail available in a 36 in. (91.4 cm) length.

## Binary Switch Operation

0.1...102.3	1...1023	10...10,230
OFF ▶ ON	OFF ▶ ON	OFF ▶ ON
0.1	1	10
0.2	2	20
0.4	4	40
0.8	8	80
1.6	16	160
3.2	32	320
6.4	64	640
12.8	128	1280
25.6	256	2560
51.2	512	5120
6.3 S	544 S	3000 S

\*\* For CE approved applications, power must be removed from the unit when a switch position is changed.

## Function Diagram



## Specifications

### Time Delay

#### Type

#### Range\*\*

Digital integrated circuitry  
0.1 - 102.3s in 0.1s increments  
1 - 1023s in 1s increments  
10 - 10,230s in 10s increments

#### Repeat Accuracy

#### Setting Accuracy

#### Reset Time

#### Recycle Time

#### Time Delay vs Temp. & Voltage

±0.1% or 20ms, whichever is greater  
±2% or 50ms, whichever is greater  
≤ 50ms  
≤ 150ms  
±5%

### Input

#### Voltage

#### Tolerance

#### 12VDC & 24VDC/AC

#### 110 to 230VAC/DC

#### AC Line Frequency/DC Ripple

#### Power Consumption

#### Input LED Indicator

### Output

#### Type

#### Form

#### Rating

12, 24/28, or 110VDC; 24, 120, or 230VAC  
-15% - 20%  
-20% - 10%  
50/60 Hz/≤10%  
≤ 3.25W  
Green; on when input voltage is applied

Electromechanical relay  
DPDT  
10A resistive @ 120/240VAC & 28VDC;  
1/3 hp @ 120/240VAC

### Life

#### Max. Switching Voltage

#### Relay LED Indicator

### Protection

#### Isolation Voltage

#### Insulation Resistance

#### Polarity

### Mechanical

#### Mounting

#### Dimensions

Mechanical - 1 x 10<sup>7</sup>; Electrical - 1 x 10<sup>6</sup>  
250VAC  
Red; ON when output relay energizes

≥ 1500V RMS input to output  
≥ 100 MΩ  
DC units reverse polarity protected

Plug-in socket  
**H** 81.3 mm (3.2"); **W** 60.7 mm (2.39");  
**D** 45.2 mm (1.78")  
Octal 8-pin plug-in

### Termination

### Environmental

#### Operating/Storage

#### Temperature

#### Weight

-20° to 65°C/-30° to 85°C  
≈ 6 oz (170 g)

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9