




CotoMOS® CT140/CS140

The CT140 and CS140 combine Coto quality and economy in an industry standard 6 pin DIP package. Both the CT140 and the CS140 offer high voltage switching and high load current. The CT140 utilizes a thru hole lead configuration, while the CS140 offers a surface mount option when the application requires it. Both relays are ideally suited to the needs of Test and Measurement, Solar, and Battery Management.


CT140/CS140 Features

- ▶ Contact Form: 1A
- ▶ Load Voltage: 1500V Maximum
- ▶ Operation LED Current: 5.0mA Maximum
- ▶ Load Current: 45mA Maximum
- ▶ On-Resistance: 180Ω Typical
- ▶ Low Off-State Leakage Current: 10μA Maximum
- ▶ I/O Breakdown Voltage: 3750Vrms Minimum
- ▶ Suffix - H for I/O Breakdown Voltage: 5000Vrms Minimum


DIMENSIONS

in Inches (Millimeters)


CT140



CS140




TERMINAL IDENTIFICATION




1: Anode (LED)
2: Cathode (LED)
3: NC
4,6: Drain (MOS FET)
5: Source (MOS FET)


CONNECTIONS



A Control bi-directional signal



C On-Resistance is 1/2 of B-connection



B On-Resistance is 1/2 of A-connection













CT140/CS140 MAXIMUM RATINGS (Ambient Temperature: 25°C)				
Parameters	Symbol	Units	Value	
INPUT SPECIFICATIONS				
Continuous LED Current	I _F	mA	50	
Peak LED Current	I _{FP}	mA	500	
LED Reverse Voltage	V _R	V	5	
Input Power Dissipation	P _{in}	mW	75	
OUTPUT SPECIFICATIONS				
Load Voltage	V _L	V (AC peak or DC)	1500	
Load Current <i>(See connections on previous page)</i>	I _L	mA	A	45mA (AC or DC)
			B	50mA (DC)
			C	70mA (DC)
Peak Load Current	I _{Peak}	mA	200	
Output Power Dissipation	P _{Out}	mW	450	
RELAY SPECIFICATIONS				
Total Power Dissipation	P _T	mW	500	
I/O Breakdown Voltage	V _{I/O}	V _{rms}	3750	
Operating Temperature	T _{Op_r}	°C	-40 ~ +85	
Storage Temperature	T _{Stg}	°C	-40 ~ +100	

CT140/CS140 ELECTRICAL SPECIFICATIONS (Ambient Temperature: 25°C)						
Parameters	Symbol	Test Conditions	Units	Min	Typ	Max
INPUT						
LED Forward Voltage	V _F	I _F =10mA	V	1.0	1.17	1.5
Operation LED Current	I _{F On}		mA		0.9	5.0
Recovery LED Voltage	V _{F Off}		V	0.5	1.0	
OUTPUT						
On-Resistance Drain to Drain	R _{On}	I _F =10mA, I _L =Rating	Ω		110	200
		I _F =10mA, I _L <5mA			180	300
Off-State Leakage Current	I _{Leak}	I _F =0mA, V _L =1500V	μA			10
Output Capacitance	C _{Out}	V _L =0V, f=1MHz	pF		83	
TRANSMISSION						
Turn-On Time	T _{On}	I _F =10mA, I _L =Rating	ms		0.3	1.0
Turn-Off Time	T _{Off}		ms		0.04	0.5
COUPLED						
I/O Insulation Resistance	R _{I/O}		Ω	10 ¹⁰		
I/O Capacitance	C _{I/O}	f=1MHz	pF		1.3	

Environmental Ratings:

Operating Temp: -40°C to +85°C; Storage Temp: -40 to +100°C.

40 SERIES GRAPHS



Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9