


## Slide DIP Switch

## A6S-H

### Standard Surface-Mounting Slide DIP Switches



- Gold-plated twin contacts ensure high reliability.
- Washable, with seal tape available.
- Models with from 1 to 10 poles meet wide needs.
- Embossed taping available for small-reel 100 pcs/500 pcs.

RoHS Compliant





### ■List of Models

#### Tube Packaging

| Type         |                   | Flat actuator                                                                      |                                                                                     | Raised actuator |
|--------------|-------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-----------------|
|              |                   | Standard                                                                           | With seal tape                                                                      |                 |
|              |                   |  |  |                 |
| No. of poles | Quantity per tube |                                                                                    |                                                                                     |                 |
| 1            | 130               | A6S-1101-H                                                                         | A6S-1102-H                                                                          | A6S-1104-H      |
| 2            | 76                | A6S-2101-H                                                                         | A6S-2102-H                                                                          | A6S-2104-H      |
| 3            | 55                | A6S-3101-H                                                                         | A6S-3102-H                                                                          | A6S-3104-H      |
| 4            | 42                | A6S-4101-H                                                                         | A6S-4102-H                                                                          | A6S-4104-H      |
| 5            | 35                | A6S-5101-H                                                                         | A6S-5102-H                                                                          | A6S-5104-H      |
| 6            | 28                | A6S-6101-H                                                                         | A6S-6102-H                                                                          | A6S-6104-H      |
| 7            | 25                | A6S-7101-H                                                                         | A6S-7102-H                                                                          | A6S-7104-H      |
| 8            | 22                | A6S-8101-H                                                                         | A6S-8102-H                                                                          | A6S-8104-H      |
| 9            | 20                | A6S-9101-H                                                                         | A6S-9102-H                                                                          | A6S-9104-H      |
| 10           | 18                | A6S-0101-H                                                                         | A6S-0102-H                                                                          | A6S-0104-H      |

**Note:** Order in multiples of the package quantity.



## Embossed Taping (Standard reel)

| Type         |                   | Flat actuator                                                                     |                                                                                   | Raised actuator   |                                                                                     |
|--------------|-------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------|-------------------------------------------------------------------------------------|
|              |                   | Standard                                                                          | With seal tape                                                                    |                   |                                                                                     |
| No. of poles | Quantity per reel |  |  | Quantity per reel |  |
| 1            | 800               | A6S-1101-PH                                                                       | A6S-1102-PH                                                                       | 800               | A6S-1104-PH                                                                         |
| 2            | 900               | A6S-2101-PH                                                                       | A6S-2102-PH                                                                       | 700               | A6S-2104-PH                                                                         |
| 3            |                   | A6S-3101-PH                                                                       | A6S-3102-PH                                                                       | 700               | A6S-3104-PH                                                                         |
| 4            |                   | A6S-4101-PH                                                                       | A6S-4102-PH                                                                       | 700               | A6S-4104-PH                                                                         |
| 5            |                   | A6S-5101-PH                                                                       | A6S-5102-PH                                                                       | 800               | A6S-5104-PH                                                                         |
| 6            |                   | A6S-6101-PH                                                                       | A6S-6102-PH                                                                       | 700               | A6S-6104-PH                                                                         |
| 7            |                   | A6S-7101-PH                                                                       | A6S-7102-PH                                                                       | 800               | A6S-7104-PH                                                                         |
| 8            |                   | A6S-8101-PH                                                                       | A6S-8102-PH                                                                       | 700               | A6S-8104-PH                                                                         |
| 9            |                   | --- (See note 2.)                                                                 | A6S-9102-PH                                                                       | 700               | A6S-9104-PH                                                                         |
| 10           |                   | --- (See note 2.)                                                                 | A6S-0102-PH                                                                       | 800               | A6S-0104-PH                                                                         |

Note: 1. Order in multiples of the package quantity.

2. Models with a different number of poles than those listed here can also be ordered. For details, consult your OMRON sales representative.




## Embossed Taping (Small reel)

| Type         |                   | Flat actuator                                                                     |                                                                                   | Raised actuator                                                                     |
|--------------|-------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|              |                   | Standard                                                                          | With seal tape                                                                    |                                                                                     |
| No. of poles | Quantity per reel |  |  |  |
| 2            | 400               | --- (See note 2.)                                                                 | A6S-2102-PMH                                                                      | --- (See note 2.)                                                                   |
| 3            |                   | A6S-3101-PMH                                                                      | --- (See note 2.)                                                                 | --- (See note 2.)                                                                   |
| 4            |                   | A6S-4101-PMH                                                                      | A6S-4102-PMH                                                                      | A6S-4104-PMH                                                                        |
| 6            |                   | A6S-6101-PMH                                                                      | A6S-6102-PMH                                                                      | A6S-6104-PMH                                                                        |
| 8            |                   | A6S-8101-PMH                                                                      | A6S-8102-PMH                                                                      | A6S-8104-PMH                                                                        |
| 10           |                   | A6S-0101-PMH                                                                      | A6S-0102-PMH                                                                      | A6S-0104-PMH                                                                        |

Note: 1. Order in multiples of the package quantity.

2. Models with a different number of poles than those listed here can also be ordered. For details, consult your OMRON sales representative.

## Embossed Taping (100 pcs reel)

| Type         |                   | Flat actuator                                                                       |                                                                                     | Raised actuator                                                                       |
|--------------|-------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|              |                   | Standard                                                                            | With seal tape                                                                      |                                                                                       |
| No. of poles | Quantity per reel |  |  |  |
| 1            | 100               | A6S-1101-H-R100                                                                     | A6S-1102-H-R100                                                                     | A6S-1104-H-R100                                                                       |
| 2            |                   | A6S-2101-H-R100                                                                     | A6S-2102-H-R100                                                                     | A6S-2104-H-R100                                                                       |
| 3            |                   | A6S-3101-H-R100                                                                     | A6S-3102-H-R100                                                                     | A6S-3104-H-R100                                                                       |
| 4            |                   | A6S-4101-H-R100                                                                     | A6S-4102-H-R100                                                                     | A6S-4104-H-R100                                                                       |
| 5            |                   | A6S-5101-H-R100                                                                     | A6S-5102-H-R100                                                                     | A6S-5104-H-R100                                                                       |
| 6            |                   | A6S-6101-H-R100                                                                     | A6S-6102-H-R100                                                                     | A6S-6104-H-R100                                                                       |
| 7            |                   | A6S-7101-H-R100                                                                     | A6S-7102-H-R100                                                                     | A6S-7104-H-R100                                                                       |
| 8            |                   | A6S-8101-H-R100                                                                     | A6S-8102-H-R100                                                                     | A6S-8104-H-R100                                                                       |
| 9            |                   | A6S-9101-H-R100                                                                     | A6S-9102-H-R100                                                                     | A6S-9104-H-R100                                                                       |
| 10           |                   | A6S-0101-H-R100                                                                     | A6S-0102-H-R100                                                                     | A6S-0104-H-R100                                                                       |

## ■ Ratings/Characteristics

|                                    |                   |                                                            |
|------------------------------------|-------------------|------------------------------------------------------------|
| Rating (resistive load)            |                   | 25 mA at 24 VDC<br>10 $\mu$ A (minimum current) at 3.5 VDC |
| Ambient operating temperature      |                   | -20 to +70°C at 60% max. (with no icing or condensation)   |
| Ambient operating humidity         |                   | 35% to 95% (at +5 to +35°C)                                |
| Insulation resistance              |                   | 100 M $\Omega$ min. (at 250 VDC with insulation tester)    |
| Contact resistance (initial value) |                   | 200 m $\Omega$ max.                                        |
| Dielectric strength                | Between terminals | 500 VAC for 1 min                                          |
| Vibration resistance               | Malfunction       | 10 to 55 Hz, 1.5-mm double amplitude                       |

|                      |             |                                                                                                            |
|----------------------|-------------|------------------------------------------------------------------------------------------------------------|
| Shock resistance     | Malfunction | 300 m/s <sup>2</sup> min.                                                                                  |
| Durability           | Electrical  | 1,000 operations min.                                                                                      |
| Washing              |             | Standard models: Not possible, Models with seal tape: Possible, Models with raised actuators: Not possible |
| Degree of protection |             | IEC IP40                                                                                                   |
| Operating force      |             | 0.29 to 9.8 N {30 to 1,000 gf}                                                                             |
| Weight               |             | 0.25 g (2 poles)<br>0.41 g (4 poles)<br>0.58 g (6 poles)<br>0.73 g (8 poles)<br>0.87 g (10 poles)          |

## ■Dimensions (Unit: mm)

### ● Flat Actuator



#### Standard

A6S-□101-H

A6S-□101-PH

A6S-□101-PMH

A6S-□101-H-R100





#### With Seal Tape

A6S-□102-H

A6S-□102-PH

A6S-□102-PMH

A6S-□102-H-R100



\* 1 pole type is 0 to 0.15 mm


### ● Raised Actuator

A6S-□104-H


A6S-□104-PH

A6S-□104-PMH


A6S-□104-H-R100




PCB Dimensions (Reference)  
(Top View)




#### Flat Actuator Standard



#### Flat Actuator With Seal Tape



#### Raised Actuator




| No. of poles | Model         |                |                 | Dimension A |
|--------------|---------------|----------------|-----------------|-------------|
|              | Flat Actuator |                | Raised Actuator |             |
|              | Standard      | With Seal Tape |                 |             |
| 1            | A6S-1101-H    | A6S-1102-H     | A6S-1104-H      | 3.48        |
| 2            | A6S-2101-H    | A6S-2102-H     | A6S-2104-H      | 6.02        |
| 3            | A6S-3101-H    | A6S-3102-H     | A6S-3104-H      | 8.56        |
| 4            | A6S-4101-H    | A6S-4102-H     | A6S-4104-H      | 11.10       |
| 5            | A6S-5101-H    | A6S-5102-H     | A6S-5104-H      | 13.64       |
| 6            | A6S-6101-H    | A6S-6102-H     | A6S-6104-H      | 16.18       |
| 7            | A6S-7101-H    | A6S-7102-H     | A6S-7104-H      | 18.72       |
| 8            | A6S-8101-H    | A6S-8102-H     | A6S-8104-H      | 21.26       |
| 9            | A6S-9101-H    | A6S-9102-H     | A6S-9104-H      | 23.80       |
| 10           | A6S-0101-H    | A6S-0102-H     | A6S-0104-H      | 26.34       |

**Note:** Unless otherwise specified, a tolerance of  $\pm 0.4$  mm applies to all dimensions.

## ■Internal Connections

### Contact Form (Top View)



## ■Precautions

Be sure to read the Safety precautions common to all DIP Switches for correct use.

- Application examples provided in this document are for reference only. In actual applications, confirm equipment functions and safety before using the product.
- Consult your OMRON representative before using the product under conditions which are not described in the manual or applying the product to nuclear control systems, railroad systems, aviation systems, vehicles, combustion systems, medical equipment, amusement machines, safety equipment, and other systems or equipment that may have a serious influence on lives and property if used improperly. Make sure that the ratings and performance characteristics of the product provide a margin of safety for the system or equipment, and be sure to provide the system or equipment with double safety mechanisms.

**Note: Do not use this document to operate the Unit.**

---

**OMRON Corporation**  
Electronic and Mechanical Components Company

**Contact:** [www.omron.com/ecb](http://www.omron.com/ecb)

**Cat. No. A211-E1-04**  
0619(0207)(O)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Omron:

[A6S-1102-H](#) [A6S-1102-PH](#) [A6S-3101-PH](#) [A6S-4104-PH](#) [A6S-8104-PH](#) [A6S-0101-H](#) [A6S-0102-H](#) [A6S-0102-PH](#)  
[A6S-0104-H](#) [A6S-2101-H](#) [A6S-2101-PH](#) [A6S-2102-H](#) [A6S-2102-PH](#) [A6S-2104-H](#) [A6S-3101-H](#) [A6S-3102-H](#) [A6S-](#)  
[3102-PH](#) [A6S-3104-H](#) [A6S-4101-H](#) [A6S-4102-H](#) [A6S-4102-PH](#) [A6S-4104-H](#) [A6S-5101-H](#) [A6S-5102-H](#) [A6S-5102-](#)  
[PH](#) [A6S-5104-H](#) [A6S-6101-H](#) [A6S-6102-H](#) [A6S-6102-PH](#) [A6S-6104-H](#) [A6S-7101-H](#) [A6S-7102-H](#) [A6S-7102-PH](#)  
[A6S-7104-H](#) [A6S-8101-H](#) [A6S-8102-H](#) [A6S-8102-PH](#) [A6S-8104-H](#) [A6S-9101-H](#) [A6S-9102-H](#) [A6S-9102-PH](#) [A6S-](#)  
[9104-H](#) [A6S-1101-H](#) [A6S-4101-PH](#) [A6S-0104-PMH](#) [A6S-1104-H](#) [A6S-1104-PH](#) [A6S-2104-PH](#) [A6S-4101-PMH](#)  
[A6S-5104-PH](#) [A6S-6101-PMH](#) [A6S-6104-PH](#) [A6S-6104-PMH](#) [A6S-8101-PH](#) [A6S-8101-PMH](#) [A6S-8104-PMH](#) [A6S-](#)  
[7104-PH](#) [A6S-9104-PH](#) [A6S-2102-PMH](#) [A6S-8102-PMH](#) [A6S-4102-PMH](#)

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9