


RHASeries

- Realized higher voltage than RWF series (500 to 650V_{dc})
- Endurance with ripple current : 5,000 hours at 85°C
- Suitable for high voltage inverter
- RoHS2 compliant




SPECIFICATIONS

Items	Characteristics						
Category							
Temperature Range	-25 to +85°C						
Rated Voltage Range	500 to 650V _{dc}						
Capacitance Tolerance	±20% (M) (at 20°C, 120Hz)						
Leakage Current	I=0.02CV or 5mA, whichever is smaller. Where, I : Max. leakage current (μA), C : Nominal capacitance (μF), V : Rated voltage (V) (at 20°C after 5 minutes)						
Dissipation Factor (tan δ)	0.25 max. (at 20°C, 120Hz)						
Low Temperature Characteristics	Capacitance change $C(-25^{\circ}\text{C})/C(+20^{\circ}\text{C}) \geq 0.6$ (at 120Hz)						
Insulation Resistance	When measured between the terminals that are connected to each other and to the mounting clamp on the insulating sleeve covering the case by using an insulation resistance meter of 500V _{dc} , the insulation resistance shall not be less than 100MΩ.						
Insulation Withstanding Voltage	When a voltage of 2,000V _{ac} is applied for 1 minute between the terminals that are connected to each other and to the mounting clamp on the insulating sleeve covering the case, there shall not be electrical damage.						
Endurance	The following specifications shall be satisfied when the capacitors are restored to 20°C after subjected to DC voltage with the rated ripple current is applied (the peak voltage shall not exceed the rated voltage) for 5,000 hours at 85°C. <table border="1"> <tr> <td>Capacitance change</td><td>≤ ±20% of the initial value</td></tr> <tr> <td>D.F. (tan δ)</td><td>≤ 200% of the initial specified value</td></tr> <tr> <td>Leakage current</td><td>≤ The initial specified value</td></tr> </table>	Capacitance change	≤ ±20% of the initial value	D.F. (tan δ)	≤ 200% of the initial specified value	Leakage current	≤ The initial specified value
Capacitance change	≤ ±20% of the initial value						
D.F. (tan δ)	≤ 200% of the initial specified value						
Leakage current	≤ The initial specified value						
Shelf Life	The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 500 hours at 85°C without voltage applied. Before the measurement, the capacitor shall be preconditioned by applying voltage according to Item 4.1 of JIS C 5101-4. <table border="1"> <tr> <td>Capacitance change</td><td>≤ ±20% of the initial value</td></tr> <tr> <td>D.F. (tan δ)</td><td>≤ 200% of the initial specified value</td></tr> <tr> <td>Leakage current</td><td>≤ The initial specified value</td></tr> </table>	Capacitance change	≤ ±20% of the initial value	D.F. (tan δ)	≤ 200% of the initial specified value	Leakage current	≤ The initial specified value
Capacitance change	≤ ±20% of the initial value						
D.F. (tan δ)	≤ 200% of the initial specified value						
Leakage current	≤ The initial specified value						

DIMENSIONS (Screw-Mount) [mm]

● Terminal Code : LG




φ50 & φ63.5 : G=6
φ76.2 & φ89 : G=5
φ100 : G=10

<Screw specifications>


to φ89 Plus hexagon-headed screw : M5×0.8×10
Maximum screw tightening torque : 3.23Nm

● Mounting Clamp Code : B



φD	A	B	W	F
50	78.0	64.0	68.0	22.4
63.5	90.0	76.0	80.0	28.0
76.2	104.5	90.0	93.5	31.5

● Mounting Clamp Code : C




φD	E	K	M	F	J
50	32.5	37.0	4.5	22.4	14.0
63.5	38.1	43.5	4.5	28.0	14.0
76.2	44.5	50.0	4.5	31.5	14.0
89	50.8	56.5	4.5	31.5	16.0
100	56.5	63.4	5.5	41.5	18.0

φ100 Cross-recessed head (phillips) screw : M8×1.25×16
Spring washer, Washer
Maximum screw tightening torque : 6.31Nm

* The screw and the mounting clamp are separately supplied and not attached to the product.

PART NUMBERING SYSTEM



Please refer to "Product code guide (screw-mount terminal type)"

◆STANDARD RATINGS

WV (V _{dc})	Cap (μF)	Case size φD×L(mm)	tan δ	Rated ripple current (Arms/ 85°C,120Hz)	Part No.	WV (V _{dc})	Cap (μF)	Case size φD×L(mm)	tan δ	Rated ripple current (Arms/ 85°C,120Hz)	Part No.
500	1,200	50×95	0.25	5.90	ERHA501LGC122MC95U	550	5,600	89×150	0.25	18.2	ERHA551LGC562MFF0U
	1,500	50×115	0.25	7.20	ERHA501LGC152MCB5U		6,800	89×170	0.25	21.1	ERHA551LGC682MFH0U
	1,800	50×130	0.25	8.30	ERHA501LGC182MCD0U		8,200	100×170	0.25	24.8	ERHA551LGC822MGH0U
	2,200	50×150	0.25	9.80	ERHA501LGC222MCF0U		10,000	100×200	0.25	29.4	ERHA551LGC103MGL0U
	2,700	63.5×120	0.25	11.2	ERHA501LGC272MDC0U	600	1,200	63.5×95	0.25	6.70	ERHA601LGC122MD95U
	3,300	63.5×140	0.25	13.3	ERHA501LGC332MDE0U		1,500	63.5×110	0.25	8.00	ERHA601LGC152MDB0U
	3,900	63.5×170	0.25	15.7	ERHA501LGC392MDH0U		1,800	63.5×125	0.25	9.30	ERHA601LGC182MDC5U
	3,900	76.2×130	0.25	15.4	ERHA501LGC392MED0U		1,800	76.2×95	0.25	9.10	ERHA601LGC182ME95U
	4,700	76.2×150	0.25	18.1	ERHA501LGC472MEF0U		2,200	63.5×145	0.25	11.0	ERHA601LGC222MDE5U
	5,600	76.2×170	0.25	20.8	ERHA501LGC562MEH0U		2,200	76.2×110	0.25	10.8	ERHA601LGC222MEB0U
	5,600	89×130	0.25	17.1	ERHA501LGC562MFD0U		2,700	63.5×170	0.25	13.1	ERHA601LGC272MDH0U
	6,800	89×150	0.25	20.0	ERHA501LGC682MFF0U		2,700	76.2×125	0.25	12.6	ERHA601LGC272MEC5U
	8,200	89×190	0.25	24.4	ERHA501LGC822MFK0U		3,300	76.2×145	0.25	14.9	ERHA601LGC332MEE5U
	10,000	89×210	0.25	28.2	ERHA501LGC103MFM0U		3,900	76.2×170	0.25	17.3	ERHA601LGC392MEH0U
	12,000	100×210	0.25	32.9	ERHA501LGC123MGM0U		3,900	89×130	0.25	14.2	ERHA601LGC392MFD0U
	15,000	100×250	0.25	39.8	ERHA501LGC153MGR0U		4,700	76.2×190	0.25	20.0	ERHA601LGC472MEK0U
							4,700	89×150	0.25	16.6	ERHA601LGC472MFF0U
550	1,000	50×95	0.25	5.40	ERHA551LGC102MC95U		5,600	89×170	0.25	19.1	ERHA601LGC562MFH0U
	1,200	50×110	0.25	6.30	ERHA551LGC122MCB0U	650	1,000	63.5×100	0.25	6.30	ERHA651LGC102MDA0U
	1,500	50×130	0.25	7.60	ERHA551LGC152MCD0U		1,200	63.5×110	0.25	7.20	ERHA651LGC122MDB0U
	1,800	63.5×105	0.25	8.60	ERHA551LGC182MDA5U		1,500	63.5×130	0.25	8.60	ERHA651LGC152MDD0U
	2,200	63.5×120	0.25	10.1	ERHA551LGC222MDC0U		1,800	63.5×150	0.25	10.1	ERHA651LGC182MDF0U
	2,700	63.5×150	0.25	12.4	ERHA551LGC272MDF0U		2,200	63.5×170	0.25	11.7	ERHA651LGC222MDH0U
	2,700	76.2×105	0.25	11.7	ERHA551LGC272MEA5U		2,700	76.2×150	0.25	13.6	ERHA651LGC272MEF0U
	3,300	63.5×170	0.25	14.5	ERHA551LGC332MDH0U		3,300	76.2×170	0.25	15.8	ERHA651LGC332MEH0U
	3,300	76.2×130	0.25	14.2	ERHA551LGC332MED0U		3,900	89×155	0.25	15.3	ERHA651LGC392MFF5U
	3,900	76.2×140	0.25	15.9	ERHA551LGC392MEE0U		4,700	89×190	0.25	18.4	ERHA651LGC472MFK0U
	4,700	76.2×170	0.25	19.1	ERHA551LGC472MEH0U						
	4,700	89×130	0.25	15.6	ERHA551LGC472MFD0U						

◆RATED RIPPLE CURRENT MULTIPLIERS

● Frequency Multipliers

Frequency (Hz)	50	120	300	1k	3k
Coefficient	0.8	1.0	1.2	1.3	1.4

Note : The endurance of capacitors is reduced with internal heating produced by ripple current at the rate of halving the lifetime with every 5 to 10°C rise. When long life performance is required in actual use, the rms ripple current has to be reduced. Also, for the RHA series capacitors, using them at operating voltage less than their rated voltage can extend their lifetime. For details, please contact a representative of Nippon Chemi-Con.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

United Chemi-Con (UCC):

<u>ERHA651LGC332MEH0M</u>	<u>ERHA551LGC392MEE0M</u>	<u>ERHA501LGC182MCD0M</u>	<u>ERHA551LGC332MED0M</u>
<u>ERHA651LGC472MFK0M</u>	<u>ERHA551LGC822MGH0M</u>	<u>ERHA501LGC123MGM0M</u>	<u>ERHA501LGC332MDE0M</u>
<u>ERHA551LGC472MEH0M</u>	<u>ERHA551LGC122MCB0M</u>	<u>ERHA601LGC332MEE5M</u>	<u>ERHA501LGC562MEH0M</u>
<u>ERHA551LGC102MC95M</u>	<u>ERHA651LGC392MFF5M</u>	<u>ERHA601LGC182ME95M</u>	<u>ERHA601LGC392MEH0M</u>
<u>ERHA501LGC682MFF0M</u>	<u>ERHA601LGC472MFF0M</u>	<u>ERHA501LGC103MFM0M</u>	<u>ERHA601LGC562MFH0M</u>
<u>ERHA651LGC272MEF0M</u>	<u>ERHA651LGC152MDD0M</u>	<u>ERHA551LGC103MGL0M</u>	<u>ERHA551LGC222MDC0M</u>
<u>ERHA651LGC122MDB0M</u>	<u>ERHA551LGC272MDF0M</u>	<u>ERHA501LGC122MC95M</u>	<u>ERHA651LGC102MDA0M</u>
<u>ERHA551LGC562MFF0M</u>	<u>ERHA501LGC472MEF0M</u>	<u>ERHA651LGC182MDF0M</u>	<u>ERHA651LGC222MDH0M</u>
<u>ERHA551LGC182MDA5M</u>	<u>ERHA551LGC152MCD0M</u>	<u>ERHA601LGC272MDH0M</u>	<u>ERHA601LGC272MEC5M</u>
<u>ERHA501LGC562MFD0M</u>	<u>ERHA501LGC153MGR0M</u>	<u>ERHA501LGC222MCF0M</u>	<u>ERHA551LGC682MFH0M</u>
<u>ERHA501LGC272MDC0M</u>	<u>ERHA601LGC222MEB0M</u>	<u>ERHA501LGC822MFK0M</u>	<u>ERHA601LGC392MFD0M</u>
<u>ERHA501LGC392MED0M</u>	<u>ERHA601LGC152MDB0M</u>	<u>ERHA501LGC152MCB5M</u>	<u>ERHA501LGC392MDH0M</u>
<u>ERHA601LGC222MDE5M</u>	<u>ERHA551LGC332MDH0M</u>	<u>ERHA551LGC272MEA5M</u>	<u>ERHA551LGC472MFD0M</u>
<u>ERHA601LGC182MDC5M</u>	<u>ERHA601LGC472MEK0M</u>	<u>ERHA601LGC122MD95M</u>	<u>ERHA601LGC562MFH0U</u>

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9