

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

IDENTIFICATION LABEL


TWIST TIE

| CONTACT | CABLE<br>WIRE COLOR |
|---------|---------------------|
| 1       | WHITE/BUE           |
| 2       | BLUE                |

NOTES:

1. SEE CURRENT CATALOG FOR VARIOUS APPLICATIONS AND TO INDICATE PACKAGE QUANTITY.
2. 110 CONNECTORS ON BOTH ENDS. THE PATCH CORDS CAN BE USED WITH PAN-PUNCH™ 110 CONNECTING BLOCKS.
3. FEATURES INCLUDE A CLEAR CAP TO ENSURE PROPER WIRE SEQUENCE AND CONNECTOR ORIENTATION. RETAINING CLIPS SECURE THE JACKET CLOSE TO THE POINT OF TERMINATION WHICH MINIMIZES WIRE UNTWISTING. INTEGRAL STRAIN RELIEF MINIMIZES STRESS ON WIRES DURING DISCONNECTION.
4. POLARIZED TO PREVENT REVERSE INSTALLATION TO CONNECTOR BLOCK.
5. CATEGORY 3 UNSHIELDED TWISTED PAIR CABLE WITH 24AWG STRANDED TINNED COPPER CONDUCTOR.
6. DIMENSIONS IN PARENTHESES ARE IN METRIC.

| PANDUIT P/N    | MIN. CABLE<br>LENGTH | WEIGHT                             |
|----------------|----------------------|------------------------------------|
| P110PC11G2Y    | 2 FT.                | .24 LB/10 PCS<br>(112.1 g/10 PCS)  |
| P110PC11G3Y    | 3 FT.                | .31 LB/10 PCS<br>(144.5 g/10 PCS)  |
| P110PC11G4Y    | 4 FT.                | .38 LB/10 PCS<br>(176.9 g/10 PCS)  |
| P110PC11G5Y    | 5 FT.                | .45 LB/10 PCS<br>(209.3 g/10 PCS)  |
| P110PC11G6Y    | 6 FT.                | .52 LB/10 PCS<br>(241.7 g/10 PCS)  |
| P110PC11G7Y    | 7 FT.                | .59 LB/10 PCS<br>(274.1 g/10 PCS)  |
| P110PC11G8Y    | 8 FT.                | .66 LB/10 PCS<br>(306.5 g/10 PCS)  |
| P110PC11G9Y    | 9 FT.                | .73 LB/10 PCS<br>(338.9 g/10 PCS)  |
| P110PC11G12Y   | 12 FT.               | 1.93 LB/10 PCS<br>(436.1 g/10 PCS) |
| P110PC11G15Y   | 15 FT.               | 1.15 LB/10 PCS<br>(533.3 g/10 PCS) |
| P110PC11G18Y   | 18 FT.               | 1.36 LB/10 PCS<br>(630.5 g/10 PCS) |
| P110PC11G.5MY  | .5M                  | .22 LB/10 PCS<br>(100.45g/10 PCS)  |
| P110PC11G1MY   | 1M                   | .33 LB/10 PCS<br>(153.6 g/10 PCS)  |
| P110PC11G1.5MY | 1.5M                 | .45 LB/10 PCS<br>(206.8 g/10 PCS)  |
| P110PC11G2MY   | 2M                   | .56 LB/10 PCS<br>(259.9 g/10 PCS)  |
| P110PC11G3MY   | 3M                   | .79 LB/10 PCS<br>(366.2 g/10 PCS)  |
| P110PC11G4MY   | 4M                   | 1.02 LB/10 PCS<br>(472.5 g/10 PCS) |
| P110PC11G5MY   | 5M                   | 1.25 LB/10 PCS<br>(578.8 g/10 PCS) |
| P110PC11G6MY   | 6M                   | 1.48 LB/10 PCS<br>(685.1 g/10 PCS) |



PART NUMBER

P110PC1\*\*\*Y

TITLE

CATEGORY 3 110 PATCH CORD

CUSTOMER DRAWING

ITEM REVISION NAME


M02479JQ/05

DATASET FILE NAME

M02479JQ\_DC253/00B

UNLESS OTHERWISE SPECIFIED,  
DIMENSIONAL TOLERANCES ARE: IN [ mm ]

.X ± .XXX ± .010 [ .3 ]  
.XX ± .03 [ .8 ] ANGLES ±



THIRD ANGLE  
PROJECTION

MATERIAL:

DRAWING NUMBER:

02479-253

DRAWN BY

DATE

CHK

SCALE

NER

3-17-06

WJC

NONE

SHT 1 OF 1

SIZE

A

| REV | DATE    | BY  | CHK  | APR | DESCRIPTION                     | ECN       |
|-----|---------|-----|------|-----|---------------------------------|-----------|
| 1   | 5/28/14 | JSP | REFR | MMR | A. REVISED DRAWING TITLE BLOCK. | 02479-253 |
| R   | 3-17-06 | NER | WJC  | RMD | RELEASED TO PRODUCTION          | 02479-253 |

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9