

Ceramic Chip Capacitors

Type NPO, X5R, X7R, Y5V

ISO 9001:2008
TS-16949

1. General

1-1 Range of Application

This document applies to miniaturized ceramic chip capacitors for applications in circuits of electronic devices.


2. Type Designation

The type designation shall be the following form:

New Type

NPO	0805	H	T	TD	101	K
Dielectric	Size	Voltage	Termination Material	Packaging	Capacitance Code	Tolerance
NPO X5R X7R Y5V	0402 0603 0805 1206 1210	A = 10V C = 16V E = 25V H = 50V I = 100V J = 200V K = 6.3V	T: Sn	TP: 7" 2mm pitch (0402 only) TD: 7" paper tape TE: 7" embossed plastic TDB: 13" paper tape TEB: 13" embossed plastic	NPO, X5R, X7R, Y5V - 2 significant digits + no. of zeros. R indicates decimal point.	B = $\pm 0.1\text{pF}$ C = $\pm 0.25\text{pF}$ D = $\pm 0.5\text{pF}$ F = $\pm 1\%$ G = $\pm 2\%$ J = $\pm 5\%$ K = $\pm 10\%$ M = $\pm 20\%$ Z = $+80\%, -20\%$

3. Dimensions and Construction



Case Size	Dimensions inches (mm)			
	L	W	t (Max.)	d
0402	.039 $\pm$.004 (1.0 $\pm$ 0.1)	.02 $\pm$.004 (0.5 $\pm$ 0.1)	.021 (0.55)	.01 $\pm$.006 (0.25 $\pm$ 0.15)
0603	.063 $\pm$.006 (1.6 $\pm$ 0.15)	.032 $\pm$.006 (0.81 $\pm$ 0.15)	.035 (0.9)	.014 $\pm$.006 (0.35 $\pm$ 0.15)
0805	.079 $\pm$.008 (2.01 $\pm$ 0.2)	.049 $\pm$.008 (1.25 $\pm$ 0.2)	.051 (1.3)	.02 $\pm$.01 (0.50 $\pm$ 0.25)
1206	.126 $\pm$.008 (3.2 $\pm$ 0.2)	.063 $\pm$.008 (1.6 $\pm$ 0.2)	.059 (1.5)	.02 $\pm$.01 (0.5 $\pm$ 0.25)
1210	.126 $\pm$.008 (3.2 $\pm$ 0.2)	.098 $\pm$.008 (2.5 $\pm$ 0.2)	.067 (1.7)	.02 $\pm$.01 (0.5 $\pm$ 0.25)

4. Terminations

- Standard Nickel Barrier
- Solder Plated

5. Applications and Ratings

Dielectric	Capacitance Tolerance	Voltage Ratings	Dissipation Factor	T.C.C.	Test Voltage	Operating Temperature	Insulation Resistance
NPO	.47pF~8.2pF= C:±0.25pF 5.6pF~8.2pF= D±0.5pF 10pF~ 10000pF= F:±1%, G:±2%,J:±5%	50V 100V 200V	For Values >30pF: 0.1% max., ≤30pF: Q = 400 + 20 x C DF = 1/Q C is in pF	0 ± 30 ppm/°C	1.0 ± 0.2 Vrms	-55°C to +125°C	+25°C 100,000MΩ min. or 1000 MΩ - μF min. whichever is less
X5R	K: ±10%	6.3V 10V	6.3V = 7.5% max. 10V = 10% max.	±15% (0 VDC)	1.0 ± 0.2 Vrms	-55°C to +85°C	+25°C 100,000MΩ min. or 500 MΩ - μF min. whichever is less
X7R	K: ±10%	10V 16V 25V 50V 100V 200V	10V = 10% max. 16V = 3.5% max. 25V, 50V, 100V = 2.5% max.	±15% (0 VDC)	1.0 ± 0.2 Vrms	-55°C to +125°C	+25°C 100,000MΩ min. or 1000 MΩ - μF min. whichever is less
Y5V	Z: +80, -20%	10V 16V 25V 50V	16V & 25V = 7.0% 50V = 5.0%	+22% to -82% max.	1.0 ± 0.2 Vrms	-30°C to +85°C	+25°C 10,000MΩ min. or 1000 MΩ - μF min. whichever is less

For complete environmental specifications, please refer to www.koaspeer.com

6. NPO Capacitance Voltage Availability

Size			0402*	0603*		0805			1206		
pF	Capacitance values μF	Cap. Code	50 (H)	50 (H)	100 (I)	50 (H)	100 (I)	200 (J)	50 (H)	100 (I)	200 (J)
0.47	.00000047	R47									
0.56	.00000056	R56									
0.68	.00000068	R68									
0.82	.00000082	R82									
1	.0000010	1R0									
1.2	.0000012	1R2									
1.5	.0000015	1R5									
1.8	.0000018	1R8									
2.2	.0000022	2R2									
2.7	.0000027	2R7									
3.3	.0000033	3R3									
3.9	.0000039	3R9									
4.7	.0000047	4R7									
5.6	.0000056	5R6									
6.8	.0000068	6R8									
8.2	.0000082	8R2									
10	.000010	100									
12	.000012	120									
15	.000015	150									
18	.000018	180									
22	.000022	220									
27	.000027	270									
33	.000033	330									
39	.000039	390									
47	.000047	470									
56	.000056	560									
68	.000068	680									
82	.000082	820									
100	.0001	101									
120	.00012	121									
150	.00015	151									
180	.00018	181									
220	.00022	221									
270	.00027	271									
330	.00033	331									
390	.00039	391									
470	.00047	471									
560	.00056	561									
680	.00068	681									
820	.00082	821									
1000	.0010	102									
1200	.0012	122									

Capacitance tolerance available:

.47pF~8.2pF = C: ±0.25pF

5.6pF~8.2pF = D: ±0.5pF

10pF~10000pF = F: ±1%, G: ±2%, J: ±5%

7. X5R Capacitance Voltage Availability

Size			0402	0603		0805	1206	1210
Capacitance values			10	6.3	10	6.3	10	10
pF	μF	Cap. Code	(A)	(K)	(A)	(K)	(A)	(A)
56000	0.056	563						
68000	0.068	683						
82000	0.082	823						
100000	0.10	104						
120000	0.12	124						
150000	0.15	154						
180000	0.18	184						
220000	0.22	224						
270000	0.27	274						
330000	0.33	334						
470000	0.47	474						
560000	0.56	564						
680000	0.68	684						
820000	0.82	824						
1000000	1.0	105						
1200000	1.2	125						
1500000	1.5	155						
1800000	1.8	185						
2200000	2.2	225						
3300000	3.3	335						
4700000	4.7	475						
6800000	6.8	685						
10000000	10	106						
22000000	22	226						
47000000	47	476						
100000000	100	107						

Capacitance tolerance available: ±10%

8. X7R Capacitance Voltage Availability

Size			0402				0603				0805						1206					1210		
Capacitance values			10	16	25	50	10	16	25	50	10	16	25	50	100	200	10	16	50	100	200	50	100	200
pF	μF	Cap. Code	(A)	(C)	(E)	(H)	(A)	(C)	(E)	(H)	(A)	(C)	(E)	(H)	(I)	(J)	(A)	(C)	(H)	(I)	(J)	(H)	(I)	(J)
100	.0001	101																						
120	.00012	121																						
150	.00015	151																						
180	.00018	181																						
220	.00022	221																						
270	.00027	271																						
330	.00033	331																						
390	.00039	391																						
470	.00047	471																						
560	.00056	561																						
680	.00068	681																						
820	.00082	821																						
1000	.0010	102																						
1200	.0012	122																						
1500	.0015	152																						
1800	.0018	182																						
2200	.0022	222																						
2700	.0027	272																						
3300	.0033	332																						
3900	.0039	392																						
4700	.0047	472																						
5600	.0056	562																						
6800	.0068	682																						
8200	.0082	822																						
10000	.010	103																						
12000	.012	123																						
15000	.015	153																						
18000	.018	183																						
22000	.022	223																						
27000	.027	273																						
33000	.033	333																						
39000	.039	393																						
47000	.047	473																						
56000	.056	563																						
68000	.068	683																						
82000	.082	823																						
100000	.100	104																						
120000	.120	124																						
150000	.150	154																						
180000	.180	184																						
220000	.220	224																						
270000	.270	274																						
330000	.330	334																						
390000	.390	394																						
470000	.470	474																						
560000	.560	564																						
680000	.680	684																						
1000000	1.00	105																						
1200000	1.20	125																						
1500000	1.50	155																						
1800000	1.80	185																						
2200000	2.20	225																						
3900000	3.90	395																						
4700000	4.70	475																						

Capacitance tolerance available: ±10%

9. Y5V Capacitance Voltage Availability

Size			0402	0603				0805				1206			
Capacitance values			16	16	25	50	10	16	25	50	10	16	25	50	
pF	µF	Cap. Code	(C)	(C)	(E)	(H)	(A)	(C)	(E)	(H)	(A)	(C)	(E)	(H)	
2200	.0022	222													
2700	.0027	272													
3300	.0033	332													
3900	.0039	392													
4700	.0047	472													
5600	.0056	562													
6800	.0068	682													
8200	.0082	822													
10000	.010	103													
12000	.012	123													
15000	.015	153													
18000	.018	183													
22000	.022	223													
27000	.027	273													
33000	.033	333													
39000	.039	393													
47000	.047	473													
56000	.056	563													
68000	.068	683													
82000	.082	823													
100000	.100	104													
120000	.120	124													
150000	.150	154													
180000	.180	184													
220000	.220	224													
270000	.270	274													
330000	.330	334													
390000	.390	394													
470000	.470	474													
560000	.560	564													
680000	.680	684													
820000	.820	824													
1000000	1.0	105													
1200000	1.2	125													
1500000	1.5	155													
1800000	1.8	185													
2200000	2.2	225													
2700000	2.7	275													
3300000	3.3	335													
3900000	3.9	395													
4700000	4.7	475													
5600000	5.6	565													
6800000	6.8	685													
10000000	10	106													
22000000	22	226													

Capacitance tolerance available: +80%, -20%


10. Typical Impedance Characteristics - NPO

Variation of Impedance with Cap Value


Impedance vs. Frequency

0805 - C0G (NPO)


10 pF vs. 100 pF vs. 1000 pF




Δ Capacitance vs. Frequency



Temperature Coefficient




Insulation Resistance vs. Temperature



Variation of Impedance with Chip Size

Impedance vs. Frequency

1000 pF - C0G (NPO)




Variation of Impedance with Ceramic Formulation



Impedance vs. Frequency

1000 pF - C0G (NPO) vs X7R

0805




11. Typical Impedance Characteristics - X5R




12. Typical Impedance Characteristics - X7R


Variation of Impedance with Cap Value
Impedance vs. Frequency
1,000 pF vs. 10,000 pF - X7R
0805




Δ Capacitance vs. Frequency




Temperature Coefficient




Insulation Resistance vs Temperature









Variation of Impedance with Chip Size
Impedance vs. Frequency
10,000 pF - X7R



Variation of Impedance with Chip Size
Impedance vs. Frequency
100,000 pF - X7R



13. Typical Impedance Characteristics - Y5V



14. Tape and Reel Quantities


All tape and reel specifications are in compliance with RS481.

Size	Dielectric	Voltage	Cap. Range	TP	TD	TE	TDB	TEB
0402	All	All	All	10000	—	—	—	—
0603	All	All	All	—	4000	—	15000	—
0805	NPO	All	All	—	4000	—	20000	—
	X5R	All	All	—	—	3000	—	—
	X7R	200	472	—	4000	—	15000	—
		200	682	—	—	3000	—	10000
		100	< = 103	—	4000	—	20000	—
		100	153 ~ 223	—	4000	—	15000	—
		50	< = 223	—	4000	—	20000	—
		50	273 ~ 563	—	4000	—	15000	—
		50	104	—	4000	—	15000	—
		25	< = 333	—	4000	—	20000	—
		25	393 ~ 104	—	4000	—	15000	—
		16	473 ~ 683	—	4000	—	20000	—
		16	823 ~ 274	—	4000	—	15000	—
		16	334 ~ 474	—	—	3000	—	10000
		10	684 ~ 105	—	—	3000	—	10000
	Y5V	50	103 ~ 104	—	4000	—	20000	—
		50	224	—	4000	—	15000	—
		25	103 ~ 104	—	4000	—	20000	—
		25	154 ~ 224	—	4000	—	15000	—
		16	474, 105	—	4000	—	15000	—
		10	All	—	—	3000	—	10000

* TP is a 7" reel with a 2mm pitch, TD & TE are 7" reels, TDB & TEB are 13" reels

Size	Dielectric	Voltage	Cap. Range	TD	TE	TDB	TEB
1206	NPO	200	< = 151	4000	—	20000	—
		200	221 ~ 102	4000	—	15000	—
		100	< = 471	4000	—	20000	—
		50	< = 471	4000	—	20000	—
	X5R	10	475, 106	—	3000	—	—
		100	< = 473	4000	—	15000	—
		100	683	—	4000	—	—
		100	104	—	2000	—	—
		200	< = 153	4000	—	15000	—
		200	223	—	3000	—	10000
		50	< = 124	4000	—	15000	—
		50	154 ~ 224	—	3000	—	10000
		16	< = 394	4000	—	15000	—
		16	474 ~ 105	—	3000	—	10000
		10	225 ~ 275	—	3000	—	10000
	Y5V	50	104 ~ 224	4000	—	20000	—
		50	334 ~ 474	4000	—	15000	—
		50	684	—	3000	—	10000
		25	104 ~ 224	4000	—	20000	—
		25	334 ~ 684	4000	—	15000	—
		25	225	—	3000	—	10000
		16	105	4000	—	15000	—
		10	335 ~ 475	—	3000	—	10000
		10	226	—	2500	—	7000
		10	106	—	2000	—	—
1210	X5R	10	106	—	2000	—	—
	X7R	50	123 ~ 333	—	4000	—	10000
		50	823 ~ 224	—	3000	—	10000
		100	473 ~ 823	—	4000	—	10000
		200	223 ~ 473	—	3000	—	10000

15. Reel Specifications



Reel Dimensions


Tape Size ⁽¹⁾	Dimensions inches (mm)						
	A Max.	B* Min.	C	D* Min.	N Min.	W ₁	W ₂ Max. W ₃
8mm	12.992 (330)	0.059 (1.5)	0.512 ± 0.008 (13.0 ± 0.20)	.795 (20.2)	1.969 (50)	.331 ± .060 (8.4 ± 1.5)	.567 (14.4) .311 (7.9 Min.) .429 (10.9 Max.)
12mm						.488 ± .076 (12.4 ± 2.0)	.724 (18.4) .469 (11.9 Min.) .607 (15.4 Max.)

Metric dimensions will govern. English measurements rounded and for reference only.

(1) For tape sizes 16mm and 24mm (used with chip size 3640) consult EIA RS-481 latest revision.

16. Carrier Tape Specifications

Embossed plastic
8 & 12mm



Tape Size <i>Constant</i>	Dimensions inches (mm)							
	D ₀	E	P ₀	P ₂	T Max.	T ₁	G ₁	G ₂
8mm, 12mm	.059 ±.004 (1.5 ±0.10) 0.0	.069 ± .004 (1.75 ±0.10)	.157 ± .004 (4.0 ± 0.10)	.079 ± .002 (2.0 ± 0.05)	.024 (0.600)	.004 (0.10) Max.	.030 (0.75) Min. See note 3	.030 (0.75) Min. See note 4




Tape Size <i>Variable</i>	Dimensions inches (mm)							
	B ₁ Max. See note 6	D ₁ Min. See note 5	F	P ₁	R Min. See note 2	T ₂	W	A ₀ B ₀ K ₀
8mm	.179 (4.55)	.039 (1.0)	.138 ± .002 (3.5 ± 0.05)	.157 ± .004 (4.0 ± 0.10)	.984 (25)	.098 (2.5 Max.)	.315 ± .012 (8.0 ± 0.3) 0.1	See note 1
12mm	.323 (8.2)	.059 (1.5)	.217 ± .002 (5.5 ± 0.05)	.157 ± .004 (4.0 ± 0.10)	1.181 (30)	.256 (6.5 Max.)	.472 ± .012 (12.0 ± .30)	See note 1
12mm 1/2 Pitch	.179 (4.55)	.039 (1.0)	.138 ± .002 (3.5 ± 0.05)	.079 ± .004 (2.0 ± 0.10)	.984 (25)	.098 (2.5 Max.)	.315 ± .012 (8.0 ± 0.3) 0.1	See note 1
12mm Double Pitch	.323 (8.2)	.059 (1.5)	.217 ± .002 (5.5 ± 0.05)	.315 ± .004 (8.0 ± 0.10)	1.181 (30)	.256 (6.5 Max.)	.472 ± .012 (12.0 ± .30)	See note 1

Notes:

- A₀, B₀ and K₀ are determined by the max. dimensions to the ends of the terminals extending from the components body and/or the body of the component. The clearance between the end of the terminals of the body of the components to the sides and depth of the cavity (A₀, B₀ and K₀) must be within .002" (0.05)mm min. and .020" (0.50)mm max. The clearance allowed must also prevent rotation of the component within the cavity of not more than 20 degrees (see examples A & B).
- Tape with components shall pass around radius "R" without damage. The minimum trailer length (Note 2 Fig. 3) may require additional length to provide R min. for .472" (12)mm embossed tape for reels with hub diameters approaching N min. (Table 4).
- G₁ dimension is the flat area from the edge of the sprocket hole to either the outward deformation of the carrier tape between the embossed cavities or to the edge of the cavity whichever is less.
- G₂ dimension is the flat area from the edge of the carrier tape opposite the sprocket holes to either the outward deformation of the carrier tape between the embossed cavity or to the edge of the cavity whichever is less.
- The embossed hole location shall be measured from the sprocket hole controlling the location of the embossment. Dimensions of embossment location and hole location shall be applied independent of each other.
- B₁ dimension is a reference dimension for tape feeder clearance only.

17. Carrier Tape Specifications

Punched paper tape
8 & 12mm



Carrier Tape Dimensions

Tape Size <i>Constant</i>	Dimensions inches (mm)							
	D ₀	E	P ₀	P ₂	T ₁	G ₁		
8mm	.059 ±.004 (1.5 ± 0.1)	.069 ± .004 (1.75 ± 0.10)	.157 ± .004 (4.0 ± 0.10)	.079 ± .002 (2.0 ± 0.05)	.004 (0.10) Max.	.030 (0.75) Min.	.030 (0.75) Min.	.984 (25) See note 2
12mm								

Tape Size <i>Variable</i>	Dimensions inches (mm)				
	P ₁	F	W	A ₀ B ₀	T
8mm	.157 ± .004 (4.0 ± 0.10)	.138 ± .002 (3.5 ± 0.05)	.315 ± .012 (8.0 ± 0.3)	See note 1	See note 3
12mm	.157 ± .004 (4.0 ± 0.10)	.217 ± .002 (5.5 ± 0.05)	.472 ± .012 (12.0 ± 0.3)		
8mm 1/2 Pitch	.079 ± .004 (2.0 ± 0.10)	.138 ± .002 (3.5 ± 0.05)	.315 ± .012 (8.0 ± 0.3)		
12mm Double Pitch	.315 ± .004 (8.0 ± 0.10)	.217 ± .002 (5.5 ± 0.05)	.472 ± .012 (12.0 ± 0.3)		


Notes:

1. A₀, B₀ and T are determined by the max. dimensions to the ends of the terminals extending from the component body and/or the body dimensions of the component. The clearance between the ends of the terminals or body of the components to the sides and depth of the cavity (A₀, B₀ and T) must be within .002" (0.05) mm min. and .020" (0.50) mm max. The clearance allowed must also prevent rotation of the component within the cavity of not more than 20 degrees (see examples C & D).
2. Tape with components shall pass around radius "R" without damage.
3. .043" (1.1) mm base tape and .063" (1.6) mm max. for non-paper base compositions.

18. Recommended Land Pattern Dimensions

Component pads should be designed to achieve good solder filets and minimize component movement during reflow soldering. Pad dimensions are given below for multilayer ceramic capacitors for both reflow and wave soldering. The basis for these designs is:

- Pad width equal to component width. It is permissible to decrease this to as low as 85% of component width but it is not advisable to go below this.
- Pad overlap 0.5mm beneath component
- Pad extension 0.5mm beyond components for reflow and 1.0mm for wave soldering



Case Size	Dimensions inches (mm)			
	A	B	C	D
0402	0.02 (0.50)	0.07 (1.70)	0.02 (0.60)	0.02 (0.50)
0603	0.03 (0.75)	0.09 (2.30)	0.03 (0.80)	0.03 (0.70)
0805	0.05 (1.25)	0.12 (3.00)	0.04 (1.00)	0.04 (1.00)
1206	0.06 (1.60)	0.16 (4.00)	0.04 (1.00)	0.09 (2.00)
1210	0.10 (2.50)	0.16 (4.00)	0.04 (1.00)	0.09 (2.00)

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9