

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0740582513](#)
Status: **Active**
Overview: [vhdm](#)
Description: 2.00mm (.079") Pitch VHDM® Board-to-Board Backplane Header, Vertical, 6-Row, Pin End Version, 150 Circuits, Pin Length 4.75mm (.187")

Documents:
[Drawing \(PDF\)](#)

[RoHS Certificate of Compliance \(PDF\)](#)

General

Product Family	Backplane Connectors
Series	74058
Application	Backplane
Application Tooling Documents	Tooling Manual
Comments	Keying Postion A
Component Type	PCB Header
Overview	vhdm
Product Name	VHDM®
Style	N/A

Physical

Circuits (Loaded)	150
Circuits (maximum)	150
Color - Resin	Black
Durability (mating cycles max)	200
First Mate / Last Break	No
Guide to Mating Part	Yes
Keying to Mating Part	Yes
Material - Metal	Beryllium Copper, High Performance Alloy (HPA), Stainless Steel
Material - Plating Mating	Gold
Material - Plating Termination	Tin-Lead
Material - Resin	High Temperature Thermoplastic
Number of Columns	N/A
Number of Pairs	Open Pin Field
Number of Rows	6
Orientation	Vertical
PC Tail Length (in)	0.098 In
PC Tail Length (mm)	2.50 mm
PCB Locator	No
PCB Retention	None
PCB Thickness Recommended (in)	0.071 In
PCB Thickness Recommended (mm)	1.80 mm
Packaging Type	Tube
Pitch - Mating Interface (in)	0.079 In
Pitch - Mating Interface (mm)	2.00 mm
Pitch - Term. Interface (in)	0.039 In
Pitch - Term. Interface (mm)	1.00 mm
Plating min: Mating (µin)	30
Plating min: Mating (µm)	0.75
Plating min: Termination (µin)	30
Plating min: Termination (µm)	0.75
Polarized to PCB	Yes
Stackable	No
Surface Mount Compatible (SMC)	Yes




image - Reference only

Series

EU RoHS
Not RoHS Compliant
REACH SVHC
Not Reviewed
Halogen-Free
Status
Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[74058Series](#)

Mates With
74030 VHDM® Board-to-Board
Daughtercard Receptacle

Application Tooling | FAQ
Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global	
Description	Product #
Flat Rock Tooling for Pneumatic Press	0622013700
VHDM® Signal Pin Inserter Repair Tool	0622015700
VHDM® 6 Row Pin and Shield Repair Tool	0622015800
VHDM® 6 Row Shield Extraction Tool	0622016000

Temperature Range - Operating	105°C	VHDM® Insertion	<u>0622020204</u>
Termination Interface: Style	Through Hole - Compliant Pin	Module for Advanced	
Electrical		Mate Signal Header,	
Current - Maximum per Contact	1A	6 Row by 25 Wide,	
Data Rate	3.125 Gbps	50.00mm (1.97")	
Real Signals (per 25mm)	75	VHDM® Insertion	<u>0622020208</u>
Shield Type	Ground Plane Shield	Module for Standard	
Shielded	Yes	Shield Signal	
Voltage - Maximum	120V AC (RMS)/DC	Header, 6 Row by	
		25 Wide, 50.00mm	
		(1.97")	
Material Info			
VHDM and Very High Density Metric are trademarks of Amphenol Corporation			

This document was generated on 05/19/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

M/N
74058-()

-**0*

-**1*

-**2*

-**3*

-**4*


-**5*

-**6*

-**7*

-**8*

KEYING PIN
ORIENTATION




74058

* * * *

NUMBER OF
COLUMN
10 OR 25

CONTACT LOAD
(PIN LENGTH)
1 & 6 = 4.75
2 & 7 = 6.25
3 & 8 = 4.25
4 & 9 = 5.15



PART NUMBER	COLUMN	NUMBER OF SIGNAL PIN	NUMBER OF SHIELD	A MAX	B	M	Au (um) THICKNESS	Sn/Ph (um) THICKNESS
74058-10*1	10	60	10	20.00	18.00	4.75	0.76	0.38-1.25
74058-10*6							1.25	
74058-25*1	25	150	25	50.00	48.00	4.75	0.76	
74058-25*6							1.25	
74058-10*2	10	60	10	20.00	18.00	6.25	0.76	
74058-10*7							1.25	
74058-25*2	25	150	25	50.00	48.00	6.25	0.76	
74058-25*7							1.25	
74058-10*3	10	60	10	20.00	18.00	4.25	0.76	
74058-10*8							1.25	
74058-25*3	25	150	25	50.00	48.00	4.25	0.76	
74058-25*8							1.25	
74058-10*4	10	60	10	20.00	18.00	5.15	0.76	
74058-10*9							1.25	
74058-25*4	25	150	25	50.00	48.00	5.15	0.76	
74058-25*9							1.25	

REVISED
EC NOLDT2001-1270
DRWN:MWANG 01/05/10
CHK:JLAURX 01/05/10
APPR:CBIXLER 01/05/10

DESCRIPTION
MAJOR
CRITICAL

REV

QUALITY SYMBOLS

GENERAL TOLERANCES:
(UNLESS SPECIFIED)

SCALE
2.5:1

DESIGN UNITS
☒mm ☐INCH

DRAWN BY & DATE
MWANG 11/09/98

CHECKED BY & DATE
JLAURX 11/09/98

APPROVED BY & DATE
CBIXLER 11/09/98

CAD FILENAME
SD-74058-002-DGN

DRAFT WHERE APPLICABLE MUST
REMAIN WITHIN DIMENSIONS

DIMENSIONS:
☐mm ☐INCH ☒mm ONLY

SHT
REVISE ON
CAD ONLY

TITLE:
VHDM BACKPLANE 6 ROW
SIGNAL-PIN END SALES DRAWING

MOLEX INCORPORATED

MATERIAL NO.
SEE CHART

DRAWING NO.
SD-74058-002

SHEET NO.
2

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX
INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

SIZE
B

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9