Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



89841 Multi-Conductor - Low Capacitance Computer and Computer P.O.S. Cable



For more Information please call

1-800-Belden1



General Description:

Low cap 24 AWG stranded (7x32) TC conductors, plenum, foam FEP insulation, twisted pairs, overall Beldfoil (100% coverage) + TC braid shield (90% coverage), 24 AWG stranded TC drain wire, FEP jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
1	24	7x32	TC - Tinned Copper

Total Number of Conductors: 2

Insulation

Insulation Material:

Insulation Trade Name	Insulation Material	Wall Thickness (mm)
Teflon®	FFEP - Foam Fluorinated Ethylene Propylene	0.635

Outer Shield

Outer Shield Material:

1	Layer # Outer Shield Trade Name		Type	Outer Shield Material	Coverage (%)
1	1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
ı	2		Braid	TC - Tinned Copper	90

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
24	7x32	TC - Tinned Copper

Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material
Teflon®	FEP - Fluorinated Ethylene Propylene

Overall Cable

Overall Nominal Diameter: 5.131 mm

Pair

Pair Color Code Chart:

Number	Color
1	White/Blue & Blue/White

Mechanical Characteristics (Overall)

Operating Temperature Range:	-70°C To +150°C
UL Temperature Rating:	150°C
Bulk Cable Weight:	40.181 Kg/Km
Max. Recommended Pulling Tension:	203.283 N
Min. Bend Radius/Minor Axis:	57.150 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

Page 1 of 3 12-12-2013

Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



89841 Multi-Conductor - Low Capacitance Computer and Computer P.O.S. Cable

	NEC/(UL) Specification:	CMP
	CEC/C(UL) Specification:	CMP
	EU Directive 2011/65/EU (ROHS II):	Yes
	EU CE Mark:	Yes
	EU Directive 2000/53/EC (ELV):	Yes
	EU Directive 2002/95/EC (RoHS):	Yes
	EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
	EU Directive 2002/96/EC (WEEE):	Yes
	EU Directive 2003/11/EC (BFR):	Yes
	CA Prop 65 (CJ for Wire & Cable):	Yes
	MII Order #39 (China RoHS):	Yes
Fla	me Test	
	UL Flame Test:	NFPA 262
	CSA Flame Test:	FT6
Ple	enum/Non-Plenum	
	Plenum (Y/N):	Yes
	Non-Plenum Number:	9841

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:



Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m) 39.372

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/m) 72.182

Nominal Velocity of Propagation:

VP (%) 76

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km) 78.744

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km) 10.1711

Max. Operating Voltage - UL:

Voltage 300 V RMS

Max. Recommended Current:

Current
4 Amps per conductor @ 25°C

Notes (Overall)

Notes: Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

Put Ups and Colors:

Item # Putup Ship Weight C	Color Notes	Item Desc
----------------------------	-------------	-----------

Page 2 of 3 12-12-2013

Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



89841 Multi-Conductor - Low Capacitance Computer and Computer P.O.S. Cable

89841 0021000	305 MT	13.154 KG	RED	С	1 PR #24 FFEPR SH FEP
89841 002500	152 MT	7.031 KG	RED		1 PR #24 FFEPR SH FEP
89841 0025000	1,524 MT	65.771 KG	RED		1 PR #24 FFEPR SH FEP

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 2 Revision Date: 12-12-2013

© 2013 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

ПОСТАВКА ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru_6 moschip.ru_4 moschip.ru_9