

## Description

Very cost effective design to meet international requirements. No exposed metal parts which are, or could become, current-carrying except for terminals. R-type TO CBE to EN 60934.

- Manual reset, cycling trip free mechanism
- Extremely small and lightweight
- UL, CSA, VDE and EN 60934 (IEC 60934) approved

## Typical applications

Battery chargers, consumer products, power supplies, motors.

## Ordering information

### Type No.

1658 single pole thermal circuit breaker

#### Threadneck design

G21 manual reset type, 3/8"-27 threadneck

A00 auto reset type, without threadneck

#### Hardware

00 no hardware

01 one PAL nut, bulk

02 one PAL nut, one knurled nut, bulk

#### Terminals

P10 blade terminals A6.3-0.8 (QC .250)

P13 blade terminals A6.3-0.8 (QC .250), 90°

#### Current ratings

5...30 A

1658 - G21 - 02 - P10 - 5 A Ordering example

\* Screws and lock washers bulk shipped

## Preferred types

**NEW**

| Preferred types  | Standard current ratings (A) |   |   |   |   |    |    |    |    |    |    |    |
|------------------|------------------------------|---|---|---|---|----|----|----|----|----|----|----|
|                  | 5                            | 6 | 7 | 8 | 9 | 10 | 12 | 15 | 16 | 20 | 25 | 30 |
| 1658-G21-02-P10- | x                            | x | x | x | x | x  | x  | x  | x  | x  | x  | x  |
| 1658-G21-02-P13- | x                            | x | x | x | x | x  | x  | x  | x  |    |    |    |
| 1658-A00-00-P10- | x                            | x | x | x | x | x  | x  | x  | x  |    |    |    |

## Standard current ratings and typical voltage drop values

| Current rating (A) | voltage drop values (mV) | Current rating (A) | voltage drop values (mV) |
|--------------------|--------------------------|--------------------|--------------------------|
| 5                  | ≤ 250                    | 12                 | ≤ 250                    |
| 6                  | ≤ 250                    | 15                 | ≤ 250                    |
| 7                  | ≤ 250                    | 16                 | ≤ 250                    |
| 8                  | ≤ 250                    | 20                 | ≤ 250                    |
| 9                  | ≤ 250                    | 25                 | ≤ 250                    |
| 10                 | ≤ 250                    | 30                 | ≤ 250                    |




1658-...

## Technical data

For further details please see chapter: Technical Information

|                                                                   |                                                                                           |                                                    |                    |                        |
|-------------------------------------------------------------------|-------------------------------------------------------------------------------------------|----------------------------------------------------|--------------------|------------------------|
| Voltage rating                                                    | AC 240 V; DC 28 V                                                                         |                                                    |                    |                        |
| Current ratings                                                   | 5...30 A                                                                                  |                                                    |                    |                        |
| Typical life                                                      |                                                                                           |                                                    |                    |                        |
| AC + DC                                                           | 5...16 A                                                                                  | 1,000 operations at 2 x I <sub>N</sub> , inductive |                    |                        |
|                                                                   | 17...25 A                                                                                 | 1,000 operations at 2 x I <sub>N</sub> , resistive |                    |                        |
| Behaviour at rated switching capacity (EN 60934; test sequence D) | operat.                                                                                   | I <sub>N</sub>                                     | U <sub>N</sub>     |                        |
|                                                                   | 40                                                                                        | 5...16 A                                           | AC 240 V           | 6 x I <sub>N</sub> ind |
|                                                                   | 40                                                                                        | 5...16 A                                           | DC 28 V            | 4 x I <sub>N</sub> ind |
|                                                                   | 40                                                                                        | 17...25 A                                          | AC 240 V           | 120 A resistive        |
|                                                                   | 40                                                                                        | 17...25 A                                          | DC 28 V            | 120 A resistive        |
| Ambient temperature                                               | -20...+60 °C (-4...+140 °F), ≤ 7 A max. +40 °C (+104 °F)                                  |                                                    |                    |                        |
| Insulation co-ordination (IEC 60664 and 60664 A)                  | rated impulse withstand voltage                                                           |                                                    | pollution degree   |                        |
|                                                                   | 2.5 kV                                                                                    |                                                    | 2                  |                        |
|                                                                   | reinforced insulation in operating area                                                   |                                                    |                    |                        |
| Dielectric strength (IEC 60664 and 60664A)                        | test voltage operating area                                                               |                                                    | AC 3,000 V         |                        |
| Insulation resistance                                             | > 100 MΩ (DC 500 V)                                                                       |                                                    |                    |                        |
| Interrupting capacity I <sub>cn</sub>                             | 5...7 A                                                                                   | 180 A                                              |                    |                        |
|                                                                   | 8...30 A                                                                                  | 200 A                                              |                    |                        |
| Interrupting capacity (UL 1077/EN 60934 PC1)                      | I <sub>N</sub>                                                                            | U <sub>N</sub>                                     |                    |                        |
|                                                                   | 5...16 A                                                                                  | AC 240 V                                           | 2,000 A            |                        |
|                                                                   | 5...30 A                                                                                  | AC 120 V                                           | 2,000 A            |                        |
|                                                                   | 5...30 A                                                                                  | DC 32 V                                            | 2,500 A            |                        |
|                                                                   | 5...30 A                                                                                  | DC 28 V                                            | 2,000 A (1658-A..) |                        |
| Degree of protection (IEC 60529/DIN 40050)                        | operating area IP40<br>terminal area IP00                                                 |                                                    |                    |                        |
| Vibration                                                         | 8 g (57-500 Hz) ± 0.61 mm (10-57 Hz), to IEC 60068-2-6, test Fc, 10 frequency cycles/axis |                                                    |                    |                        |
| Shock                                                             | 30 g (11 ms)<br>to IEC 60068-2-27, test Ea                                                |                                                    |                    |                        |
| Corrosion                                                         | 96 hours at 5 % salt mist, to IEC 60068-2-11, test Ka                                     |                                                    |                    |                        |
| Humidity                                                          | 240 hours at 95 % RH<br>to IEC 60068-2-78, test Cab                                       |                                                    |                    |                        |
| Mass                                                              | approx. 16 g                                                                              |                                                    |                    |                        |


## Dimensions



A00




G21 tightening torque max. 0.8 Nm  
3/8-27UNS-2A



See ordering information for mounting hardware.


## Terminal design

P10




blade terminals DIN 46244-A6.3-0.8  
(QC .250)

P13




blade terminals DIN 46244-A6.3-0.8 (QC .250)  
angled 90°


## Installation drawing



## Internal connection diagram



## Typical time/current characteristics




The time/current characteristic curve depends on the ambient temperature prevailing. In order to eliminate nuisance tripping, please multiply the circuit breaker current ratings by the derating factor shown below. See also section Technical information.


| Ambient temp. °F           | -4   | +14  | +32  | +73.4 | +104 | +122 | +140 |
|----------------------------|------|------|------|-------|------|------|------|
| Ambient temp. °C           | -20  | -10  | 0    | +23   | +40  | +50  | +60  |
| Derating factor $I_N > 7A$ | 0.83 | 0.85 | 0.9  | 1     | 1.1  | 1.18 | 1.25 |
| $I_N < 7A$                 | 0.74 | 0.76 | 0.82 | 1     | 1.23 | -    | -    |

## Accessories


**Mounting nut 3/8", 27-thread**  
Y 306 671 01




**Knurled nut 3/8", 27-thread  
plastic (standard)**  
Y 307 117 02




**Knurled nut 3/8", 27-thread  
nickel-plated brass**  
Y 300 190 03




**Hex nut 3/8", 27-thread  
nickel-plated brass**  
Y 300 192 01




**Press to Reset Plate for 3/8"  
thread, aluminium**  
Y 301 059 02



**Reset button seal for 3/8", 27-thread,  
short**  
X 201 285 01




**long**  
X 200 799 01



## Panel cut out

**1658-3/8-27 UNS-2A**



## Approvals

| Authority      | Voltage ratings                                        | Current ratings                                                                                        |
|----------------|--------------------------------------------------------|--------------------------------------------------------------------------------------------------------|
| VDE (EN 60934) | AC 240 V; DC 28 V                                      | 5...25 A                                                                                               |
| UL             | AC 240 V<br>AC 120 V<br>AC 120 V<br>DC 32 V<br>DC 28 V | 5...16 A 1658-G..<br>18...30 A 1658-G..<br>5...30 A 1658-A..<br>5...30 A 1658-G..<br>5...30 A 1658-A.. |

This is a metric design and millimeter dimensions take precedence  $\left(\frac{\text{mm}}{\text{inch}}\right)$

All dimensions without tolerances are for reference only. In the interest of improved design, performance and cost effectiveness the right to make changes in these specifications without notice is reserved. Product markings may not be exactly as the ordering codes. Errors and omissions excepted.



## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9