



**Product:** [7939A](#) 

DataTuff® 5e, 4 Bonded-Pr #24 Str BC, PO Ins, OS, PVC Jkt, CMX-Outdoor CMR

 [Request Sample](#)

**Product Description**

Industrial Ethernet Cat 5e, 4 Bonded-Pair 24AWG (7x32) Bare Copper, PO Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CMX-Outdoor CMR

**Technical Specifications**

**Product Overview**

|                        |                                                                                                                   |
|------------------------|-------------------------------------------------------------------------------------------------------------------|
| Suitable Applications: | outdoor, harsh environment, IIoT, factory or process automation, IP cameras and devices, data communication, etc. |
|------------------------|-------------------------------------------------------------------------------------------------------------------|

**Physical Characteristics (Overall)**

**Conductor**

| AWG | Stranding | Material         | No. of Pairs |
|-----|-----------|------------------|--------------|
| 24  | 7x32      | BC - Bare Copper | 4            |

|                        |   |
|------------------------|---|
| Conductor Count:       | 8 |
| Total Number of Pairs: | 4 |

**Insulation**

| Material     |     |
|--------------|-----|
| Polyolefin   |     |
| Bonded-Pair: | Yes |

**Color Chart**

| Number | Color                          |
|--------|--------------------------------|
| 1      | White/Blue Stripe and Blue     |
| 2      | White/Orange Stripe and Orange |
| 3      | White/Green Stripe and Green   |
| 4      | White/Brown Stripe and Brown   |

**Outer Shield Material**

| Type | Material    | Material Trade Name | Coverage [%] | Drainwire Material | Drainwire AWG | Drainwire Construction n x D |
|------|-------------|---------------------|--------------|--------------------|---------------|------------------------------|
| Tape | Alum / Poly | Beldfoil®           | 100%         | TC - Tinned Copper | 24            | 7x32                         |

**Outer Jacket Material**

| Material                 | Nominal Diameter | Nominal Wall Thickness | Ripcord | Separator Material |
|--------------------------|------------------|------------------------|---------|--------------------|
| PVC - Polyvinyl Chloride | 0.295 in         | 0.03 in                | No      | Polyester          |

**Electrical Characteristics**

**Conductor DCR**

| Max. Conductor DCR | Max. DCR Unbalance |
|--------------------|--------------------|
| 9.38 Ohm/1000ft    | 3 %                |

**Capacitance**

| Max. Capacitance Unbalance | Nom.Mutual Capacitance |
|----------------------------|------------------------|
| 330 pF/ft                  | 15 pF/ft               |

**Delay**

| Max. Delay  | Max. Delay Skew | Nominal Velocity of Propagation (VP) [%] | Typical Delay Skew |
|-------------|-----------------|------------------------------------------|--------------------|
| 510 ns/100m | 45 ns/100m      | 69%                                      | 12 ns/ft           |

High Freq

| Frequency [MHz] | Max. Insertion Loss (Attenuation) | Min. NEXT [dB] | Min. PSNEXT [dB] | Min. ACR [dB] | Min. PSACR [dB] | Min. ACRF (ELFEXT) [dB] | Min. PSACRF (PSELFEXT) [dB] | Min. RL (Return Loss) [dB] | Min. SRL (Structural Return Loss) | Max./Min. Input Impedance (unFitted) | Max./Min. Fitted Impedance |
|-----------------|-----------------------------------|----------------|------------------|---------------|-----------------|-------------------------|-----------------------------|----------------------------|-----------------------------------|--------------------------------------|----------------------------|
| 1 MHz           | 2.5 dB/100m                       | 65.3 dB        | 62.3 dB          | 62.8 dB       | 59.8 dB         | 63.8 dB                 | 60.8 dB                     | 20 dB                      | 23 dB                             | 100 ± 15 Ohm                         | 100 ± 15 Ohm               |
| 4 MHz           | 4.9 dB/100m                       | 56.3 dB        | 53.3 dB          | 51.4 dB       | 48.4 dB         | 51.7 dB                 | 48.7 dB                     | 23 dB                      | 23 dB                             | 100 ± 15 Ohm                         | 100 ± 15                   |
| 8 MHz           | 6.9 dB/100m                       | 51.8 dB        | 48.8 dB          | 44.9 dB       | 41.9 dB         | 45.7 dB                 | 42.7 dB                     | 24.5 dB                    | 24.5 dB                           | 100 ± 15 Ohm                         | 100 ± 15                   |
| 10 MHz          | 7.8 dB/100m                       | 50.3 dB        | 47.3 dB          | 42.5 dB       | 39.5 dB         | 43.8 dB                 | 40.8 dB                     | 25 dB                      | 25 dB                             | 100 ± 15 Ohm                         | 100 ± 15                   |
| 16 MHz          | 9.9 dB/100m                       | 47.3 dB        | 44.3 dB          | 37.4 dB       | 34.4 dB         | 39.7 dB                 | 36.7 dB                     | 25 dB                      | 25 dB                             | 100 ± 15 Ohm                         | 100 ± 15                   |
| 20 MHz          | 11.1 dB/100m                      | 45.8 dB        | 42.8 dB          | 34.7 dB       | 31.7 dB         | 37.7 dB                 | 34.7 dB                     | 25 dB                      | 25 dB                             | 100 ± 15 Ohm                         | 100 ± 15                   |
| 25 MHz          | 12.5 dB/100m                      | 44.3 dB        | 41.3 dB          | 21.8 dB       | 28.8 dB         | 35.8 dB                 | 32.8 dB                     | 24.3 dB                    | 24.3 dB                           | 100 ± 15 Ohm                         | 100 ± 15                   |
| 31.25 MHz       | 14.1 dB/100m                      | 42.9 dB        | 39.9 dB          | 28.8 dB       | 25.8 dB         | 33.9 dB                 | 30.9 dB                     | 23.6 dB                    | 23.6 dB                           | 100 ± 15 Ohm                         | 100 ± 15                   |
| 62.5 MHz        | 20.4 dB/100m                      | 38.4 dB        | 35.4 dB          | 18 dB         | 15 dB           | 27.8 dB                 | 24.8 dB                     | 21.5 dB                    | 21.5 dB                           | 100 ± 15 Ohm                         | 100 ± 15                   |
| 100 MHz         | 26.4 dB/100m                      | 35.3 dB        | 32.3 dB          | 8.9 dB        | 5.9 dB          | 23.8 dB                 | 20.8 dB                     | 20.1 dB                    | 20.1 dB                           | 100 ± 15 Ohm                         |                            |

Voltage

| UL Voltage Rating |
|-------------------|
| 300 V RMS         |

Temperature Range

|                          |                |
|--------------------------|----------------|
| Installation Temp Range: | -25°C To +75°C |
| UL Temp Rating:          | 60°C           |
| Operating Temp Range:    | -40°C To +75°C |

Mechanical Characteristics

|                             |               |
|-----------------------------|---------------|
| Bulk Cable Weight:          | 35 lbs/1000ft |
| Max. Pull Tension:          | 40 lbs        |
| Min Bend Radius/Minor Axis: | 0.6 in        |

Standards

|                       |                                             |
|-----------------------|---------------------------------------------|
| NEC/(UL) Compliance:  | CMR, CMX-Outdoor, UL 444                    |
| CEC/C(UL) Compliance: | CMG                                         |
| IEC Compliance:       | ISO/IEC 11801 Cat 5e Patch                  |
| CPR Euroclass:        | Eca                                         |
| Data Category:        | Category 5e                                 |
| ANSI Compliance:      | ICEA 661                                    |
| TIA/EIA Compliance:   | TIA-568.C.2 Category 5e Patch, NEMA WC-63.1 |

Applicable Environmental and Other Programs

|                                       |                               |
|---------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV):        | Yes                           |
| EU Directive 2003/11/EC (BFR):        | Yes                           |
| EU Directive 2011/65/EU (ROHS II):    | Yes                           |
| EU Directive 2012/19/EU (WEEE):       | Yes                           |
| EU Directive 2015/863/EU:             | Yes                           |
| EU Directive Compliance:              | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                           | Yes                           |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2004-01-04                    |
| MII Order #39 (China RoHS):           | Yes                           |

Suitability

|                                    |     |
|------------------------------------|-----|
| Suitability - Indoor:              | Yes |
| Suitability - Oil Resistance:      | Yes |
| Suitability - Outdoor:             | Yes |
| Suitability - Sunlight Resistance: | Yes |

Flammability, LSOH, Toxicity Testing

|                  |              |
|------------------|--------------|
| UL Flammability: | UL1666 Riser |
|------------------|--------------|

|                    |               |
|--------------------|---------------|
| CSA Flammability:  | FT4           |
| IEC Flammability:  | IEC 60332-1-2 |
| UL voltage rating: | 300 V RMS     |

Plenum/Non-Plenum

|               |    |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Part Number

Variants

| Item #        | Color | Putup Type | Length   | UPC          |
|---------------|-------|------------|----------|--------------|
| 7939A 0101000 | Black | Reel       | 1,000 ft | 612825191773 |
| 7939A 0102000 | Black | Reel       | 2,000 ft | 612825191780 |
| 7939A 0061000 | Blue  | Reel       | 1,000 ft | 612825191759 |
| 7939A 0081000 | Gray  | Reel       | 1,000 ft | 612825191766 |
| 7939A 0021000 | Red   | Reel       | 1,000 ft | 612825191742 |
| 7939A 1NH1000 | Teal  | Reel       | 1,000 ft | 612825191797 |

|           |                                                                                                 |
|-----------|-------------------------------------------------------------------------------------------------|
| Footnote: | C - CRATE REEL PUT-UP.                                                                          |
| Patent:   | <a href="https://www.belden.com/resources/patents">https://www.belden.com/resources/patents</a> |

Product Notes

|        |                                                                                                  |
|--------|--------------------------------------------------------------------------------------------------|
| Notes: | Operating temperatures are subject to length de-rating. Cable passes -40C Cold Bend per UL 1581. |
|--------|--------------------------------------------------------------------------------------------------|

History

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.311 Revision Date: 04-28-2020 |
|----------------------|--------------------------------------------------|

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9